



DataTwist® 6 U/UTP Cables

TIA/EIA-568-B.2, Category 6,
 Non-Bonded-Pair Cables

De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Freq. MHz	Max. Atten. dB/100m	Min. PSUM			Input Imp. (Ω)	Min. RL dB
			ft.	m	lbs.	kg		inch	mm		inch	mm			NEXT dB	ACR dB/100m	ELFEXT dB/100m		
Cat 6 • 23 AWG • Unbonded-Pair • Solid 0.6 mm Bare Copper • Twisted Pair																			
Polyolefin Insulation • PVC Jacket (Grey and Blue)																			
 4-Pair	7965E		B-328	B-100	9.5	4.3	0.57 mm 23 AWG Solid BC	0.040	1.01	Non- Bonded-Pair Unshielded U/UTP	0.244	6.20	1	2.1	72.0	70.2	65.0	100 ± 15	20.0
			U-1000	U-305	28.9	13.1							4	3.8	63.0	59.4	53.0	100 ± 15	23.0
			1000	305	28.9	13.1							10	6.0	57.0	51.3	45.0	100 ± 15	25.0
			1640	500	47.4	21.5							16	7.6	54.0	46.6	41.0	100 ± 15	25.0
			3280	1000	94.8	43.0							20	8.5	53.0	44.3	39.0	100 ± 15	25.0
													25	9.6	51.0	41.8	37.0	100 ± 15	24.3
													31.25	10.7	50.0	39.1	35.0	100 ± 15	23.6
													62.5	15.5	45.0	29.9	29.0	100 ± 15	21.5
													100	19.9	42.0	22.4	25.0	100 ± 15	20.1
													155	25.3	39.0	14.1	21.0	100 ± 22	18.8
				200	29.1	38.0	8.6	19.0	100 ± 22	18.0									
				250	33.0	36.0	3.3	17.0	100 ± 22	17.3									

Color Code: see chart below
 305 m, 500 m and 1000 m put-up available in Blue only.

Applicable industry standards: EN 50173, ISO/IEC 11801, TIA/EIA 568-B2

Polyolefin Insulation • FRNC/LSNH Jacket (Grey or Blue)																			
 4-Pair	7965ENH		B-328	B-100	9.5	4.3	0.57 mm 23 AWG Solid BC	0.040	1.01	Non- Bonded-Pair Unshielded U/UTP	0.244	6.20	see above						
			1000	305	28.9	13.1													
			1640	500	47.4	21.5													
			3280	1000	94.8	43.0													
			Color Code: see chart below																
			Applicable industry standards: EN 50173, ISO/IEC 11801, TIA/EIA 568-B2 Burning Energy: 478 kJ/m																

BC = Bare Copper • ACR = Attenuation Crosstalk Ratio • ELFEXT = Equal Level Far-end Crosstalk • NEXT = Near-end Crosstalk • PSUM = Power Sum • RL = Return Loss • DCR = DC resistance

Color Code

Pair No.	Color
1	White/Blue Stripe, Blue
2	White/Orange Stripe, Orange
3	White/Green Stripe, Green
4	White/Brown Stripe, Brown