





Speaker Cables



De-scription	Part No.	UL NEC / C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Shielding Material	Nominal OD		Component	Description	Shielding Material & Nom. DCR	Insulation Material & Colors	Component Jacket Material & Colors	Component OD	
			ft.	m	lbs.	kg		inch	mm						inch	mm
26 AWG • 2 CDR (Audio) Stranded (18x0.1) 0.5 mm BC + 3 CDR (Power) Stranded (32x0.2) 1.2 mm BC • Conductors Cabled with Fillers																
Polyethylene Insulation • Overall Matte Black PVC Jacket																
300V RMS 60°C	BE43908		328	100	37.5	17.0	Unshielded	0.461	11.7	1xAudio	1-Pair 26 AWG 0.48 mm (18x0.1) BC	Overall 90% BC Braid	PE Black Red	PVC Black	0.044	1.12
			1640	500	187.4	85.0					1xPower				3 Conductors 18 AWG 1.15 mm (32x0.2) BC	Unshielded
 <p>2x0.14 mm² (Audio) 3x1.20 mm² (Power)</p> <p>Pulling Tension: 200 N</p>																

De-scription	Part No.	UL NEC / C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Color Code	
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m		
16 AWG • 2 Conductor • Stranded (25x0.23) 1.5 mm Bare Copper																		
PVC Insulation • Overall Matte Black PVC Jacket (Grey or Black)																		
300V RMS 60°C	BE46382 2 CDR		328	100	15.9	7.2	1.5 mm	0.098	2.50	Unshielded	0.276	7.00	12	-	CDR/CDR	35	115	Black, Red
			1640	500	79.8	36.2	16 AWG											
			3280	1000	159.4	72.3	(25x0.23) BC											
 <p>2x1.5 mm²</p> <p>1000 m put-up available in Black only. Pulling Tension: 240 N</p>																		

14 AWG • 4 or 8 Conductor • Stranded (104x34) 1.9 mm Bare Copper • Conductors Cabled with Fillers • Paper Wrap																		
PVC Insulation • Overall Matte Black PVC Jacket																		
300V RMS 60°C	1810A 4 CDR		250	76	26.3	11.9	1.85 mm	0.025	0.64	Unshielded	0.390	9.91	8.8	-	CDR/CDR CDR/SCR	19 57	61 187	Red, Green, White, Black
			500	152	55.5	25.2	14 AWG											
			1000	305	114.0	51.7	(104x34) BC											
 <p>High-Flex 4x2.1 mm²</p> <p>Compatible with Speakon® connectors. Pulling Tension: 889 N</p>																		
PVC Insulation • Overall Matte Black PVC Jacket																		
300V RMS 60°C	1811A 8 CDR		1000	305	205.0	93.0	1.85 mm	0.025	0.64	Unshielded	0.515	13.08	8.8	-	CDR/CDR CDR/SCR	19 57	61 187	Brown, Red, Orange, Yellow, Green, White, Blue, Black
							14 AWG (104x34) BC											
 <p>8x2.1 mm²</p> <p>Compatible with Speakon® connectors. Pulling Tension: 1779 N</p>																		

BC = Bare Copper • PE = Polyethylene • DCR = DC resistance • SCR = Capacitance between one conductor and other conductors connected to shield. • CDR = Capacitance between conductors

Speakon® is a Neutrik trademark.

Speaker Cables



De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	

13 AWG • 2 Conductor • Stranded (50x0.25) 2.1 mm Bare Copper**PVC Insulation • Overall Matte PVC Jacket** (Grey or Black)

300V RMS 60°C	BE46381 2 CDR		328	100	22.5	10.2	2.05 mm 13 AWG (50x0.25) BC	0.114	2.90	Unshielded	0.317	8.05	7.4	–	CDR/CDR	40	131	Black, Red
------------------	-------------------------	--	-----	-----	------	------	-----------------------------------	-------	------	------------	-------	------	-----	---	---------	----	-----	------------

2x2.5 mm²

1000 m put-up available in Black only.
Pulling Tension: 400 N

13 AWG • 4 Conductor • Stranded (50x0.25) 2.1 mm Bare Copper • Conductors Cabled with Fillers • Paper Wrap**PVC Insulation • Overall Matte Black PVC Jacket**


300V RMS 60°C	BE46379 4 CDR		3280	1000	399.5	181.2	2.05 mm 13 AWG (50x0.25) BC	0.114	2.90	Unshielded	0.394	10.00	7.4	–	CDR/CDR	40	131	Red, Green, White, Black
------------------	-------------------------	--	------	------	-------	-------	-----------------------------------	-------	------	------------	-------	-------	-----	---	---------	----	-----	-----------------------------

4x2.5 mm²

Pulling Tension: 200 N

13 AWG • 8 Conductor • Stranded (300x0.1) 2.1 mm Bare Copper • Conductors Cabled with Fillers • Paper Wrap**PVC Insulation • Overall Matte Black PVC Jacket**

300V RMS 60°C	BE43907 8 CDR		820	250	160.5	72.8	2.05 mm 13 AWG (300x0.1) BC	0.114	2.90	Unshielded	0.488	12.40	7.4	–	CDR/CDR	40	131	Red, Green, White, Black, Yellow, Purple, Brown, Blue
------------------	-------------------------	--	-----	-----	-------	------	-----------------------------------	-------	------	------------	-------	-------	-----	---	---------	----	-----	----------------------------------------------------------------------

8x2.5 mm²

Pulling Tension: 1500 N

11 AWG • 2 Conductor • Stranded (56x0.3) 2.6 mm Bare Copper**PVC Insulation • Overall Matte PVC Jacket** (Grey or Black)

300V RMS 60°C	BE46380 2 CDR		328	100	31.5	14.3	2.6 mm 11 AWG (56x0.3) BC	0.138	3.50	Unshielded	0.354	9.00	4.5	–	CDR/CDR	35	116	Black, Red
------------------	-------------------------	--	-----	-----	------	------	---------------------------------	-------	------	------------	-------	------	-----	---	---------	----	-----	------------

2x4.0 mm²

500 m put-up available in Grey only.
Pulling Tension: 600 N

BC = Bare Copper • DCR = DC resistance • SCR = Capacitance between one conductor and other conductors connected to shield. • CDR = Capacitance between conductors