





Security Composite Cables

CCTV Plus Audio or Pan and Tilt CCTV Control Applications



| De- scription | Part No. | UL NEC/ C(UL)CEC Type IEC | Standard Lengths | | Standard Unit Weight | | Shielding Material | Nominal OD | | Compo- nent | Description | Shielding Material & Nom. DCR | Insulation Material & Colors | Component Jacket Material & Colors | Component Insulation OD | |
|---|-------------|---------------------------------|---------------------|-----|-------------------------|------|-----------------------|------------|------|----------------|---|--|------------------------------------|---|----------------------------|------|
| | | | ft. | m | lbs. | kg | | inch | mm | | | | | | inch | mm |
| Composite • (2) Conductor 26 AWG • (1) Coax Solid 0.4 mm Bare Copper • Alu Triplex/Duplex • 72% Tinned Copper Braid | | | | | | | | | | | | | | | | |
| PVC Insulation (Conductors) • Gas-Injected PE Insulation (Coax) • Grey PVC Jacket | | | | | | | | | | | | | | | | |
| | SEC0001 | | 328 | 100 | 11.7 | 5.3 | Unshielded | 0.252 | 6.40 | 1xData | 2 Conductor 26 AWG 0.50 mm (16x0.193) BC | Unshielded | PVC 1.90 mm | PVC | 0.062 | 1.57 |
|  | | | | | | | | | | 1xCoax | 21 AWG 0.41 mm Solid BC | Alu Triplex/Duplex 72% TC Braid | Foam Polyethylene | PVC | 0.142 | 3.60 |
| Composite • (2) Conductor 16 AWG • (1) Coax Solid 0.8 mm BC • Alu Triplex/Duplex • 55% Tinned Copper Braid • (2) Conductor 26 AWG | | | | | | | | | | | | | | | | |
| PVC Insulation (Conductors) • Gas-Injected PE Insulation (Coax) • Grey PVC Jacket | | | | | | | | | | | | | | | | |
| | SEC0002 | | 328 | 100 | 29.8 | 13.5 | Unshielded | 0.315 | 8.00 | 1xData | 2 Conductor 16 AWG 1.50 mm (30x0.25) BC | Unshielded | PE 3.50 mm | PVC | 0.101 | 2.56 |
|  | | | | | | | | | | 1xCoax | 20 AWG 0.81 mm Solid BC | Alu Triplex/Duplex 55% TC Braid | Foam Polyethylene | PVC | 0.142 | 3.60 |
| | | | | | | | | | | 1xControl | 2 Conductor 26 AWG 0.50 mm (16x0.20) BC | Unshielded | PE 3.50 mm | PVC | 0.062 | 1.57 |
| Composite • (2) Conductor 20 AWG • (1) Coax Solid 0.4 mm Bare Copper • Alu Triplex/Duplex • 72% Tinned Copper Braid | | | | | | | | | | | | | | | | |
| PVC Insulation (Conductors) • Gas-Injected PE Insulation (Coax) • Grey PVC Jacket | | | | | | | | | | | | | | | | |
| | SEC0003 | | 328 | 100 | 14.8 | 6.7 | Unshielded | 0.291 | 7.40 | 1xData | 2 Conductor 20 AWG 1.00 mm (32x0.20) BC | Unshielded | PVC 1.90 mm | PVC | 0.085 | 2.17 |
|  | | | | | | | | | | 1xCoax | 26 AWG 0.41 mm Solid BC | Alu Triplex/Duplex 72% TC Braid | Foam Polyethylene | PVC | 0.142 | 3.60 |
| Composite • (2) Conductor 24 AWG • (1) Coax Solid 0.4 mm BC • Alu Triplex/Duplex • 72% Tinned Copper Braid • (2) Conductor 26 AWG | | | | | | | | | | | | | | | | |
| PVC Insulation (Conductors) • Gas-Injected PE Insulation (Coax) • Grey PVC Jacket | | | | | | | | | | | | | | | | |
| | SEC0004 | | 328 | 100 | 13.4 | 6.1 | Unshielded | 0.260 | 6.60 | 1xData | 2 Conductor 24 AWG 0.22 mm (30x0.25) BC | Unshielded | PVC 1.90 mm | PVC | 0.045 | 1.15 |
|  | | | | | | | | | | 1xCoax | 26 AWG 0.41 mm Solid BC | Alu Triplex/Duplex 72% TC Braid | Foam Polyethylene | PVC | 0.142 | 3.60 |
| | | | | | | | | | | 1xControl | 2 Conductor 26 AWG 0.50 mm (16x0.20) BC | Unshielded | PE 3.50 mm | PVC | 0.062 | 1.57 |

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance