




### Security Composite Cables

#### Banana Peel® Access Control Composite Cables Jacketless



De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Shielding Material	Nominal OD		Compo- nent	Description	Shielding Material & Nom. DCR	Insulation Material & Colors	Component Jacket Material & Colors	Component OD	
			ft.	m	lbs.	kg		inch	mm						inch	mm

Composite • **4 CDR Beldfoil®** 18 AWG 1.22 mm • **3 Pair Beldfoil®** 22 AWG 0.8 mm • **2 CDR Beldfoil®** 22 AWG 0.8 mm • **4 CDR Beldfoil®** 22 AWG 0.8 mm • **Banana Peel®** Unjacketed, Bonded Central Spline

PVC Insulation (Pairs) • Foam Insulation (Coax) • Black PVC Jacket																	
 Kötter approved	300V 75°C	<b>558AFS</b>	NEC: CMR CEC: CMG	500 1000	152 305	58.4 108.0	26.5 49.0	White, Black, Red, Green	0.448	11.38	Lock Power	4-Conductor 18 AWG 1.22 mm (7x26) BC	Overall Beldfoil®	PVC 2.89 mm	PVC Grey	0.202	5.13
								White & Green, Orange & Brown, Red & Black			Card Reader	3-Pair 22 AWG 0.76 mm (7x30) BC	Overall Beldfoil®	PVC 1.25 mm	PVC Orange	0.233	5.92
								Black, Red			Door Contact	2-Conductor 22 AWG 0.76 mm (7x30) BC	Overall Beldfoil®	PVC 2.00 mm	PVC White	0.140	3.56
								White, Black, Red, Green			Rex/ Spare	4-Conductor 22 AWG 0.76 mm (7x30) BC	Overall Beldfoil®	PVC 2.00 mm	PVC Blue	0.161	4.09

BC = Bare Copper • DCR = DC resistance

20 • New Generation® Cables