

## Fire Alarm Cables

Commercial Applications  
Power-Limited Unshielded




De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

**22 AWG** • Solid 0.6 mm Bare Copper • Numbered and Color Coded • Rip Cord

**Polyethylene Insulation • Red FRNC/LSNH Jacket**

300V 75°C	IEC 60754-2						1.02 mm 18 AWG Solid BC	0.068	1.72	Unshielded		see chart below	
--------------	-------------	--	--	--	--	--	-------------------------------	-------	------	------------	--	-----------------	--



Rip Cord

Part No.	UL NEC / C(UL)/CEC Type IEC	Standard Lengths (ft. / m)	Standard Unit Weight (lbs. / kg)	Conductor (Stranding) Diameter (mm)	Nominal Insulation OD (inch / mm)	Nominal OD (inch / mm)
4322UL	4 CDR	328 / 100 1640 / 500	9.3 / 4.2 46.3 / 21.0	1.02	0.068 / 1.72	0.177 / 4.50
4324UL	6 CDR	328 / 100 1640 / 500	13.0 / 5.9 65.0 / 29.5	1.02	0.068 / 1.72	0.213 / 5.40

BC = Bare Copper • DCR = DC resistance

### Color Code

Cond. No.	Color	Cond. No.	Color
1	Black	4	Blue
2	Red	5	Orange
3	Brown	6	Yellow