

Fire Alarm Cables

Commercial Applications
Power-Limited Unshielded



De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm	

12 AWG • Solid 2.1 mm Bare Copper • Numbered and Color Coded • Rip Cord

PVC Insulation • Red PVC Jacket

300V 75°C	5020UL	NEC: FPLR CEC: CMG FT4	1000	305	55.1	25.0	2.05 mm 12 AWG Solid BC	0.094	2.38	Unshielded	0.247	6.27	Black, Red
--------------	---------------	---------------------------------	------	-----	------	------	-------------------------------	-------	------	------------	-------	------	------------




Rip Cord

2 CDR

Polyethylene Insulation • Red FRNC/LSNH Jacket

300V 70°C	4020UL	IEC 60754-2	1640	500	85.3	38.7	2.05 mm 12 AWG Solid BC	0.107	2.72	Unshielded	0.248	6.30	Black, Red
--------------	---------------	----------------	------	-----	------	------	-------------------------------	-------	------	------------	-------	------	------------



Rip Cord

2 CDR

BC = Bare Copper • DCR = DC resistance

20 • New Generation® Cables