



# Home Cinema Audio Cables

## High-Conductivity (Oxygen-Free) Copper Speaker Cables

De-scription	Part No.	UL NEC / C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Insulation OD		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Color Code
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	

**Low Cap • 14 AWG • Stranded (105x34) 1.9 mm Oxygen-Free High-Conductivity Bare Copper • Conductors Cabled**

**Polyolefin Insulation • PVC Jacket (Green, Blue, Grey, White and Black)**

<b>1309A</b>	NEC:	U-500	U-152	22.5	10.2	1.85 mm	0.015	0.39	Unshielded	0.264	6.71	-	-	CDR/CDR	20.5	67.3	Black, Red	
	CMR, CL3R	2000	610	46.1	20.9	14 AWG												
	CEC:																	(105x34) BC
	CMG FT4																	



2 CDR  
2x2.1 mm<sup>2</sup>

For audio use only.  
305 m put-ups not available in Blue or Green.  
Suitable for direct burial applications.  
White and Black jackets are sunlight-resistant.

Brightly colored jackets for easy identification.  
Print legends that incorporate location information (room 12345, zone ABCDE).  
Cable jackets with ascending/descending sequential markings at 0.6 m intervals.  
Extremely flexible, easy-to-pull constructions (highly stranded conductors; PVC jackets)

**Polyolefin Insulation • PVC Jacket (Green, Blue, Grey, White and Black)**

<b>1310A</b>	NEC:	500	152	41.4	18.8	1.85 mm	0.015	0.39	Unshielded	0.319	8.10	-	-	CDR/CDR	20.5	67.3	Black, Red	
	CMR, CL3R	1000	305	84.0	38.1	14 AWG												
	CEC:																	(105x34) BC
	CMG FT4																	



4 CDR  
4x2.1 mm<sup>2</sup>

For audio use only.  
305 m put-ups not available in Blue or Green.  
Suitable for direct burial applications.  
White and Black jackets are sunlight-resistant.

Brightly colored jackets for easy identification.  
Print legends that incorporate location information (room 12345, zone ABCDE).  
Cable jackets with ascending/descending sequential markings at 0.6 m intervals.  
Extremely flexible, easy-to-pull constructions (highly stranded conductors; PVC jackets)

**Low Cap • 12 AWG • Stranded (165x34) 2.4 mm Oxygen-Free High-Conductivity Bare Copper • Conductors Cabled**

**Polyolefin Insulation • PVC Jacket (Grey, White and Black)**

<b>1311A</b>	NEC:	U-500	U-152	36.6	16.6	2.41 mm	0.018	0.46	Unshielded	0.352	8.94	-	-	CDR/CDR	22.3	73.2	Black, Red
	CMR, CL3R	500	152	36.6	16.6	12 AWG											
	CEC:	1000	305	74.1	33.6	(165x34) BC											
	CMG FT 4																



2 CDR  
2x3.2 mm<sup>2</sup>

For audio use only.  
305 m put-ups not available in Blue or Green.  
Suitable for direct burial applications.  
White and Black jackets are sunlight-resistant.

Brightly colored jackets for easy identification.  
Print legends that incorporate location information (room 12345, zone ABCDE).  
Cable jackets with ascending/descending sequential markings at 0.6 m intervals.  
Extremely flexible, easy-to-pull constructions (highly stranded conductors; PVC jackets)

**Polyolefin Insulation • PVC Jacket (Grey, White and Black)**

<b>1312A</b>	NEC:	500	152	66.6	30.2	2.41 mm	0.018	0.46	Unshielded	0.423	10.74	-	-	CDR/CDR	22.3	73.2	Black, Red	
	CMR, CL3R	1000	305	132.1	59.9	12 AWG												
	CEC:																	(165x34) BC
	CMG FT 4																	



4 CDR  
4x3.2 mm<sup>2</sup>

For audio use only.  
305 m put-ups not available in Blue or Green.  
Suitable for direct burial applications.  
White and Black jackets are sunlight-resistant.

Brightly colored jackets for easy identification.  
Print legends that incorporate location information (room 12345, zone ABCDE).  
Cable jackets with ascending/descending sequential markings at 0.6 m intervals.  
Extremely flexible, easy-to-pull constructions (highly stranded conductors; PVC jackets)

**Low Cap • 10 AWG • Stranded (259x34) 3.0 mm Oxygen-Free High-Conductivity Bare Copper • Conductors Cabled**

**Polyolefin Insulation • PVC Jacket (Grey, White and Black)**

<b>1313A</b>	NEC:	500	152	55.1	25.0	2.97 mm	0.026	0.66	Unshielded	0.428	10.87	-	-	CDR/CDR	23.2	76.1	Black, Red	
	CMR, CL3R	1000	305	109.1	49.5	10 AWG												
	CEC:																	(259x34) BC
	CMG FT 4																	



2 CDR  
2x5.2 mm<sup>2</sup>

For audio use only.  
305 m put-ups not available in Blue or Green.  
Suitable for direct burial applications.  
White and Black jackets are sunlight-resistant.

Brightly colored jackets for easy identification.  
Print legends that incorporate location information (room 12345, zone ABCDE).  
Cable jackets with ascending/descending sequential markings at 0.6 m intervals.  
Extremely flexible, easy-to-pull constructions (highly stranded conductors; PVC jackets)

TC = Tinned Copper • BC = Bare Copper • DCR = DC resistance • CDR = Capacitance between conductors