

## Tools and Accessories

### For Mini Hi-Res Coaxial Cables




De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Pieces		Standard Unit Weight		AWG of Cable	Cable Reten- tion Force		Body Material/ Plating	Center Pin Retention		Nom. Imp. (Ω)	Current Rating	Insertion Loss
			Carton	Box	lbs.	kg		> lbs.	> kg		inch	mm			

**One-Piece-Connector • Male BNC • 25 AWG (Mini RG-59) • 2-stud Bayonet Lock • Solid, One-Piece-Brass with Gold-Plated Center Pins • Patent Pending Viewing Window**

**Gold-Plated Construction**

300V RMS	1B25A		*100	10	3.8	1.7	25 AWG	40.0	18.1	Nickel Brass Compression Gold-Plated Center Pin ( > 0.01 mm Gold on Beryllium Cu)	0.331	0.150	75	5 amp	< 0.1 dB @ 1 GHz
----------	-------	--	------	----	-----	-----	--------	------	------	--	-------	-------	----	-------	------------------



\* Stand packages cannot be broken.  
Including termination instructions.


Return loss at 5-1000 MHz: ≥ 20 dB  
RFI: > 100 dB

Frequency Range: DC-3.0 GHz (dependent upon cable limitations)  
Can be used with video multicores 127xR and 1281Sx.

**One-Piece-Connector • RCA • 25 AWG (Mini RG-59) • Solid, One-Piece-Brass with Gold-Plated Center Pins • Patent Pending Viewing Window**

**Gold-Plated Construction**

300V RMS	1R25A		*100	10	3.3	1.5	25 AWG	40.0	18.1	Nickel Brass Compression Gold-Plated Center Pin	0.331	0.150	N/A	2 amp	< 0.1 dB @ 1 GHz
----------	-------	--	------	----	-----	-----	--------	------	------	--	-------	-------	-----	-------	------------------



\* Stand packages cannot be broken.  
Including termination instructions.

Return loss at 5-1000 MHz: ≥ 20 dB

Frequency Range: DC-3.0 GHz (dependent upon cable limitations)  
Can be used with video multicores 127xR and 1281Sx.

**Stripping Tool • 3-Cut • 25 AWG (Mini RG-59)**

**Cable Preparation Tool**

HCST			1	1	0.8	0.4	25 AWG								
------	--	--	---	---	-----	-----	--------	--	--	--	--	--	--	--	--



Can be used with video-multicores 127xR and 1281Sx.

**Compression Tool • BNC/RCA die • 25 AWG (Mini RG-59)**

**Easy-to-Use Compression Tool**

HCCT			1	1	1.8	0.8	25 AWG								
------	--	--	---	---	-----	-----	--------	--	--	--	--	--	--	--	--



Can be used with video-multicores 127xR and 1281Sx.