

Instrument & Communication

250V, 90°C

De- scription	Part No.	No. of Pairs	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Conductor OD		Shielding Material Nom. DCR	Nominal OD		Application
			ft.	m	lbs.	kg		AWG	Section mm ²		inch	mm	


90°C • 18 AWG • Stranded Bare Copper • Twisted Pair • Fleece Cloth • Overall Bare Copper Braid

TPE-E-112 Insulation • Black TPE-O-107 Jacket

GL 2067604 HH

Overall
BC Braid

In industrial areas, e.g.
- Shipbuilding industry
- Mechanical engineering



SHO0055	1	3280	1000	167.5	76.0	(7x0.36) BC	18	0.75	0.252	6.40
SHO0056	2	3280	1000	227.1	103.0	(7x0.36) BC	18	0.75	0.280	7.10
SHO0057	4	3280	1000	401.2	182.0	(7x0.36) BC	18	0.75	0.402	10.20
SHO0058	7	3280	1000	573.2	260.0	(7x0.36) BC	18	0.75	0.492	12.50
SHO0059	10	3280	1000	745.2	338.0	(7x0.36) BC	18	0.75	0.563	14.30
SHO0060	14	3280	1000	987.7	448.0	(7x0.36) BC	18	0.75	0.646	16.40
SHO0061	19	3280	1000	1239.0	562.0	(7x0.36) BC	18	0.75	0.713	18.10
SHO0062	24	3280	1000	1567.5	711.0	(7x0.36) BC	18	0.75	0.815	20.70

BC = Bare Copper • DCR = DC resistance