





**Broadband Coax**

## Trunk Cables



BROADBAND

De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation			
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/ 100 ft.	dB/ 100 m	
<b>Coax 3C • Solid 3.38 mm Bare Copper • Copper-Foil • 60% Bare Copper Braid</b>																				
<b>Gas-Injected Polyethylene Insulation • Polyethylene Jacket (Black or Green)</b>																				
70°C	<b>CX3C0</b>		2296	700	496.9	225.4	3.38 mm	0.587	14.90	Cu-foil + 60% BC Braid 2.6 /km*** 15.8 mm	0.780	19.80	75	84%	16.5	54.0	5	0.1	0.4	
			3444	1050	745.4	338.1	Solid BC 4.5 /km* 1.9 /km**	100	0.5								1.8			
																				
FB20																				
Return loss at 5-470 MHz: 26 dB 470-1000 MHz: 23 dB 1000-2150 MHz: 18 dB																				
Screening attenuation at 30-1000 MHz: 100 dB Transfer impedance at 5-30 MHz: 0.8 m /m Screening Class: A++ Pulling Tension: 1200 N																				
70°C	<b>CX3C3</b>		2296	700	626.5	284.2	3.38 mm	0.587	14.90	Cu-foil + 60% BC Braid 2.6 /km*** 15.8 mm	0.780	19.80	75	84%	16.5	54.0				see above
																				
FB20																				
Return loss at 5-470 MHz: 26 dB 470-1000 MHz: 23 dB 1000-2150 MHz: 18 dB																				
Screening attenuation at 30-1000 MHz: 100 dB Transfer impedance at 5-30 MHz: 0.8 m /m Screening Class: A++ Pulling Tension: 6000 N																				
Available in Black. 7.2 mm ZP messenger																				
<b>Gas-Injected Polyethylene Insulation • Grey FRNC/LSNH Jacket</b>																				
70°C	<b>CX3C2</b>	IEC 332-1	2296	700	620.4	281.4	3.38 mm	0.587	14.90	Cu-foil + 60% BC Braid 2.6 /km*** 15.8 mm	0.780	19.80	75	84%	16.5	54.0				see above
																				
FB20																				
Return loss at 5-470 MHz: 26 dB 470-1000 MHz: 23 dB 1000-2150 MHz: 18 dB																				
Screening attenuation at 30-1000 MHz: 100 dB Transfer impedance at 5-30 MHz: 0.8 m /m Screening Class: A++ Pulling Tension: 1200 N																				
<b>Coax 3C • Solid 3.38 mm Bare Copper • Copper-Foil</b>																				
<b>Gas-Injected Polyethylene Insulation • Polyethylene Jacket (Black or Green)</b>																				
70°C	<b>CX3C1</b>		2296	700	419.8	190.4	3.38 mm	0.587	14.90	Cu-foil 2.6 /km*** 15.3 mm	0.709	18.00	75	84%	16.5	54.0				see above
																				
FB18																				
Return loss at 5-470 MHz: 26 dB 470-1000 MHz: 23 dB 1000-2150 MHz: 18 dB																				
Screening attenuation at 30-1000 MHz: 100 dB Transfer impedance at 5-30 MHz: 0.8 m /m Screening Class: A++ Pulling Tension: 1200 N																				

\* DC loop resistance • \*\* DC resistance inner conductor • \*\*\* DC resistance outer conductor • DCR = DC resistance • BC = Bare Copper • ZP = Stranded Zinc-Plated Steel

## Broadband Coax

### Distribution Cables




De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/ 100 ft.	dB/ 100 m

#### CT167C • Solid 1.67 mm Bare Copper • Copper-Foil • 55 % Bare Copper Braid

##### 5-Cell Polyethylene Insulation • Black Polyethylene Jacket

70°C	CT167C1	328	100	24.5	11.1	1.67 mm	0.287	7.28	Cu-foil + 55% BC Braid	0.398	10.10	75	81%	16.5	54.0	5	0.3	0.9
		820	250	61.2	27.8	Solid BC 15.0 /km* 8.5 /km**										6.5 /km*** 8.1 mm	230	1.8




Return loss at 5-470 MHz: 26 dB  
470-1000 MHz: 23 dB  
1000-2150 MHz: 18 dB

Screening attenuation at 30-1000 MHz: 85 dB  
Transfer impedance at 5-30 MHz: 5.0 m /m  
Screening Class: A  
Pulling Tension: 300 N

1000	4.3	14.0
1350	5.0	16.3
1750	5.9	19.2
2150	6.7	21.9
2400	7.1	23.2
3000	8.0	26.1

##### 5-Cell Polyethylene Insulation • Black RBS Polyethylene Jacket

70°C	CT167C3	820	250	63.4	28.8	1.67 mm	0.287	7.28	Cu-foil + 55% BC Braid	0.398	10.10	75	81%	16.5	54.0	see above		
					Solid BC 15.0 /km* 8.5 /km**	6.5 /km*** 8.1 mm												




RBS jacket

Return loss at 5-470 MHz: 26 dB  
470-1000 MHz: 23 dB  
1000-2150 MHz: 18 dB

Screening attenuation at 30-1000 MHz: 85 dB  
Transfer impedance at 5-30 MHz: 5.0 m /m  
Screening Class: A  
Pulling Tension: 300 N

##### 5-Cell Polyethylene Insulation • Black PVC Jacket

70°C	CT167C0	820	250	52.4	23.8	1.67 mm	0.287	7.28	Cu-foil + 55% BC Braid	0.398	10.10	75	81%	16.5	54.0	see above		
		1640	500	104.7	47.5	Solid BC												
		3280	1000	209.4	95.0	15.0 /km* 8.5 /km**										6.5 /km*** 8.1 mm		




Return loss at 5-470 MHz: 26 dB  
470-1000 MHz: 23 dB  
1000-2150 MHz: 18 dB

Screening attenuation at 30-1000 MHz: 85 dB  
Transfer impedance at 5-30 MHz: 5.0 m /m  
Screening Class: A  
Pulling Tension: 300 N

##### 5-Cell Polyethylene Insulation • Grey FRNC/LSNH Jacket

70°C	CT167C2	IEC 322-1	820	250	52.4	23.8	1.67 mm	0.287	7.28	Cu-foil + 55% BC Braid	0.398	10.10	75	81%	16.5	54.0	see above		
			1640	500	104.7	47.5	Solid BC												
			3280	1000	209.4	95.0	15.0 /km* 8.5 /km**										6.5 /km*** 8.1 mm		



Return loss at 5-470 MHz: 26 dB  
470-1000 MHz: 23 dB  
1000-2150 MHz: 18 dB





Screening attenuation at 30-1000 MHz: 85 dB  
Transfer impedance at 5-30 MHz: 5.0 m /m  
Screening Class: A  
Pulling Tension: 300 N

\* DC loop resistance • \*\* DC resistance inner conductor • \*\*\* DC resistance outer conductor • DCR = DC resistance • BC = Bare Copper

## Broadband Coax

### Distribution Cables






De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/ 100 ft.	dB/ 100 m
<b>PRG11C • Solid 1.55 mm Bare Copper • Copper-Foil • 50% Bare Copper Braid</b>																			
<b>Gas-Injected Polyethylene Insulation • Grey FRNC/LSNH Jacket</b>																			
70°C	PRG11C2	IEC 332-1	820	250	45.2	20.5	1.55 mm	0.285	7.25	Cu-foil + 50% BC Braid 10.6 /km*** 7.9 mm	0.398	10.10	75	81%	16.8	55.0	5	0.3	0.9
			1640	500	90.4	41.0	Solid BC 20.0 /km* 9.4 /km**	50	0.9								2.8		
																			
Return loss at 5-470 MHz: 26 dB      Screening attenuation at 30-1000 MHz: 85 dB 470-1000 MHz: 23 dB      Transfer impedance at 5-30 MHz: 5.0 m /m 1000-2000 MHz: 18 dB      Screening Class: A 2000-3000 MHz: 16 dB      Pulling Tension: 225 N																			
<b>Gas-Injected Polyethylene Insulation • PVC Jacket (Black or White)</b>																			
70°C	PRG11C4		820	250	44.6	20.3	1.55 mm	0.285	7.25	Cu-foil + 50% BC Braid 10.6 /km*** 7.9 mm	0.398	10.10	75	81%	16.8	55.0	see above		
			1640	500	89.3	40.5	Solid BC 20.0 /km* 9.4 /km**	230	2.0								6.4		
																			
Return loss at 5-470 MHz: 26 dB      Screening attenuation at 30-1000 MHz: 85 dB 470-1000 MHz: 23 dB      Transfer impedance at 5-30 MHz: 5.0 m /m 1000-2000 MHz: 18 dB      Screening Class: A 2000-3000 MHz: 16 dB      Pulling Tension: 225 N																			
1000 m put-up available in Black only.																			
<b>PRG11A • Solid 1.55 mm Bare Copper • Duofoil® • 50% Tinned Copper Braid</b>																			
<b>Gas-Injected Polyethylene Insulation • Black Polyethylene Jacket</b>																			
70°C	PRG11A3		1640	500	67.2	30.5	1.55 mm	0.285	7.25	Duofoil® + 50% TC Braid 12.8 /km*** 7.9 mm	0.398	10.10	75	81%	16.8	55.0	5	0.3	0.9
							Solid BC 22.2 /km* 9.4 /km**	50	0.9								2.9		
																			
Return loss at 5-470 MHz: 26 dB      Screening attenuation at 30-1000 MHz: 85 dB 470-1000 MHz: 23 dB      Transfer impedance at 5-30 MHz: 5.0 m /m 1000-2000 MHz: 18 dB      Screening Class: A 2000-3000 MHz: 16 dB      Pulling Tension: 225 N																			
<b>Gas-Injected Polyethylene Insulation • White PVC Jacket</b>																			
70°C	PRG11A2		1640	500	86.0	39.0	1.55 mm	0.285	7.25	Duofoil® + 50% TC Braid 12.8 /km*** 7.9 mm	0.398	10.10	75	81%	16.8	55.0	see above		
							Solid BC 22.2 /km* 9.4 /km**	230	2.0								6.4		
																			
Return loss at 5-470 MHz: 26 dB      Screening attenuation at 30-1000 MHz: 85 dB 470-1000 MHz: 23 dB      Transfer impedance at 5-30 MHz: 5.0 m /m 1000-2000 MHz: 18 dB      Screening Class: A 2000-3000 MHz: 16 dB      Pulling Tension: 225 N																			

\* DC loop resistance • \*\* DC resistance inner conductor • \*\*\* DC resistance outer conductor • DCR = DC resistance • BC = Bare Copper • TC = Tinned Copper

Duofoil® see technical information page 23.13.

**Broadband Coax**  
Distribution Cables



De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation												
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/ 100 ft.	dB/ 100 m										
<b>PRG11D • Solid 1.55 mm Bare Copper • Duobond Plus® • 50 % Tinned Copper Braid</b>																													
<b>Gas-Injected Polyethylene Insulation • Black Polyethylene Jacket</b>																													
70°C	PRG11D3		820	250	34.7	15.8	1.55 mm	0.285	7.25	Duobond Plus® + 50% TC Braid 9.5 /km*** 8.1 mm	0.398	10.10	75	81%	16.8	55.0	5	0.3	0.9										
			1640	500	69.4	31.5	Solid BC 18.9 /km* 9.4 /km**	50	0.9								2.8												
	BTQ																												
		Return loss at	5-470 MHz: 26 dB	470-1000 MHz: 23 dB	1000-2000 MHz: 18 dB	2000-3000 MHz: 16 dB	Screening attenuation at 30-1000 MHz: 105 dB	Transfer impedance at 5-30 MHz: 1.9 m /m	Screening Class: A+	Pulling Tension: 250 N	862	3.9	12.7	1000	4.2	13.9	1350	5.0	16.5	1750	5.8	19.0	2150	6.4	21.1	2400	6.9	22.5	3000
<b>Gas-Injected Polyethylene Insulation • Black FRNC/LSNH Jacket</b>																													
70°C	PRG11D1	IEC 332-1	1640	500	97.0	44.0	1.55 mm	0.285	7.25	Duobond Plus® + 70% TC Braid 7.0 /km*** 8.1 mm	0.398	10.10	75	81%	16.8	55.0	see above												
							Solid BC 16.4 /km* 9.4 /km**										50	0.9	2.8										
	BTQ																												
		Return loss at	5-470 MHz: 26 dB	470-1000 MHz: 23 dB	1000-2000 MHz: 18 dB	2000-3000 MHz: 16 dB	Screening attenuation at 30-1000 MHz: 105 dB	Transfer impedance at 5-30 MHz: 1.9 m /m	Screening Class: A+	Pulling Tension: 250 N	862	3.9	12.7	1000	4.2	13.9	1350	5.0	16.5	1750	5.8	19.0	2150	6.4	21.1	2400	6.9	22.5	3000
<b>Gas-Injected Polyethylene Insulation • Black PVC Jacket</b>																													
70°C	PRG11D0		1640	500	83.8	38.0	1.55 mm	0.285	7.25	Duobond Plus® + 50% TC Braid 9.5 /km*** 8.1 mm	0.398	10.10	75	81%	16.8	55.0	see above												
							Solid BC 18.9 /km* 9.4 /km**										50	0.9	2.8										
	BTQ																												
		Return loss at	5-470 MHz: 26 dB	470-1000 MHz: 23 dB	1000-2000 MHz: 18 dB	2000-3000 MHz: 16 dB	Screening attenuation at 30-1000 MHz: 105 dB	Transfer impedance at 5-30 MHz: 1.9 m /m	Screening Class: A+	Pulling Tension: 250 N	862	3.9	12.7	1000	4.2	13.9	1350	5.0	16.5	1750	5.8	19.0	2150	6.4	21.1	2400	6.9	22.5	3000

\* DC loop resistance • \*\* DC resistance inner conductor • \*\*\* DC resistance outer conductor • DCR = DC resistance • BC = Bare Copper • TC = Tinned Copper

Duobond Plus® see technical information page 23.13.

## Broadband Coax

## Drop Cables



De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation			
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/ 100 ft.	dB/ 100 m	
<b>CT125C • Solid 1.25 mm Bare Copper • Copper-Foil • 51 % Bare Copper Braid</b>																				
<b>5-Cell Polyethylene Insulation • Black Polyethylene Jacket</b>																				
70°C	CT125C1		820	250	31.4	14.3	1.25 mm	0.217	5.50	Cu-foil	0.307	7.80	75	81%	16.5	54.0	50	1.1	3.5	
			1640	500	62.8	28.5	Solid BC			+ 51% BC								230	2.4	7.8
			3280	1000	125.7	57.0	28.5 /km*			Braid									470	3.5
						15.0 /km**			13.5 /km***								862	4.7	15.5	
									6.2 mm								1000	5.2	17.0	
																	1750	6.7	22.0	
																	2150	7.9	26.0	
Return loss at			5-470 MHz: 23 dB				Screening attenuation at 30-1000 MHz: 85 dB													
			470-1000 MHz: 20 dB				Transfer impedance at 5-30 MHz: 5.0 m /m													
			1000-2000 MHz: 18 dB				Screening Class: A													
			2000-3000 MHz: 16 dB				Pulling Tension: 100 N													
<b>5-Cell Polyethylene Insulation • Black RBS Polyethylene Jacket</b>																				
70°C	CT125C3		1640	500	88.2	40.0	1.25 mm	0.217	5.50	Cu-foil	0.307	7.80	75	81%	16.5	54.0	see above			
			3280	1000	176.4	80.0	Solid BC			+ 51% BC										
						28.5 /km*			Braid											
						15.0 /km**			13.5 /km***											
									6.2 mm											
RBS jacket																				
Return loss at			5-470 MHz: 23 dB				Screening attenuation at 30-1000 MHz: 85 dB													
			470-1000 MHz: 20 dB				Transfer impedance at 5-30 MHz: 5.0 m /m													
			1000-2000 MHz: 18 dB				Screening Class: A													
			2000-3000 MHz: 16 dB				Pulling Tension: 100 N													
<b>5-Cell Polyethylene Insulation • Black PVC Jacket</b>																				
70°C	CT125C0		328	100	15.0	6.8	1.25 mm	0.217	5.50	Cu-foil	0.307	7.80	75	81%	16.5	54.0	see above			
			820	250	37.5	17.0	Solid BC			+ 51% BC										
			1640	500	75.0	34.0	28.5 /km*			Braid										
						15.0 /km**			13.5 /km***											
									6.2 mm											
Return loss at			5-470 MHz: 23 dB				Screening attenuation at 30-1000 MHz: 85 dB													
			470-1000 MHz: 20 dB				Transfer impedance at 5-30 MHz: 5.0 m /m													
			1000-2000 MHz: 18 dB				Screening Class: A													
			2000-3000 MHz: 16 dB				Pulling Tension: 100 N													
<b>RG7C • Solid 1.25 mm Bare Copper • Copper-Foil • 50% Bare Copper Braid</b>																				
<b>Gas-Injected Polyethylene Insulation • Black Polyethylene Jacket</b>																				
70°C	RG7C01		820	250	34.4	15.6	1.25 mm	0.224	5.70	Cu-foil	0.319	8.10	75	82%	16.5	54.0	5	0.4	1.2	
			1640	500	68.9	31.3	Solid BC			+ 50% BC								50	1.0	3.4
							26.5 /km*			Braid									100	1.5
						14.5 /km**			12.0 /km***								230	2.3	7.5	
									6.3 mm								400	3.1	10.1	
																	800	4.5	14.6	
																	862	4.6	15.1	
																	1000	5.0	16.5	
																	1350	5.9	19.5	
																	1750	6.9	22.6	
																	2150	7.7	25.3	
																	2400	8.2	27.0	
Return loss at			5-470 MHz: 23 dB				Screening attenuation at 30-1000 MHz: 85 dB													
			470-1000 MHz: 20 dB				Transfer impedance at 5-30 MHz: 15.0 m /m													
			1000-2000 MHz: 18 dB				Screening Class: B													
			2000-3000 MHz: 16 dB				Pulling Tension: 90 N													
<b>Gas-Injected Polyethylene Insulation • Black FRNC/LSNH Jacket</b>																				
70°C	RG7C02 IEC 332-1		820	250	34.4	15.6	1.25 mm	0.224	5.70	Cu-foil	0.319	8.10	75	82%	16.5	54.0	see above			
			1640	500	68.9	31.3	Solid BC			+ 50% BC										
						26.5 /km*			Braid											
						14.5 /km**			12.0 /km***											
									6.3 mm											
Return loss at			5-470 MHz: 23 dB				Screening attenuation at 30-1000 MHz: 85 dB													
			470-1000 MHz: 20 dB				Transfer impedance at 5-30 MHz: 15.0 m /m													
			1000-2000 MHz: 18 dB				Screening Class: B													
			2000-3000 MHz: 16 dB				Pulling Tension: 90 N													

\* DC loop resistance • \*\* DC resistance inner conductor • \*\*\* DC resistance outer conductor • DCR = DC resistance • BC = Bare Copper





**Broadband Coax**

Drop Cables



De- scription	Part No.	UL NEC/ C(UL)/CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/ 100 ft.	dB/ 100 m

**H125C • Solid 1.0 mm Bare Copper • Copper-Foil • 40% Bare Copper Braid**

**Gas-Injected Polyethylene Insulation • Grey FRNC/LSNH Jacket**

70°C	<b>H125C04</b>	IEC 332-1	1640	500	49.6	22.5	1.0 mm Solid BC 41.0 /km* 23.0 /km**	0.189	4.80	Cu-foil + 40% BC Braid 18.0 /km*** 5.4 mm	0.268	6.80	75	81%	16.8	55.0	5	0.4	1.4
																	50	1.3	4.3
																	100	1.9	6.1
																	230	2.8	9.2
																	400	3.8	12.3
																	800	5.4	17.7
																	862	5.6	18.4
																	1000	6.1	19.9
																	1350	7.1	23.4
																	1750	8.2	27.0
																	2150	9.2	30.2
																	2400	9.8	32.1



Return loss at	5-470 MHz: 23 dB	Screening attenuation at 30-1000 MHz: 85 dB
	470-1000 MHz: 20 dB	Transfer impedance at 5-30 MHz: 15.0 m /m
	1000-2000 MHz: 18 dB	Screening Class: B
	2000-3000 MHz: 16 dB	Pulling Tension: 55 N

**Gas-Injected Polyethylene Insulation • PVC Jacket (Black, Brown, Crème, Grey or White)**

70°C	<b>H125C00</b>		B-328	B-100	10.4	4.7	1.0 mm Solid BC 41.0 /km* 23.0 /km**	0.189	4.80	Cu-foil + 40% BC Braid 18.0 /km*** 5.4 mm	0.268	6.80	75	81%	16.8	55.0				see above	
			820	250	25.9	11.8															
			1640	500	51.8	23.5															
			3280	1000	103.6	47.0															



Return loss at	5-470 MHz: 23 dB	Screening attenuation at 30-1000 MHz: 85 dB
	470-1000 MHz: 20 dB	Transfer impedance at 5-30 MHz: 15.0 m /m
	1000-2000 MHz: 18 dB	Screening Class: B
	2000-3000 MHz: 16 dB	Pulling Tension: 55 N

Brown, Crème and Grey available in B-100 m only.

**Gas-Injected Polyethylene Insulation • White PVC Jacket**

70°C	<b>H125C03</b>		820	250	49.1	22.3	1.0 mm Solid BC 41.0 /km* 23.0 /km**	0.189	4.80	Cu-foil + 40% BC Braid 18.0 /km*** 5.24 mm	0.268	6.80	75	81%	16.8	55.0				see above	



Return loss at	5-470 MHz: 23 dB	Screening attenuation at 30-1000 MHz: 75 dB
	470-1000 MHz: 20 dB	Transfer impedance at 5-30 MHz: 15.0 m /m
	1000-2000 MHz: 18 dB	Screening Class: B
	2000-3000 MHz: 16 dB	Pulling Tension: 55 N

ShotGun

**H125A • Solid 1.0 mm Bare Copper • Duofoil® • 70% Tinned Copper Braid**

**Gas-Injected Polyethylene Insulation • Black Polyethylene Jacket**

70°C	<b>H125A08</b>		1640	500	45.2	20.5	1.0 mm Solid BC 41.0 /km* 23.0 /km**	0.189	4.80	Duofoil® + 70% TC Braid 18.0 /km*** 5.5 mm	0.268	6.80	75	81%	16.8	55.0	5	0.5	1.8
																	50	1.4	4.7
																	100	2.0	6.5
																	230	3.0	9.8
																	400	3.9	12.9
																	800	5.7	18.6
																	862	5.9	19.3
																	1000	6.4	20.9
																	1350	7.5	24.6
																	1750	8.7	28.4
																	2150	9.7	31.9
																	2400	10.4	34.0



Return loss at	5-470 MHz: 23 dB	Screening attenuation at 30-1000 MHz: 85 dB
	470-1000 MHz: 20 dB	Transfer impedance at 5-30 MHz: 15.0 m /m
	1000-2000 MHz: 18 dB	Screening Class: B
	2000-3000 MHz: 16 dB	Pulling Tension: 55 N

**Gas-Injected Polyethylene Insulation • White FRNC/LSNH Jacket**

70°C	<b>H125A07</b>	IEC 332-1	B-328	B-100	10.8	4.9	1.0 mm Solid BC 41.0 /km* 23.0 /km**	0.189	4.80	Duofoil® + 70% TC Braid 18.0 /km*** 5.5 mm	0.268	6.80	75	81%	16.8	55.0				see above	
			1640	500	54.0	24.5															



Return loss at	5-470 MHz: 23 dB	Screening attenuation at 30-1000 MHz: 85 dB
	470-1000 MHz: 20 dB	Transfer impedance at 5-30 MHz: 15.0 m /m
	1000-2000 MHz: 18 dB	Screening Class: B
	2000-3000 MHz: 16 dB	Pulling Tension: 55 N

\* DC loop resistance • \*\* DC resistance inner conductor • \*\*\* DC resistance outer conductor • DCR = DC resistance • BC = Bare Copper • TC = Tinned Copper

Duofoil® see technical information page 23.13.





**Broadband Coax**

Drop Cables



De-scription	Part No.	UL NEC / C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation	
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/100 ft.

**H125D • Solid 1.0 mm Bare Copper • Duobond Plus® • 50 % Tinned Copper Shield**

**Gas-Injected Polyethylene Insulation • PE Jacket (Green with White Stripes)**

70°C	H125D00	1640	500	45.2	20.5	1.0 mm	0.189	4.80	Duobond Plus®	0.280	7.10	75	80%	16.8	55.0	5	0.5	1.7
		3280	1000	90.4	41.0	Solid BC			+ 50% TC							50	1.4	4.7
						37.0 /km*			Braid							100	1.9	6.2
						23.0 /km**			14.0 /km***							230	3.0	9.8
									5.6 mm							400	3.9	12.9
																800	5.7	18.8
																862	5.9	19.3
																1000	6.5	21.2
																1350	7.7	25.1
																1750	8.8	29.0
																2150	10.0	32.7
																2400	10.6	34.8

Shorting Fold

BTQ

Return loss at 5-470 MHz: 23 dB  
470-1000 MHz: 20 dB  
1000-2000 MHz: 18 dB  
2000-3000 MHz: 16 dB

Screening attenuation at 30-1000 MHz: 95 dB  
Transfer impedance at 5-30 MHz: 5.0 m /m  
Screening Class: A  
Pulling Tension: 60 N

**CT100C • Solid 1.0 mm Bare Copper • Copper-Foil • 53 % Bare Copper Braid**

**5-Cell Polyethylene Insulation • PVC Jacket (Black, Brown and White)**

70°C	CT100C0	328	100	11.5	5.2	1.0 mm	0.185	4.70	Cu-foil	0.262	6.65	75	82%	16.8	55.0	50	1.5	4.6
		820	250	28.1	13.0	Solid BC			+ 53% BC							230	3.0	9.8
		1640	500	57.3	26.0	41.0 /km*			Braid							470	4.6	15.0
		3280	1000	112.4	51.0	26.0 /km**			15.0 /km***							862	5.9	19.5
									5.35 mm							1000	6.6	21.5
																1750	8.8	29.0
																2150	9.9	32.5

Return loss at 5-470 MHz: 23 dB  
470-1000 MHz: 20 dB  
1000-2000 MHz: 18 dB  
2000-3000 MHz: 16 dB

Screening attenuation at 30-1000 MHz: 75 dB  
Transfer impedance at 5-30 MHz: 15.0 m /m  
Screening Class: B  
Pulling Tension: 55 N

500 m put-up available in Black only.

**5-Cell Polyethylene Insulation • PVC RBS Jacket (Black and White)**

70°C	CT100C3	328	100	11.2	5.1	1.0 mm	0.185	4.70	Cu-foil	0.262	6.65	75	82%	16.8	55.0	see above		
		820	250	28.1	12.8	Solid BC			+ 53% BC									
		1640	500	56.2	25.5	41.0 /km*			Braid									
		3280	1000	112.4	51.0	26.0 /km**			15.0 /km***									
									5.35 mm									

Return loss at 5-470 MHz: 23 dB  
470-1000 MHz: 20 dB  
1000-2000 MHz: 18 dB  
2000-3000 MHz: 16 dB

Screening attenuation at 30-1000 MHz: 75 dB  
Transfer impedance at 5-30 MHz: 15.0 m /m  
Screening Class: B  
Pulling Tension: 55 N

**5-Cell Polyethylene Insulation • Black FRNC/LSNH Jacket**

70°C	CT100C1	3280	1000	116.8	53.0	1.0 mm	0.185	4.70	Cu-foil	0.262	6.65	75	82%	16.8	55.0	see above		
						Solid BC			+ 53% BC									
						41.0 /km*			Braid									
						26.0 /km**			15.0 /km***									
									5.35 mm									

Return loss at 5-470 MHz: 23 dB  
470-1000 MHz: 20 dB  
1000-2000 MHz: 18 dB  
2000-3000 MHz: 16 dB

Screening attenuation at 30-1000 MHz: 75 dB  
Transfer impedance at 5-30 MHz: 15.0 m /m  
Screening Class: B  
Pulling Tension: 55 N

**H124A • Solid 1.0 mm Bare Copper • Duofoil® • 31 % Tinned Copper Braid**

**Gas-Injected Polyethylene Insulation • White PVC Jacket**

70°C	H124A00	B-328	B-100	6.8	3.1	1.0 mm	0.173	4.40	Duofoil®	0.232	5.90	75	84%	16.2	53.0	5	0.6	2.0
		U-820	U-250	17.1	7.8	Solid BC			+ 31% TC							50	1.4	4.5
		1640	500	34.2	15.5	58.0 /km*			Braid							100	2.0	6.4
		16400	5000	341.7	155.0	35.0 /km**			23.0 /km***							230	2.9	9.5
									5.1 mm							400	4.1	13.3
																800	5.9	19.3
																862	6.0	19.8
																1000	6.6	21.8
																1350	7.8	25.7
																1750	9.1	29.7
																2150	10.2	33.4
																2400	10.9	35.6

Return loss at 5-470 MHz: 23 dB  
470-1000 MHz: 20 dB  
1000-2000 MHz: 18 dB  
2000-3000 MHz: 16 dB

Screening attenuation at 30-1000 MHz: 75 dB  
Transfer impedance at 5-30 MHz: 40.0 m /m  
Screening Class: C  
Pulling Tension: 55 N

\* DC loop resistance • \*\* DC resistance inner conductor • \*\*\* DC resistance outer conductor • DCR = DC resistance • BC = Bare Copper • TC = Tinned Copper

Duofoil® and Duobond Plus® see technical information page 23.13.



## Broadband Coax

## Drop Cables



De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation			
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/ 100 ft.	dB/ 100 m	
<b>H121C • Solid 0.8 mm Bare Copper • Copper-Foil • 45% Bare Copper Braid</b>																				
<b>Gas-Injected Polyethylene Insulation • White PVC Jacket</b>																				
70°C	<b>H121C00</b>		B-328 1640	B-100 500	6.0 29.8	2.7 13.5	0.8 mm Solid BC 59.0 /km* 35.0 /km**	0.138	3.50	Cu-foil + 45% BC Braid 24.0 /km*** 4.1 mm	0.197	5.00	75	84%	16.2	53.0	5	0.5	1.7	
																		50	1.6	5.3
																		100	2.3	7.5
																		230	3.5	11.4
																		400	4.6	15.1
																		800	6.6	21.7
																		862	6.9	22.6
																		1000	7.5	24.5
																		1350	8.8	28.7
																		1750	10.1	33.0
																		2150	11.3	36.9
																		2400	12.0	39.2
Return loss at			5-470 MHz: 20 dB				Screening attenuation at 30-1000 MHz: 80 dB													
			470-1000 MHz: 18 dB				Transfer impedance at 5-30 MHz: 10.0 m /m													
			1000-2000 MHz: 16 dB				Screening Class: B													
			2000-3000 MHz: 15 dB				Pulling Tension: 40 N													
<b>H121A • Solid 0.8 mm Bare Copper • Duofoil® • 75% Tinned Copper Braid</b>																				
<b>Gas-Injected Polyethylene Insulation • White PVC Jacket</b>																				
70°C	<b>H121A03</b>		B-328 1640	B-100 500	6.4 32.0	2.9 14.5	0.8 mm Solid BC 55.0 /km* 35.0 /km**	0.138	3.50	Duofoil® + 75% TC Braid 20.0 /km*** 4.1 mm	0.197	5.00	75	84%	16.2	53.0	5	0.7	2.3	
																		50	1.8	5.9
																		100	2.5	8.1
																		230	3.7	12.1
																		400	4.8	15.9
																		800	6.9	22.7
																		862	7.2	23.6
																		1000	7.8	25.6
																		1350	9.1	30.0
																		1750	10.5	34.5
																		2150	11.8	38.6
																		2400	12.5	41.0
Return loss at			5-470 MHz: 20 dB				Screening attenuation at 30-1000 MHz: 100 dB													
			470-1000 MHz: 18 dB				Transfer impedance at 5-30 MHz: 4.2 m /m													
			1000-2000 MHz: 16 dB				Screening Class: A													
			2000-3000 MHz: 15 dB				Pulling Tension: 45 N													
<b>H121A • Solid 0.8 mm Bare Copper • Duofoil® • 40% Tinned Copper Braid</b>																				
<b>Gas-Injected Polyethylene Insulation • White FRNC/LSNH Jacket</b>																				
70°C	<b>H121A04</b>	IEC 332-1	B-328 1640	B-100 500	7.3 36.4	3.3 16.5	0.8 mm Solid BC 55.0 /km* 35.0 /km**	0.138	3.50	Duofoil® + 75% TC Braid 20.0 /km*** 4.1 mm	0.197	5.00	75	84%	16.2	53.0	see above			
<b>H121B</b>																				
Return loss at			5-470 MHz: 20 dB				Screening attenuation at 30-1000 MHz: 100 dB													
			470-1000 MHz: 18 dB				Transfer impedance at 5-30 MHz: 4.2 m /m													
			1000-2000 MHz: 16 dB				Screening Class: A													
			2000-3000 MHz: 15 dB				Pulling Tension: 45 N													
<b>H121A • Solid 0.8 mm Bare Copper • Duofoil® • 40% Tinned Copper Braid</b>																				
<b>Gas-Injected Polyethylene Insulation • Black Polyethylene Jacket</b>																				
70°C	<b>H121A01</b>		1640 3280	500 1000	22.0 44.1	10.0 20.0	0.8 mm Solid BC 75.0 /km* 35.0 /km**	0.138	3.50	Duofoil® + 40% TC Braid 40.0 /km*** 4.1 mm	0.197	5.00	75	84%	16.2	53.0	see above			
<b>H121B</b>																				
Return loss at			5-470 MHz: 20 dB				Screening attenuation at 30-1000 MHz: 75 dB													
			470-1000 MHz: 18 dB				Transfer impedance at 5-30 MHz: 33.0 m /m													
			1000-2000 MHz: 16 dB				Screening Class: C													
			2000-3000 MHz: 15 dB				Pulling Tension: 40 N													
<b>Gas-Injected Polyethylene Insulation • PVC Jacket (Black or White)</b>																				
70°C	<b>H121A00</b>		B-328 820 1640	B-100 250 500	6.4 16.0 32.0	2.9 7.3 14.5	0.8 mm Solid BC 75.0 /km* 35.0 /km**	0.138	3.50	Duofoil® + 40% TC Braid 40.0 /km*** 4.1 mm	0.197	5.00	75	84%	16.2	53.0	see above			
<b>H121B</b>																				
Return loss at			5-470 MHz: 20 dB				Screening attenuation at 30-1000 MHz: 75 dB													
			470-1000 MHz: 18 dB				Transfer impedance at 5-30 MHz: 33.0 m /m													
			1000-2000 MHz: 16 dB				Screening Class: C													
			2000-3000 MHz: 15 dB				Pulling Tension: 40 N													

\* DC loop resistance • \*\* DC resistance inner conductor • \*\*\* DC resistance outer conductor • DCR = DC resistance • BC = Bare Copper • TC = Tinned Copper  
Duofoil® see technical information page 23.13.



**Broadband Coax**

Headend Cables



De- scription	Part No.	UL NEC/ C(UL)CEC Type IEC	Standard Lengths		Standard Unit Weight		Conductor (Stranding) Diameter Nom. DCR	Nominal Core OD (Dielectric)		Shielding Material Nom. DCR	Nominal OD		Nom. Imp. ( )	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation	
			ft.	m	lbs.	kg		inch	mm		inch	mm			pF/ft.	pF/m	MHz	dB/ 100 ft.

**20 AWG • Solid 0.8 mm Silver-Plated Copper-Covered Steel • Duobond Plus® • 95 % Aluminum Braid**

**Gas-Injected Foam Polyethylene Insulation • PVC Jacket** (available in Black, Grey, White, Red, Blue, Yellow, Brown, Orange, Green, Purple, Beige, Pink or Aqua)

80°C	<b>9167</b>	NEC: CATVR CMR CEC: CMG FT4	1000	305	27.1	12.3	0.81 mm 20 AWG Solid SPCCS 99.4 /km*	0.144	3.66	Duobond Plus® + 95% AL Braid 14.8 /km***	0.242	6.15	75	83%	16.2	53.1	5	0.8	2.5
																	50	1.8	6.0
																	240	3.6	11.7
																	450	5.0	16.3
																	862	7.0	22.9
																	1000	7.7	25.2



Shorting Fold


Return loss at 5-470 MHz: 20 dB  
470-862 MHz: 18 dB  
862-2150 MHz: 16 dB

Screening attenuation at 30-1000 MHz: 85 dB  
Sweep tested. 5 MHz to 1 GHz.

**23 AWG • Solid 0.6 mm Copper-Covered Steel • 95 % Bare Copper Braid**

**Polyethylene Insulation • Black PVC Jacket**

70°C	<b>MRG5900</b>		328	100	10.1	4.6	0.58 mm Solid CCS	0.146	3.70	95% BC Braid 15.0 /km***	0.242	6.15	75	66%	20.4	67.0	5	0.9	2.9
			B-328	B-100	10.1	4.6	94.0 /km*										50	2.4	8.0
			B-656	B-200	20.3	9.2	79.0 /km**										100	3.5	11.6
			1640	500	50.7	23.0	79.0 /km**										230	5.2	17.2
			3280	1000	101.4	46.0											400	7.6	25.0
																	800	11.5	37.8
																	862	12.0	39.2
																	1000	13.1	42.9



Return loss at 5-470 MHz: 20 dB  
470-1000 MHz: 18 dB  
1000-2000 MHz: 16 dB  
2000-3000 MHz: 15 dB

Screening attenuation at 30-1000 MHz: 65 dB

**23 AWG • Solid 0.6 mm Bare Copper • 92 % Double Tinned Copper Braid**

**Polyethylene Insulation • Black PVC Jacket**

70°C	<b>H106T00</b>		B-328	B-100	12.6	5.7	0.58 mm Solid BC	0.146	3.70	92% TC Braid + 92% TC Braid 18.5 /km***	0.236	6.00	75	66%	20.4	67.0	5	0.7	2.4
			1640	500	62.8	28.5	97.5 /km*										50	2.4	8.0
							79.0 /km**										100	3.5	11.6
																	230	5.6	18.3
																	400	7.6	25.0
																	800	11.5	37.8
																	862	12.0	39.2
																	1000	13.1	42.9



Return loss at 5-470 MHz: 20 dB  
470-1000 MHz: 18 dB

Screening attenuation at 30-1000 MHz: 75 dB

**Polyethylene Insulation • Grey FRNC Jacket**

70°C	<b>H106T01</b>	IEC 332-1	1640	500	63.9	29.0	0.58 mm Solid BC	0.146	3.70	92% TC Braid + 92% TC Braid 18.5 /km***	0.236	6.00	75	66%	20.4	67.0			see above	
							97.5 /km*													
							79.0 /km**													



Return loss at 5-470 MHz: 20 dB  
470-1000 MHz: 18 dB

Screening attenuation at 30-1000 MHz: 75 dB

\* DC loop resistance • \*\* DC resistance inner conductor • \*\*\* DC resistance outer conductor • DCR = DC resistance • BC = Bare Copper • TC = Tinned Copper • SPCCS = Silver-Plated Copper-Covered Steel • AL = Aluminum • CCS = Copper-Covered Steel

Duobond Plus® see technical information page 23.13.