

DataTwist® 5e UTP Cable

TIA/EIA-568-B.2, Category 5e Nonbonded-Pair Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		Max. DCR (Ω / 100m)	Max. DCR Unbal. (%)	Max. Cap. Unbal. (pF/ 100m)	Freq. (MHz)	Max. Atten. (dB/ 100m)	Min. PSUM NEXT (dB)	Min. PSUM ACR (dB/ 100m)	Min. PSUM ELFEXT (dB/ 100m)	Input Imped. (Ω)	Min. RL (dB)
				Ft.	m	Lbs.	kg	Inch	mm										

24 AWG Solid Bare Copper Conductors • Twisted Pairs • Rip Cord • See Color Code Chart (below)**Plenum • FEP Teflon® Insulation • Flamarrest® Jacket** (Available in Natural or Blue)

	1590A	NEC: CMP CEC: CMP FT6	2	1000	304.8	16.0	7.3	.175	4.44	9.38	5.0	330		1	2.0	62.3	60.3	60.8	100±15	20.0
														10	6.5	47.3	49.2	40.8	100±15	25.0
														16	8.2	44.3	40.8	36.7	100±15	25.0
														31.25	11.7	39.9	36.0	30.9	100±15	23.6
														62.5	17.0	35.4	28.2	24.8	100±15	21.5
														100	22.0	32.3	19.0	20.8	100±15	20.1
														200	32.0	27.8	10.3	14.7	100±25	15.0
																	1.0			

Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5e

Plenum • FEP Teflon® Insulation • Flamarrest® Jacket (Red, Orange, Yellow, Green, Gray, White, Black, Pink, Natural or Blue)

	1585A	NEC: CMP CEC: CMP FT6	4	U-1000	U-304.8	23.0	10.5	.198	5.03	9.38	3.0	330		1	2.0	62.3	60.3	60.8	100±15	20.0
														4	4.1	53.3	49.2	48.7	100±15	23.0
														10	6.5	47.3	40.8	40.8	100±15	25.0
														16	8.2	44.3	36.0	36.7	100±15	25.0
														31.25	11.7	39.9	28.2	30.9	100±15	23.6
														62.5	17.0	35.4	19.0	24.8	100±15	21.5
														100	22.0	32.3	10.3	20.8	100±15	20.1
														200	32.0	27.8	1.0	14.7	100±25	15.0

†3000 ft. put-up available in Natural or Blue only.

Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5e

Plenum • FEP Teflon Insulation • Fluorescent Pink Flamarrest Jacket

	1585B	NEC: CMP CEC: CMP FT6	4	1000	304.8	24.0	10.9	.197	5.00	9.38	3.0	330		1	2.0	62.3	60.3	60.8	100±15	20.0
														4	4.1	53.3	49.2	48.7	100±15	23.0
														10	6.5	47.3	40.8	40.8	100±15	25.0
														16	8.2	44.3	36.0	36.7	100±15	25.0
														31.25	11.7	39.9	28.2	30.9	100±15	23.6
														62.5	17.0	35.4	19.0	24.8	100±15	21.5
														100	22.0	32.3	10.3	20.8	100±15	20.1
														200	32.0	27.8	1.0	14.7	100±25	15.0

Jacket sequentially marked at 2 ft. intervals.

Third party verified to TIA/EIA-568-B.2, Category 5e

Plenum • FEP Teflon Insulation • FEP Jacket (Available in Blue or White)

	1585LC	NEC: Limited Combustible FHC 25/50 CMP CEC: CMP FT6	4	U-1000	U-304.8	23.0	10.5	.195	4.95	9.38	3.0	330		1	2.0	62.3	60.3	60.8	100±15	20.0
														4	4.1	53.3	49.2	48.7	100±15	23.0
														10	6.5	47.3	40.8	40.8	100±15	25.0
														16	8.2	44.3	36.0	36.7	100±15	25.0
														31.25	11.7	39.9	28.2	30.9	100±15	23.6
														62.5	17.0	35.4	19.0	24.8	100±15	21.5
														100	22.0	32.3	10.3	20.8	100±15	20.1
														200	32.0	27.8	1.0	14.7	100±25	15.0

Jacket sequentially marked at 2 ft. intervals. No rip cord.

Third party verified to TIA/EIA-568-B.2, Category 5e

Patch Cable • 24 AWG Stranded (7x32) Bare Copper Conductors • Twisted Pairs • RJ-45 Compatible* • See Color Code Chart (below)**Non-Plenum • Polyolefin Insulation • PVC Jacket** (Available in Red, Orange, Yellow, Green, Blue, Purple, Light Gray, White or Black)

	1592A	NEC: CM CEC: CM FT1	4	U-1000	U-304.8	22.0	10.0	.213	5.41	9.38	3.0	330		1	2.5	62.3	—	60.8	100±15	20.0
														4	4.9	53.3	—	48.7	100±15	23.0
														10	7.8	47.3	—	40.8	100±15	25.0
														16	9.9	44.3	—	36.7	100±15	25.0
														31.25	14.1	39.9	—	30.9	100±15	23.6
														62.5	20.4	35.4	—	24.8	100±15	21.5
														100	26.4	32.3	—	20.8	100±15	20.1
														200	38.9	27.8	—	14.7	100±25	15.0

*RJ-45 compatible for either T568-A or T568-B configurations.

Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5e Patch

ACR = Attenuation Crosstalk Ratio • DCR = DC Resistance • ELFEXT = Equal Level Far-end Crosstalk • FEP = Fluorinated Ethylene Propylene • NEXT = Near-end Crosstalk • PSUM = Power Sum • RL = Return Loss • UTP = Unshielded Twisted Pair(s)

Color Codes: DataTwist 5e

Pair No.	Color Combination
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

Teflon is a DuPont trademark.

IBDN Plus 25-Pair Cat5E UTP Cable


TIA/EIA-568-B.2, Category 5E

Enhanced Category 5 Nonbonded-pair Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		Max. DCR (Ω /100m)	Max. DCR Unbal. (%)	Max. Cap. Unbal. (pF/100m)	Freq. (MHz)	Max. Atten. (dB/100m)	Min. PSUM NEXT (dB)	Min. PSUM ELFEXT (dB/100m)	Input Imped. (Ω)	Min. RL (dB)
				Ft.	m	Lbs.	kg	Inch	mm									

24 AWG Solid Bare Copper Conductors • Twisted Pairs • Rip Cord • See Color Code Chart (below)**Non-Plenum • Polyolefin Insulation • Gray PVC Jacket**

Gray, Reel	24576125	NEC: CMR CEC: CMR	25	1000	304.8	119	54.0	.490	12.45	9.38	—	330	0.772 1.0 4.0 8.0 10.0 16.0 20.0 25.0 31.25 62.5 100.0	1.8 2.0 4.1 15.8 16.5 8.2 9.3 10.4 11.7 17.0 22.0	64.0 62.3 53.3 48.8 47.3 44.2 42.8 41.3 39.9 35.4 32.3	63.0 63.8 48.8 42.7 40.8 36.7 34.8 32.8 30.9 24.9 20.8	102±15 100±15 100±15 100±15 100±15 100±15 100±15 100±15 100±15 100±15 100±15	19.4 20.0 23.0 24.5 25.0 25.0 25.0 24.3 23.6 21.5 20.1
------------	-----------------	----------------------------	----	------	-------	-----	------	------	-------	------	---	-----	--	---	--	--	--	--




Rip Cord

Jacket sequentially marked at 2 ft. intervals.

Third party verified to TIA/EIA-568-B.2, Category 5e

Plenum • FEP Insulation • Gray Low-smoke PVC Jacket

Gray, Reel	24577125	NEC: CMP CEC: CMP	25	1000	304.8	127	57.6	.430	10.90	9.38	—	330	0.772 1.0 4.0 8.0 10.0 16.0 20.0 25.0 31.25 62.5 100.0	1.8 2.0 4.1 15.8 16.5 8.2 9.3 10.4 11.7 17.0 22.0	64.0 62.3 53.3 48.8 47.3 44.2 42.8 41.3 39.9 35.4 32.3	63.0 63.8 48.8 42.7 40.8 36.7 34.8 32.8 30.9 24.9 20.8	102±15 100±15 100±15 100±15 100±15 100±15 100±15 100±15 100±15 100±15 100±15	19.4 20.0 23.0 24.5 25.0 25.0 24.3 23.6 21.5 20.1
------------	-----------------	----------------------------	----	------	-------	-----	------	------	-------	------	---	-----	--	---	--	--	--	--



Rip Cord

Jacket sequentially marked at 2 ft. intervals.

Third party verified to TIA/EIA-568-B.2, Category 5e

ACR = Attenuation Crosstalk Ratio • DCR = DC Resistance • ELFEXT = Equal Level Far-end Crosstalk • NEXT = Near-end Crosstalk • PSUM = Power Sum • RL = Return Loss • UTP = Unshielded Twisted Pair(s)

Color Codes:**IBDN Plus 25-Pair Cat5**

Pair No.	Tip	Ring
1	White	Blue
2	White	Orange
3	White	Green
4	White	Brown
5	White	Slate
6	Red	Blue
7	Red	Orange
8	Red	Green
9	Red	Brown
10	Red	Slate
11	Black	Blue
12	Black	Orange
13	Black	Green
14	Black	Brown
15	Black	Slate
16	Yellow	Blue
17	Yellow	Orange
18	Yellow	Green
19	Yellow	Brown
20	Yellow	Slate
21	Violet	Blue
22	Violet	Orange
23	Violet	Green
24	Violet	Brown
25	Violet	Slate

IBDN Plus 25-Pair Cat5 UTP Cable


TIA/EIA-568-A, Category 5

Category 5 Nonbonded-pair Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		Max. DCR (Ω / 100m)	Max. DCR Unbal. (%)	Max. Cap. Unbal. (pF/ 100m)	Freq. (MHz)	Max. Atten. (dB/ 100m)	Min. PSUM NEXT (dB)	Input Imped. (Ω)	Min. SRL (dB)
				Ft.	m	Lbs.	kg	Inch	mm								

24 AWG Solid Bare Copper Conductors • Twisted Pairs • Rip Cord • See Color Code Chart (below)**Non-Plenum • Polyolefin Insulation • Blue PVC Jacket**

Blue, Reel	24572238	NEC:	25	1000	304.8	118.0	53.5	4.90	124.5	9.38	5.0	330	0.772	1.8	64.0	102±15	—
Blue, Reel	24572250	CMR	25	492	150.0								1.0	2.1	62.0	100±15	23
Blue,, Reel	24572260	CEC: CMR	25	500	152.4								4.0	4.3	53.0	100±15	23
													8.0	5.9	48.0	100±15	23
													10.0	6.6	47.0	100±15	23
													16.0	8.2	44.0	100±15	23
													20.0	9.2	42.0	100±15	23
													25.0	10.5	41.0	100±15	22
													31.25	11.8	40.0	100±15	21
													62.5	17.1	35.0	100±15	18
													100.0	22.0	32.0	100±15	16




Rip Cord

Jacket sequentially marked at 2 ft. intervals.

Third party verified to TIA/EIA-568-A, Category 5

Plenum • 100% FEP Insulation • Gray Low-Smoke PVC Jacket

Gray, Reel	24572351	NEC:	25	328	100.0	118.0	53.5	4.90	124.5	9.38	5.0	330	0.772	1.8	64.0	102±15	—
Gray, Reel	24572352	CMP	25	984	300.0								1.0	2.1	62.0	100±15	23
Gray, Reel	24572353	CEC: CMP	25	1000	304.8								4.0	4.3	53.0	100±15	23
													8.0	5.9	48.0	100±15	23
													10.0	6.6	47.0	100±15	23
													16.0	8.2	44.0	100±15	23
													20.0	9.2	42.0	100±15	23
													25.0	10.5	41.0	100±15	22
													31.25	11.8	40.0	100±15	21
													62.5	17.1	35.0	100±15	18
													100.0	22.0	32.0	100±15	16



Rip Cord

Jacket sequentially marked at 2 ft. intervals.

Third party verified to TIA/EIA-568-A, Category 5

ACR = Attenuation Crosstalk Ratio • DCR = DC Resistance • ELFEXT = Equal Level Far-end Crosstalk • NEXT = Near-end Crosstalk • PSUM = Power Sum • RL = Return Loss • UTP = Unshielded Twisted Pair(s)

Color Codes:**IBDN Plus 25-Pair Cat5**


Pair No.	Tip	Ring
1	White	Blue
2	White	Orange
3	White	Green
4	White	Brown
5	White	Slate
6	Red	Blue
7	Red	Orange
8	Red	Green
9	Red	Brown
10	Red	Slate
11	Black	Blue
12	Black	Orange
13	Black	Green
14	Black	Brown
15	Black	Slate
16	Yellow	Blue
17	Yellow	Orange
18	Yellow	Green
19	Yellow	Brown
20	Yellow	Slate
21	Violet	Blue
22	Violet	Orange
23	Violet	Green
24	Violet	Brown
25	Violet	Slate

DataTwist® 5 UTP Cable

TIA/EIA-568-A, Category 5 Nonbonded-Pair Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		Max. DCR (Ω / 100m)	Max. DCR Unbal. (%)	Max. Cap. Unbal. (pF/ 100m)	Freq. (MHz)	Max. Atten. (dB/ 100m)	Min. PSUM NEXT (dB)	Fitted Input Imped. (Ω)	Min. SRL (dB)
				Ft.	m	Lbs.	kg	Inch	mm								

24 AWG Solid Bare Copper Conductors • Twisted Pairs • Rip Cord • See Color Code Chart (below)**Non-Plenum • Polyolefin Insulation • PVC Jacket** (Available in Light Gray or Blue)


	1864A	NEC: CMR CEC: CMR FT4	25	1000	304.8	144.0	65.4	.526	13.36	9.38	5.0	330	1	2.0	62.3	100±15	23.0
													10	6.5	47.3	100±15	23.0
													16	8.2	44.3	100±15	23.0
													31.25	11.7	39.9	100±15	21.1
													62.5	17.0	35.4	100±15	18.0
													100	22.0	32.3	100±15	16.0

Rip Cord

Jacket sequentially marked at 2 ft. intervals.

Third party verified to TIA/EIA-568-A, Category 5

Plenum • FEP Teflon® Insulation • FEP Jacket (Available in Blue Tint or White Tint)

	1871A	NEC: CMP CEC: CMP	25	1000	304.8	131.0	59.5	.430	10.92	9.38	5.0	330	1	2.0	62.3	100±15	23.0
													10	6.5	47.3	100±15	23.0
													16	8.2	44.3	100±15	23.0
													31.25	11.7	39.9	100±15	21.1
													62.5	17.0	35.4	100±15	18.0
													100	22.0	32.3	100±15	16.0

Rip Cord

Jacket sequentially marked at 2 ft. intervals.

Third party verified to TIA/EIA-568-A, Category 5

DCR = DC Resistance • NEXT = Near-end Crosstalk • PSUM = Power Sum • SRL = Structural Return Loss • UTP = Unshielded Twisted Pair(s)

Color Codes: 1864A

Pair	Color Combination
1	White & Blue
2	White & Orange
3	White & Green
4	White & Brown
5	White & Gray
6	Red & Blue
7	Red & Orange
8	Red & Green
9	Red & Brown
10	Red & Gray
11	Black & Blue
12	Black & Orange
13	Black & Green

Pair	Color Combination
14	Black & Brown
15	Black & Gray
16	Yellow & Blue
17	Yellow & Orange
18	Yellow & Green
19	Yellow & Brown
20	Yellow & Gray
21	Purple & Blue
22	Purple & Orange
23	Purple & Green
24	Purple & Brown
25	Purple & Gray

Color Codes: 1871A

Pair	Color Combination
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown
5	White/Gray Stripe & Gray
6	Red/Blue Stripe & Blue
7	Red/Orange Stripe & Orange
8	Red/Green Stripe & Green
9	Red/Brown Stripe & Brown
10	Red/Gray Stripe & Gray
11	Black/Blue Stripe & Blue
12	Black/Orange Stripe & Orange
13	Black/Green Stripe & Green

Pair	Color Combination
14	Black/Brown Stripe & Brown
15	Black/Gray Stripe & Gray
16	Yellow/Blue Stripe & Blue
17	Yellow/Orange Stripe & Orange
18	Yellow/Green Stripe & Green
19	Yellow/Brown Stripe & Brown
20	Yellow/Gray Stripe & Gray
21	Purple/Blue Stripe & Blue
22	Purple/Orange Stripe & Orange
23	Purple/Green Stripe & Green
24	Purple/Brown Stripe & Brown
25	Purple/Gray Stripe & Gray

Teflon is a DuPont trademark.

IBDN Plus UTP Cable


TIA/EIA-568-A, Category 5

Category 5 Nonbonded-pair Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		Max. DCR (Ω / 100m)	Max. DCR Unbal. (%)	Max. Cap. Unbal. (pF/ 100m)	Freq. (MHz)	Max. Atten. (dB/ 100m)	Min. PSUM NEXT (dB)	Min. PSUM ACR (dB/ 100m)	Input Imped. (Ω)	Min. SRL (dB)
				Ft.	m	Lbs.	kg	Inch	mm									

24 AWG Solid Bare Copper Conductors • Twisted Pairs • Rip Cord • See Color Code Chart (below)**Non-Plenum • Polyolefin Insulation • PVC Jacket**

White, Box	24570086	NEC:	4	1000	304.8	10.9	24.0	.186	4.72	9.38	5.0	330	0.772	1.8	64.0	62.2	—	—
Blue, Box	24570036	CMR											1.0	2.0	62.3	60.3	100±15	23.0
		CEC:											4.0	4.1	53.3	49.2	100±15	23.0
		CMR											8.0	5.8	48.8	43.0	100±15	23.0
													10.0	6.5	47.3	40.8	100±15	23.0
													16.0	8.2	44.3	36.0	100±15	23.0
													20.0	9.3	42.8	33.5	100±15	23.0
													25.0	10.4	41.3	30.9	100±15	22.0
													31.25	11.7	39.9	28.2	100±15	21.1
													62.5	17.0	35.4	18.4	100±15	18.1
													100.0	22.0	32.3	10.3	100±15	16.0
													155.0 [▶]	28.1	29.5	1.4	100±15	14.1




Jacket sequentially marked at 2 ft. intervals.

Featuring Descending Length Marking.

Third party verified to TIA/EIA-568-A, Category 5

Non-Plenum • Polyolefin Insulation • LSZH Polymer Alloy

Purple, Box	24570152	NEC:	4	1000	304.8	11.3	25.0	.198	5.03	9.38	5.0	330	0.772	1.8	64.0	62.2	—	—
		CMR											1.0	2.0	62.3	60.3	100±15	23.0
		CEC:											4.0	4.1	53.3	49.2	100±15	23.0
		CMR											8.0	5.8	48.8	43.0	100±15	23.0
													10.0	6.5	47.3	40.8	100±15	23.0
													16.0	8.2	44.3	36.0	100±15	23.0
													20.0	9.3	42.8	33.5	100±15	23.0
													25.0	10.4	41.3	30.9	100±15	22.0
													31.25	11.7	39.9	28.2	100±15	21.1
													62.5	17.0	35.4	18.4	100±15	18.1
													100.0	22.0	32.3	10.3	100±15	16.0
													155.0 [▶]	28.1	29.5	1.4	100±15	14.1




Jacket sequentially marked at 2 ft. intervals.

Featuring Descending Length Marking.

Third party verified to TIA/EIA-568-A, Category 5

Plenum • Dual Insulation: Polyolefin/FEP • Low-Smoke PVC Jacket

White, Box	24570700	NEC:	4	1000	304.8	9.98	22.0	.188	4.78	9.38	5.0	330	0.772	1.8	64.0	62.2	—	—
Blue, Box	24570750	CMP											1.0	2.0	62.3	60.3	100±15	23.0
		CEC:											4.0	4.1	53.3	49.2	100±15	23.0
		CMP											8.0	5.8	48.8	43.0	100±15	23.0
													10.0	6.5	47.3	40.8	100±15	23.0
													16.0	8.2	44.3	36.0	100±15	23.0
													20.0	9.3	42.8	33.5	100±15	23.0
													25.0	10.4	41.3	30.9	100±15	22.0
													31.25	11.7	39.9	28.2	100±15	21.1
													62.5	17.0	35.4	18.4	100±15	18.1
													100.0	22.0	32.3	10.3	100±15	16.0
													155.0 [▶]	28.1	29.5	1.4	100±15	14.1



Jacket sequentially marked at 2 ft. intervals.

Featuring Descending Length Marking.

Third party verified to TIA/EIA-568-A, Category 5

ACR = Attenuation Crosstalk Ratio • DCR = DC Resistance • ELFEXT = Equal Level Far-end Crosstalk • NEXT = Near-end Crosstalk • PSUM = Power Sum • RL = Return Loss • UTP = Unshielded Twisted Pair(s)


[▶]Values provided for information only.**Color Codes: IBDN Plus**

Pair No.	Color Combination
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

DataTwist® 3 UTP Cable


TIA/EIA-568-A, Category 3 Nonbonded-Pair Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Weight		Nominal OD		Nominal DCR (Cond.)	Nom. Imped. (Ω)	Nominal Capacitance		Freq. (MHz)	Min. NEXT (dB)	Maximum Attenuation	
				Ft.	m	Lbs.	kg	Inch	mm			* pF/Ft.	* pF/m			(dB/ 1000')	(dB/ 100m)

24 AWG Solid Bare Copper Conductors • Twisted Pairs • See Color Code Chart (below)**Non-Plenum • Polyolefin Insulation • Gray PVC Jacket**

1227A1	NEC: CMR CEC: CMR	2	U-1000	U-304.8	13.0	6.0	.173	4.39	28.0Ω/M' 91.8Ω/km	100	19.0	62.3	1	41.0	7.8	2.56
													4	32.0	17.0	5.58
													10	26.0	30.0	9.71
													16	23.0	40.0	13.10
1229A1	NEC: CMR CEC: CMR	4	U-1000	U-304.8	22.0	10.0	.197	5.00								
1232A1	NEC: CMR CEC: CMR	25†	1000	304.8	104.0	47.2	.399	10.14								

Jacket sequentially marked at 2 ft. intervals.
Third party verified to TIA/EIA-568-A, Category 3

Plenum • Low-Smoke PVC Insulation • White Low-Smoke PVC Jacket

1243A2	NEC: CMP CEC: CMP	2	U-1000	U-304.8	14.0	6.4	.170	4.32	28.0Ω/M' 91.8Ω/km	100	19.0	62.3	1	41.0	7.8	2.56
													4	32.0	17.0	5.58
													10	26.0	30.0	9.71
													16	23.0	40.0	13.10
1245A2	NEC: CMP CEC: CMP	4	U-1000	U-304.8	23.0	10.4	.200	5.08								

Jacket sequentially marked at 2 ft. intervals.
Third party verified to TIA/EIA-568-A, Category 3

DCR = DC Resistance • NEXT = Near-end Crosstalk • UTP = Unshielded Twisted Pair(s)

*Capacitance between conductors

† 25-pair NEXT is Power Sum tested.

Not RoHS compliant at time of printing. Please check with Belden Technical Support for current compliance information at 1-800-BELDEN-1.

Color Codes: DataTwist 3

Pair No.	Color Combination
1	White/Blue Stripe & Blue/White Stripe
2	White/Orange Stripe & Orange/White Stripe
3	White/Green Stripe & Green/White Stripe
4	White/Brown Stripe & Brown/White Stripe
5	White/Gray Stripe & Gray/White Stripe
6	Red/Blue Stripe & Blue/Red Stripe
7	Red/Orange Stripe & Orange/Red Stripe
8	Red/Green Stripe & Green/Red Stripe
9	Red/Brown Stripe & Brown/Red Stripe
10	Red/Gray Stripe & Gray/Red Stripe
11	Black/Blue Stripe & Blue/Black Stripe
12	Black/Orange Stripe & Orange/Black Stripe
13	Black/Green Stripe & Green/Black Stripe

Pair No.	Color Combination
14	Black/Brown Stripe & Brown/Black Stripe
15	Black/Gray Stripe & Gray/Black Stripe
16	Yellow/Blue Stripe & Blue/Yellow Stripe
17	Yellow/Orange Stripe & Orange/Yellow Stripe
18	Yellow/Green Stripe & Green/Yellow Stripe
19	Yellow/Brown Stripe & Brown/Yellow Stripe
20	Yellow/Gray Stripe & Gray/Yellow Stripe
21	Purple/Blue Stripe & Blue/Purple Stripe
22	Purple/Orange Stripe & Orange/Purple Stripe
23	Purple/Green Stripe & Green/Purple Stripe
24	Purple/Brown Stripe & Brown/Purple Stripe
25	Purple/Gray Stripe & Gray/Purple Stripe

D-Inside and D-Flex Plenum UTP Cable


TIA/EIA-568-A and CSA T529-95, Category 3

Category 3 Nonbonded-pair Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		Max. DCR (Ω / 100m)	Max. DCR Unbal. (%)	Max. Cap. Unbal. (pF/ 100m)	Freq. (MHz)	Max. Atten. (dB/ 100m)	Min. NEXT (dB)	Input Imped. (Ω)	Min. SRL (dB)
				Ft.	m	Lbs.	kg	Inch	mm								

24 AWG Solid Bare Copper Conductors • Twisted Pairs • Rip Cord • See Color Code Chart (below)**Non-Plenum • Polyvinyl Chloride Insulation • Olive Gray Low-Smoke PVC Jacket**

Olive Gray, Box	24501922	NEC:	2	2500	762.0	11.0	4.99	0.13	3.30	9.38	5.0	262	0.772	2.2	43.0	—	—
Olive Gray, Box	24501934	CMR	3	1500	457.2	15.0	6.80	0.15	3.90				1.0	2.6	41.0	100±15	12.0
Olive Gray, Box	24501941	CEC:	4	1000	304.8	18.0	8.16	0.17	4.30				4.0	5.6	32.0	100±15	12.0
Olive Gray, Box	24501950	CMR	4	1500	457.2	18.0	8.16	0.17	4.30				8.0	8.5	28.0	100±15	12.0
Olive Gray, Reel	24501947		4	1000	304.8	18.0	8.16	0.17	4.30				10.0	9.7	26.0	100±15	12.0
													16.0	13.1	23.0	100±15	10.0



Rip Cord


Jacket sequentially marked at 2 ft. intervals.

Featuring Descending Length Marking.

Third party verified to TIA/EIA-568-A, Category 3

Plenum • Low Smoke Polyvinyl Chloride Insulation • Olive Gray Low-Smoke Jacket

Olive Gray, Box	24571097	NEC:	3	1500	457.2	16.0	7.26	0.16	4.06	9.38	5.0	262	0.772	2.2	43.0	—	—
Olive Gray, Box	24571111	CMP	4	1000	304.8	19.0	8.62	0.19	4.70				1.0	2.6	41.0	100±15	12.0
Olive Gray, Box	24571112	CEC:	4	1500	457.2	19.0	8.62	0.19	4.70				4.0	5.6	32.0	100±15	12.0
Olive Gray, Reel	24571110	CMP	4	1000	304.8	19.0	8.62	0.19	4.70				8.0	8.5	28.0	100±15	12.0
													10.0	9.7	26.0	100±15	12.0
													16.0	13.1	23.0	100±15	10.0



Rip Cord

Jacket sequentially marked at 2 ft. intervals.

Featuring Descending Length Marking.

Third party verified to TIA/EIA-568-A, Category 3

ACR = Attenuation Crosstalk Ratio • DCR = DC Resistance • ELFEXT = Equal Level Far-end Crosstalk • NEXT = Near-end Crosstalk • RL = Return Loss • UTP = Unshielded Twisted Pair(s)

Color Codes: D-Inside and D-Flex

Pair No.	Color Combination
1	White/Blue Stripe & Blue/White Stripe
2	White/Orange Stripe & Orange/White Stripe
3	White/Green Stripe & Green/White Stripe
4	White/Brown Stripe & Brown/White Stripe

D-Series Multipair UTP Cable


TIA/EIA-568-A and CSA T529-95, Category 3

Category 3 Nonbonded-pair Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		Max. DCR (Ω / 100m)	Max. DCR Unbal. (%)	Max. Cap. Unbal. (pF/ 100m)	Freq. (MHz)	Max. Atten. (dB/ 100m)	Min. PSUM NEXT (dB)	Input Imped. (Ω)	Min. SRL (dB)
				Ft.	m	Lbs.	kg	Inch	mm								

24 AWG Solid Bare Copper Conductors • Twisted Pairs • Rip Cord • See Color Code Chart (below)

Non-Plenum • Semi-Rigid Polyvinyl Chloride Insulation • Olive Gray PVC Jacket																	
Olive Gray, Reel	24501829	NEC:	6	1000	304.8	28.0	12.7	0.21	5.3	—	8.8	262	0.772	2.2	43.0	100±15	12.0
Olive Gray, Reel	24501837	CMR	12	1000	304.8	50.0	22.7	0.28	7.1				1.0	2.6	41.0	100±15	12.0
Olive Gray, Reel	24501848	CEC:	16	984	300.0	64.0	29.0	0.32	8.0				4.0	5.6	32.0	100±15	12.0
Olive Gray, Reel	24501858	CMR	25	1000	304.8	100.0	45.4	0.39	10.0				8.0	8.5	28.0	100±15	12.0
Olive Gray, Reel	24501877		50	1000	304.8	194.0	87.0	0.53	13.4				10.0	9.7	26.0	100±15	12.0
Olive Gray, Reel	24501887		75	2083	635.0	279.0	126.6	0.63	16.0				16.0	13.1	23.0	100±15	10.0
Olive Gray, Reel	24501897		100	1575	480.0	365.0	165.6	0.72	18.2								
Olive Gray, Reel	24501906		200	900	274.3	703.0	318.9	0.99	25.1								




Rip Cord

Jacket sequentially marked at 2 ft. intervals.

Featuring Descending Length Marking.

Third party verified to TIA/EIA-568-A, Category 3

Plenum • Low Smoke Polyvinyl Chloride Insulation • Low-Smoke PVC Jacket (Gray or Translucent)																	
Translucent, Reel	24571221	NEC:	25	1500	457.2	107.0	48.5	0.42	10.7	—	8.8	262	0.772	2.2	43.0	100±15	12.0
Gray, Reel	24571235	CMP	50	1000	304.8	211.0	95.7	0.49	12.4				1.0	2.6	41.0	100±15	12.0
Gray, Reel	24571250	CEC:	100	1500	457.2	415.0	188.2	0.72	18.3				4.0	5.6	32.0	100±15	12.0
Gray, Reel	24571265	CMP	200	1000	304.8	874.0	396.4	1.04	26.3				8.0	8.5	28.0	100±15	12.0
Gray, Reel	24571266		300	1000	304.8	1234.0	559.7	1.27	32.3				10.0	9.7	26.0	100±15	12.0
													16.0	13.1	23.0	100±15	10.0



Rip Cord

Jacket sequentially marked at 2 ft. intervals.

Featuring Descending Length Marking.

Third party verified to TIA/EIA-568-A, Category 3

ACR = Attenuation Crosstalk Ratio • DCR = DC Resistance • ELFEXT = Equal Level Far-end Crosstalk • NEXT = Near-end Crosstalk • PSUM = Power Sum • RL = Return Loss • UTP = Unshielded Twisted Pair(s)

Color Codes: D-Series Multipair

Pair No.	Tip	Ring
1	White/Blue	Blue/White
2	White/Orange	Orange/White
3	White/Green	Green/White
4	White/Brown	Brown/White
5	White/Slate	Slate/White
6	Red/Blue	Blue/Red
7	Red/Orange	Orange/Red
8	Red/Green	Green/Red
9	Red/Brown	Brown/Red
10	Red/Slate	Slate/Red
11	Black/Blue	Blue/Black
12	Black/Orange	Orange/Black
13	Black/Green	Green/Black


Pair No.	Tip	Ring
14	Black/Brown	Brown/Black
15	Black/Slate	Slate/Black
16	Yellow/Blue	Blue/Yellow
17	Yellow/Orange	Orange/Yellow
18	Yellow/Green	Green/Yellow
19	Yellow/Brown	Brown/Yellow
20	Yellow/Slate	Slate/Yellow
21	Violet/Blue	Blue/Violet
22	Violet/Orange	Orange/Violet
23	Violet/Green	Green/Violet
24	Violet/Brown	Brown/Violet
25	Violet/Slate	Slate/Violet

DataTwist® 5e ScTP Cable

TIA/EIA-568-B.2, Category 5e Nonbonded-Pair Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		Max. DCR (Ω / 100m)	Max. DCR Unbal. (%)	Max. Cap. Unbal. (pF/ 100m)	Freq. (MHz)	Max. Atten. (dB/ 100m)	Min. PSUM NEXT (dB)	Min. PSUM ACR (dB/ 100m)	Min. PSUM ELFEXT (dB/ 100m)	Input Imped. (Ω)	Min. RL (dB)
				Ft.	m	Lbs.	kg	Inch	mm										

24 AWG Solid Bare Copper Conductors • Twisted Pairs • Overall Beldfoil® Shield • Drain Wire* • RJ-45 Compatible • See Color Code Chart (below)**Non-Plenum • Polyolefin Insulation • PVC Jacket** (Available in Red, Orange, Yellow, Green, Blue, Gray or Black)


	1533R	NEC:	4	1000	304.8	34.0	15.5	.260	6.60	9.38	3.0	330	1	2.0	62.3	60	60.8	100±15	20.0
		CMR		A-1000	A-304.8	37.0	16.8						4	4.1	53.3	49	48.7	100±15	23.0
		CEC:		1640†	500.0	57.4	26.1						8	5.8	48.8	43	42.7	100±15	24.5
		CMR											10	6.5	47.3	41	40.8	100±15	25.0
													16	8.2	44.3	36	36.7	100±15	25.0
													20	9.3	42.8	34	34.7	100±15	25.0
													25	10.4	41.3	31	32.8	100±15	24.3
													31.25	11.7	39.9	28	30.9	100±15	23.6
													62.5	17.0	35.4	18	24.8	100±15	21.5
													100	22.0	32.3	10	20.8	100±15	20.1

†1640 ft. put-up available in Gray only.

Shield is bonded to jacket inner wall for electrical stability.

Jacket sequentially marked at 2 ft. intervals. • Third party verified to TIA/EIA-568-B.2, Category 5e


Non-Plenum • Polypropylene Insulation (Color Code: See Chart Below) • Black Low-Smoke, Zero-Halogen Jacket

	1300SB	NEC:	4	1000	304.8	35.0	15.9	.260	6.60	9.3	3.0	330	1	2.0	62.3	60	60.8	100±15	20.0
	new	CMG-LS											4	4.1	53.3	49	48.7	100±15	23.0
		CEC:											8	5.8	48.8	43	42.7	100±15	24.5
		CMG-LS FT4											10	6.5	47.3	41	40.8	100±15	25.0
		Limited											16	8.2	44.3	36	36.7	100±15	25.0
		Smoke											20	9.3	42.8	34	34.7	100±15	25.0
													25	10.4	41.3	31	32.8	100±15	24.3
													31.25	11.7	39.9	28	30.9	100±15	23.6
													62.5	17.0	35.4	18	24.8	100±15	21.5
													100	22.0	32.3	10	20.8	100±15	20.1

LSZH and ABS Type Approved

Jacket sequentially marked at 2 ft. intervals.

Plenum • FEP Teflon® Insulation • Flammarrest® Jacket (Available in Red, Orange, Yellow, Green, Blue, Gray, Black or Natural)

	1533P	NEC:	4	1000	304.8	35.0	15.9	.235	6.00	9.38	3.0	330	1	2.0	62.3	60	60.8	100±15	20.0
		CMP		A-1000	A-304.8	38.0	17.2						4	4.1	53.3	49	48.7	100±15	23.0
		CEC:											8	5.8	48.8	43	42.7	100±15	24.5
		CMP											10	6.5	47.3	41	40.8	100±15	25.0
													16	8.2	44.3	36	36.7	100±15	25.0
													20	9.3	42.8	34	34.7	100±15	25.0
													25	10.4	41.3	31	32.8	100±15	24.3
													31.25	11.7	39.9	28	30.9	100±15	23.6
													62.5	17.0	35.4	18	24.8	100±15	21.5
													100	22.0	32.3	10	20.8	100±15	20.1

Shield is bonded to jacket inner wall for electrical stability.

Jacket sequentially marked at 2 ft. intervals.

Third party verified to TIA/EIA-568-B.2, Category 5e

ACR = Attenuation Crosstalk Ratio • DCR = DC Resistance • ELFEXT = Equal Level Far-end Crosstalk • NEXT = Near-end Crosstalk • PSUM = Power Sum • RL = Return Loss
ScTP = Screened (Overall Foil) Twisted Pair(s)

*Drain wire is 24 AWG stranded tinned copper.

Color Codes: DataTwist 5e ScTP

Pair No.	Color Combination
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown


Teflon is a DuPont trademark.

DataTwist® 5 ScTP Cable

TIA/EIA-568-A, Category 5 Nonbonded-Pair Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		Max. DCR (Ω / 100m)	Max. DCR Unbal. (%)	Max. Cap. Unbal. (pF/ 100m)	Freq. (MHz)	Max. Atten. (dB/ 100m)	Min. PSUM NEXT (dB)	Input Imped. (Ω)	Min. SRL (dB)
				Ft.	m	Lbs.	kg	Inch	mm								

24 AWG Solid Bare Copper Conductors • Twisted Pairs • Overall Beldfoil® Shield • Drain Wire* • RJ-45 Compatible • See Color Code Chart (below)**Non-Plenum • Polyolefin Insulation • PVC Jacket** (Available in Red, Orange, Yellow, Green, Blue, Purple or Light Gray)


	1624R	NEC: CMR CEC: CMR	4	1000	304.8	33.0	15.0	.260	6.60	9.38	3.0	300	1	2.0	62.3	100±15	23.0
				A-1000	A-304.8	36.0	16.3						4	4.1	53.3	100±15	23.0
				1640†	500.0	54.1	24.7						8	5.8	48.8	100±15	23.0
													10	6.5	47.3	100±15	23.0
													16	8.2	44.3	100±15	23.0
													20	9.3	42.8	100±15	23.0
													25	10.4	41.3	100±15	22.0
													31.25	11.7	39.9	100±15	21.1
													65.5	17.0	35.4	100±15	18.0
													100	22.0	32.3	100±15	16.0

†1640 ft. put-up available in Gray only.

Shield is bonded to jacket inner wall for electrical stability.

Jacket sequentially marked at 2 ft. intervals. • Third party verified to TIA/EIA-568-A, Category 5

Plenum • FEP Teflon® Insulation • Flamarrest® Jacket (Available in Red, Orange, Yellow, Green, Blue, Purple, Gray or Natural)

	1624P	NEC: CMP CEC: CMP	4	1000	304.8	32.0	14.5	.230	5.84	9.38	3.0	300	1	2.0	62.3	100±15	23.0
				A-1000††	A-304.8	35.0	15.9						4	4.1	53.3	100±15	23.0
													8	5.8	48.8	100±15	23.0
													10	6.5	47.3	100±15	23.0
													16	8.2	44.3	100±15	23.0
													20	9.3	42.8	100±15	23.0
													25	10.4	41.3	100±15	22.0
													31.25	11.7	39.9	100±15	21.1
													65.5	17.0	35.4	100±15	18.0
													100	22.0	32.3	100±15	16.0

††A-1000 ft. put-up available in Yellow, Blue, Gray or Natural only.

Shield is bonded to jacket inner wall for electrical stability.

Jacket sequentially marked at 2 ft. intervals.

Third party verified to TIA/EIA-568-A, Category 5

DCR = DC Resistance • NEXT = Near-end Crosstalk • PSUM = Power Sum • RL = Return Loss • ScTP = Screened (Overall Foil) Twisted Pair(s)

*Drain wire is 24 AWG stranded tinned copper on 1624R and 24 AWG solid tinned copper on 1624P.

Color Codes: DataTwist 5 ScTP


Pair No.	Color Combination
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

VideoTwist® 6 UTP Cable for RGB Video

TIA/EIA-568-B.2-1, Category 6 Bonded-Pair Cables


Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		Max. DCR (Ω / 100m)	Max. DCR Unbal. (%)	Max. Cap. Unbal. (pF/ 100m)	Freq. (MHz)	Max. Atten. (dB/ 100m)	Min. PSUM NEXT (dB)	Min. PSUM ACR (dB/ 100m)	Min. PSUM ELFEXT (dB/ 100m)	Input Imped. (Ω)	Min. RL (dB)
				Ft.	m	Lbs.	kg	Inch	mm										

23 AWG Bonded-Pairs Solid BC Conductors • Twisted Pairs • Rip Cord • See Color Code Chart (below)**Non-Plenum • Polypropylene Insulation • PVC Jacket**

 Rip Cord	7989R	NEC: CMR CEC: CMG	4	1000 1640	304.8 500.0	32.0 52.5	14.5 23.8	.365 .165	9.27 4.12	9.0	3.0	49.2	1 4 10 16 31.25 62.5 100 200 250	2.0 3.8 6.0 7.6 10.7 15.4 19.8 29.0 32.8	72.3 63.3 57.3 54.3 49.9 45.4 42.3 37.8 36.3	70.3 59.5 51.3 46.7 39.2 30.0 22.5 8.8 3.5	64.8 52.7 44.8 40.7 34.9 28.8 24.8 18.7 16.8	100±15 100±15 100±15 100±15 100±15 100±15 100±15 100±22 100±32	20.0 23.0 25.0 25.0 23.6 21.5 20.1 18.0 17.3
--	--------------	----------------------------	---	--------------	----------------	--------------	--------------	--------------	--------------	-----	-----	------	--	--	--	--	--	--	--

Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 6

Plenum • FEP Insulation • Flamarrest® Jacket

 Rip Cord	7989P	NEC: CMP CEC: CMP	4	1000 1640	304.8 500.0	38.0 62.3	17.2 28.3	.365 .165	9.27 4.12	9.0	3.0	49.2	1 4 10 16 31.25 62.5 100 200 250	2.0 3.8 6.0 7.6 10.7 15.4 19.8 29.0 32.8	72.3 63.3 57.3 54.3 49.9 45.4 42.3 37.8 36.3	70.3 59.5 51.3 46.7 39.2 30.0 22.5 8.8 3.5	64.8 52.7 44.8 40.7 34.9 28.8 24.8 18.7 16.8	100±15 100±15 100±15 100±15 100±15 100±15 100±15 100±22 100±32	20.0 23.0 25.0 25.0 23.6 21.5 20.1 18.0 17.3
--	--------------	----------------------------	---	--------------	----------------	--------------	--------------	--------------	--------------	-----	-----	------	--	--	--	--	--	--	--

Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2-1, Category 6

ACR = Attenuation Crosstalk Ratio • BC = Bare Copper • DCR = DC Resistance • ELFEXT = Equal Level Far-end Crosstalk • NEXT = Near-end Crosstalk • PSUM = Power Sum • RL = Return Loss •
UTP = Unshielded Twisted Pair(s)**Color Codes: VideoTwist 6 RGB**


Pair No.	Color Combination
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

DataTwist® 5e UTP Cable for RGB Video

TIA/EIA-568-B.2, Category 5e Bonded and Nonbonded-Pair Cables


Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		Max. DCR (Ω / 100m)	Max. DCR Unbal. (%)	Max. Cap. Unbal. (pF/ 100m)	Freq. (MHz)	Max. Atten. (dB/ 100m)	Min. PSUM NEXT (dB)	Min. PSUM ACR (dB/ 100m)	Min. PSUM ELFEXT (dB/ 100m)	Input Imped. (Ω)	Min. RL (dB)
				Ft.	m	Lbs.	kg	Inch	mm										

Low Skew 24 AWG Bonded Pairs Solid BC Conductors • Twisted Pairs • Skew 9,0ns/100m nom. • Rip Cord • See Color Code Chart**Non-Plenum • Polyolefin Insulation • Green PVC Jacket**

 Rip Cord	7988R	NEC: CMR CEC: CMG	4	U-1000 U-1640	U-304.8 U-500.0	22.0 36.1	10.0 16.4	.204	5.18	9.0	3.0	66.0	1	2.0	65.3	60.3	60.8	100±15	20.0
													4	4.1	53.3	49.2	48.7	100±15	23.0
													10	6.5	47.3	40.8	40.8	100±15	25.0
													16	8.2	44.3	36.0	36.7	100±15	25.0
													31.25	11.7	39.9	28.2	30.9	100±15	23.6
													62.5	17.0	35.4	18.4	24.8	100±15	21.5
													100	22.0	32.3	10.3	20.8	100±15	20.1
													200	32.4	27.8	1.0	14.7	100±25	15.0

Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5e

Plenum • FEP Insulation • Green Flamarrest® Jacket

 Rip Cord	7988P	NEC: CMP CEC: CMP	4	U-1000 U-1640	U-304.8 U-500.0	23.0 37.7	10.4 17.1	.193	4.90	9.0	3.0	66.0	1	2.0	65.3	60.3	60.8	100±15	20.0
													4	4.1	53.3	49.2	48.7	100±15	23.0
													10	6.5	47.3	40.8	40.8	100±15	25.0
													16	8.2	44.3	36.0	36.7	100±15	25.0
													31.25	11.7	39.9	28.2	30.9	100±15	23.6
													62.5	17.0	35.4	18.4	24.8	100±15	21.5
													100	22.0	32.3	10.3	20.8	100±15	20.1
													200	32.4	27.8	1.0	14.7	100±25	15.0

Jacket sequentially marked at 2 ft. intervals. Third party verified to TIA/EIA-568-B.2, Category 5e

ACR = Attenuation Crosstalk Ratio • BC = Bare Copper • DCR = DC Resistance • ELFEXT = Equal Level Far-end Crosstalk • NEXT = Near-end Crosstalk • PSUM = Power Sum • RL = Return Loss • UTP = Unshielded Twisted Pair(s)


Color Codes: DataTwist 5e RGB

Pair No.	Color Combination
1	White/Blue Stripe & Blue
2	White/Orange Stripe & Orange
3	White/Green Stripe & Green
4	White/Brown Stripe & Brown

IEEE 802.3 • ISO/IEC 8802.3 10Base2 and 10Base5**Trunk Cables — Thinnet and Thicknet**

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

Thinnet 10Base2 • 20 AWG Stranded (19x32) .037" Tinned Copper Conductors • Duobond® II + Tinned Copper Braid Shield (93% Coverage)**Non-Plenum • Ethernet • Foam HDPE Insulation • Gray PVC Jacket**

	9907	NEC:	500	152.4	12.5	5.7	20 AWG	.102	2.59	Duobond II	.185	4.70	50	80%	25.4	83.3	1	.43	1.4
		CL2, CM	U-1000	U-304.8	25.0	11.4	(19x32)			+ 93%							10	1.30	4.3
		CEC:	1000	304.8	25.0	11.4	.037"			Tinned							50	2.90	9.5
		CM	1640	500.0	41.0	18.6	Tinned			Copper							100	4.20	13.8
			2500	762.0	62.5	28.4	Copper			Braid							200	6.10	20.0
			3280	1000.0	82.0	37.3	8.8Ω/M'			5.8Ω/M'							400	8.90	29.2

For Plenum versions of 9907, see 89907 or 82907.

DEC Part No. 17-01248-00

Plenum Ethernet • Foam FEP Insulation • Natural Flamarrest® Jacket

	82907	NEC:	500†	152.4	12.5	5.7	20 AWG	.095	2.41	Duobond II	.160	4.06	50	80%	25.4	83.3	1	.43	1.4
		CL2P, CMP	U-1000	U-304.8	23.0	10.5	(19x32)			+ 93%							10	1.30	4.3
		CEC:	1000†	304.8	24.0	10.9	.037"			Tinned							50	2.90	9.5
		CMP	2500†	762.0	57.5	26.1	Tinned			Copper							100	4.20	13.8
							Copper			Braid							200	6.10	20.0
							8.8Ω/M'			5.8Ω/M'							400	9.20	30.2

28.9Ω/km'

19.0Ω/km

Plenum Ethernet • Foam FEP Insulation • Gray Fluorocopolymer Jacket

	89907†	NEC:	500†	152.4	12.5	5.7	20 AWG	.095	2.41	Duobond II	.160	4.06	50	80%	25.4	83.3	1	.43	1.4
		CL2P, CMP	U-1000	U-304.8	24.0	10.9	(19x32)			+ 93%							10	1.30	4.3
		CEC:	1000†	304.8	24.0	10.9	.037"			Tinned							50	2.90	9.5
		CMP	2500†	762.0	60.0	27.3	Tinned			Copper							100	4.20	13.8
							Copper			Braid							200	6.10	20.0
							8.8Ω/M'			5.8Ω/M'							400	9.20	30.2


28.9Ω/km

19.0Ω/km

DEC Part No. 17-01246-00

Suitable for Outdoor and Direct Burial applications.

Thicknet 10Base5 • 12 AWG Solid .086" Bare Copper Conductor • Duobond IV* Quad Shield (100% Coverage)**Non-Plenum • Ethernet • Foam Polyethylene Insulation • Yellow PVC Jacket**


	9880	NEC:	500	152.4	66.0	30.0	12 AWG	.243	6.17	Duobond IV	.405	10.29	50	78%	26.0	85.0	1	.19▲	.62
		CL2, CM	1000	304.8	131.0	59.5	(solid)			(Duobond II							5	.37▲	1.21
		CEC:	1640	500.0	219.8	99.9	.086"			+ 94%							10	.52▲	1.71
		CM					Bare Copper			TC Braid							50	1.20▲	3.94
							1.42Ω/M'			+ Duofoil®							100	1.70▲	5.58
							4.66Ω/km			+ 90%							200	2.55▲	8.37

For Plenum version of 9880, see 89880.

DEC Part No. 17-00451-00

Ring-band stripes marked every 2.5 meters to aid users in tap placement.

Plenum Ethernet • Foam FEP Insulation • Orange Fluorocopolymer Jacket

	89880	NEC:	1000†	304.8	134.0	60.9	12 AWG	.245	6.22	Duobond IV	.375	9.53	50	78%	26.0	85.0	1	.18	.59
		CL2P, CMP	1640†	500.0	224.7	102.1	(solid)			(Duobond II							5	.37▲	1.21
		CEC:					.086"			+ 94%							10	.52▲	1.71
		CMP					Bare Copper			TC Braid							50	1.15	3.77
							1.42Ω/M'			+ Duofoil							100	1.65	5.41
							4.66Ω/km			+ 90%							200	2.45	8.04

1.52Ω/M'

5.0Ω/km

DEC Part No. 17-00324-00

Suitable for Outdoor and Direct Burial applications.

Ring-band stripes marked every 2.5 meters to aid users in tap placement.

DCR = DC Resistance • HDPE = High-density Polyethylene • TC = Tinned Copper

* Duobond IV = Duobond II (100% coverage) + tinned copper braid (90% coverage) + Duofoil® (100% coverage) + tinned copper braid (90% coverage).

Plenum version is Duobond II (100% coverage) + tinned copper braid (94% coverage) + Duofoil (100% coverage) + tinned copper braid (90% coverage).

† Spools are one piece, but length may vary ±10% from length shown.

▲ Maximum Attenuation

Not RoHS compliant at time of printing. Please check with Belden Technical Support for current compliance information at 1-800-BELDEN-1.

IEEE 802.3 • ISO/IEC 8802.3 10Base5

Transceiver Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Wt.		Conductor (stranding) Nom. DCR	Shielding Materials Nom. DCR	Nominal OD		Drain Wire	Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance			
					Ft.	m	Lbs.	kg			Inch	mm				* pF/Ft.	* pF/m	** pF/Ft.	** pF/m

28 and 24 AWG Stranded TC Conductors • Twisted Pairs • Overall Polyester Isolation Tape + Duofoil® + TC Braid Shield (92% Coverage) • Drain Wire

Non-Plenum • Polypropylene Insulation • Light Gray PVC Jacket

UL AWM Style 2919 (30V 80°C)	9903 	NEC: CMG CEC: CMG	4	Gray/White, Yellow/Orange, Blue/Green, Black/Red	500 1000	152.4 304.8	21.5 43.0	9.8 19.5	3 Pair: 28 AWG (7x36) TC 65.0Ω/M' 213.0Ω/km 1 Pair: 24 AWG (7x32) TC 24.0Ω/M' 78.7Ω/km Each Pair Individually Beldfoil® Shielded	Polyester Isolation Tape + Duofoil + 92% Tinned Copper Braid 2.9Ω/M' 9.5Ω/km	.250 6.35	24 AWG Stranded Tinned Copper	78*	66%	19.7	64.6	34.8	114.2
------------------------------------	--	----------------------------	---	---	-------------	----------------	--------------	-------------	---	---	--------------	---	-----	-----	------	------	------	-------



Duofoil®

Polyester Tape

Z-Fold®

* 3 Pairs

- 3 Pairs

20 AWG Stranded (7x28) TC Conductors • Twisted Pairs • Overall Polyester Isolation Tape + Duofoil + TC Braid Shield (95% Coverage) • Drain Wire

Non-Plenum • Datalene® Insulation • Light Gray PVC Jacket

UL AWM	9901	NEC:	4	Gray/White,	500	152.4	53.5	24.3	20 AWG	Polyester	.415	10.54	22	78	78%	16.7	54.8	29.5	96.8
Style 2919		CL2, CM		Yellow/Orange,	1000	304.8	106.0	48.2	(7x28)	Isolation			AWG						
(30V 80°C)		CEC:		Blue/Green,					Tinned	Tape			Stranded						
		CM		Black/Red					Copper	+ Duofoil			Tinned						
									Each Pair	+ 95%			Copper						
									Individually	Tinned			Braid						
									Beldfoil®	Copper									
									Shielded										
									10.5Ω/M'	2.0Ω/M'									
									34.4Ω/km	6.6Ω/km									

For Plenum version of 9901,
see 89901.

For Plenum version of 9901,
see 89901.

DEC Part No. 17-01320-00

UL AWM Style 2919 (30V 80°C)	9902 	NEC: CL2, CM CEC: CM	5	Gray/White, Yellow/Orange, Blue/Green, Red/Brown, Red/Black	500 1000	152.4 304.8	76.0 145.0	34.5 65.9	20 AWG (7x28) Tinned Copper Each Pair Individually Beldfoil Shielded 10.5Ω/M' 34.4Ω/km	Polyester Isolation Tape + Duofoil + 95% Tinned Copper Braid 1.65Ω/M' 5.4Ω/km	.495	12.58	20 AWG Stranded Tinned Copper	78	78%	16.7	54.8	29.5	96.8
------------------------------------	--	-------------------------------	---	---	-------------	----------------	---------------	--------------	---	--	------	-------	---	----	-----	------	------	------	------

Plenum • FEP Teflon® Insulation†† • Light Gray Fluorocopolymer (PVDF) Jacket

150°C	89901	NEC:	4	Gray/White,	500 ^{††}	152.4	51.5	23.4	20 AWG	Polyester	.370	9.40	22	78	78%	16.7	54.8	29.5	96.8
		CMP		Yellow/Orange,	1000 ^{††}	304.8	104.0	47.3	(7x28)	Isolation			AWG						
		CEC:		Blue/Green,					Tinned	Tape			Stranded						
		CMP		Red/Black					Copper	+ Duofoil			Tinned						
Z-Fold®									Each Pair	+ 95%			Copper						
									Individually	Tinned			Braid						
Duofoil									Beldfoil	Copper									
									Shielded	Braid									
									10.5Ω/M'	1.5Ω/M'									
									34.4Ω/km	4.9Ω/km									

^{††}Foam FEP (data pairs) and solid FEP (power pair).

DEC Part No. 17-01319-00 • Suitable for Outdoor and Direct Burial applications.

DCR = DC Resistance • TC = Tinned Copper

* Capacitance between conductors.

** Capacitance between one conductor and other conductors connected to shield.




†† Spools are one piece, but length may vary $\pm 10\%$ from length shown.

 Not RoHS compliant at time of printing. Please check with Belden Technical Support for current compliance information at 1-800-BELDEN-1.

Teflon is a DuPont trademark.

IEEE 802.3 • Ethernet 10Base5

Transceiver Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Wt.		Conductor (stranding) Nom. DCR	Shielding Materials Nom. DCR	Nominal OD		Drain Wire	Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance			
					Ft.	m	Lbs.	kg			Inch	mm				* pF/Ft.	* pF/m	** pF/Ft.	** pF/m
20 AWG Stranded (7x28) .038" TC Cond. • Twisted Pairs • Beldfoil® (100% Coverage) + Polyester Tape + TC Braid Shield (95% Cov.) • Drain Wire																			
Non-Plenum • Ethernet • Datalene® Insulation • Light Blue PVC Jacket																			
UL AWM Style 2919 (30V 80°C)	9892	NEC: CM, CL2 CEC: CM	4	Gray/White, Yellow/Orange, Blue/Green, Black/Red	500 1000	152.4 304.8	51.5 101.0	23.4 45.9	20 AWG (7x28) .038" Tinned Copper 9.5Ω/M' 31.2Ω/km	Polyester Isolation Tape + 95% Tinned Copper Copper Braid 1.9Ω/M' 6.2Ω/km	.398 10.1	22 AWG (7x30) Tinned Copper	78	78%	16.7	54.8	29.5	96.8	
																			
Drain Wire																			
Polyester Tape																			
20 AWG Stranded (7x28) .038" TC Conductors • Twisted Pairs • Beldfoil® Inner + Overall Duofoil® (100% Coverage) + TC Braid Shield (95% Cov.)																			
Plenum • Ethernet • Foam FEP Insulation (Data) • Solid FEP Insulation (Power) • Brown Fluorocopolymer Jacket																			
	89892	NEC: CMP CEC: CMP	4	Gray/White, Yellow/Orange, Blue/Green, Red/Black	500 1000	152.4 304.8	50.0 101.0	22.7 45.9	20 AWG (7x28) .038" Tinned Copper 9.5Ω/M' 31.2Ω/km	Polyester Isolation Tape + Duofoil + 95% Tinned Copper Braid 1.5Ω/M' 4.9Ω/km	.359 9.1	22 AWG (7x30) Tinned Copper	78	78%	16.7	54.8	29.5	96.8	
																			
Drain Wire																			
Duofoil®																			
Polyester Tape																			
Z-Fold®																			
20 and 22 AWG Stranded TC Conductors • Twisted Pairs • Beldfoil® Inner Shield (100% Coverage) + Overall TC Braid Shield (95% Coverage)																			
Non-Plenum • Ethernet • Foam HDPE (22 AWG) and PVC (20 AWG) Insulation • Light Blue PVC Jacket																			
UL AWM Style 2919 (30V 80°C)	9891	NEC: CM CEC: CM	4	Black/White, Yellow/Orange, Blue/Green, Gray/Purple	100 500 1000	30.4 152.4 304.8	7.4 36.0 70.0	3.7 16.3 16.3	3 Pair: (7x28) (7x30) TC 14.7Ω/M' 48.23Ω/km Foam HDPE Insulation 1 Pair: 20 AWG (7x28) TC 9.5Ω/M' 31.1Ω/km PVC Insulation	Each Pair Individually Beldfoil® Shielded, Overall Duofoil + 95% Tinned Copper Braid 1.8Ω/M' 5.9Ω/km	.316 8.0	22 AWG (7x30) Tinned Copper	78*	78%*	16.7*	54.8*	29.5*	96.8*	
																			
Drain Wire																			
Duofoil®																			
Polyester Tape																			
Z-Fold®																			
* 3 Pairs																			

*3 Pairs

DCR = DC Resistance • HDPE = High-density Polyethylene • TC = Tinned Copper

* Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

 Not RoHS compliant at time of printing. Please check with Belden Technical Support for current compliance information at 1-800-BELDEN-1.

IEEE 802.4 MAP & Mini-MAP • IEEE 802.7**Broadband Coaxial Cables**

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m
RG-6/U Type • 18 AWG Solid Bare Copper-covered Steel Conductor • Duobond® IV* Quad Shield (100% Coverage)																			
Non-Plenum • Gas-injected Foam Polyethylene Insulation • Gray PVC Jacket																			
	3131A	NEC:	1000 **	304.8	41.0	18.6	18 AWG	.180	4.57	Duobond IV	.300	7.62	75	82%	16.2	53.1	1	.35	1.2
		CL2R,	2500 †	762.2	102.5	46.5	(solid)			Quad Shield							2	.38	1.3
		CMR					.040"			3.6Ω/M'							5	.45	1.5
		CEC:					BCCS			11.8Ω/km							10	.59	1.9
		CMG					28.0Ω/M'										20	.86	2.8
							91.8Ω/km										50	1.37	4.5
																	100	1.97	6.5
																	200	2.82	9.3
																	300	3.48	11.4
																	400	4.04	13.3
Tap marks every 2.6 meters to aid users in installation.																			
Plenum • Foam FEP Insulation • Gray Fluorocopolymer Jacket																			
150°C	3132A	NEC:	1000 **	304.8	36.0	16.4	18 AWG	.170	4.32	Duobond IV	.274	6.96	75	82%	16.3	53.5	1	.36	1.2
		CMP					(solid)			Quad Shield							2	.38	1.3
		CEC:					.040"			3.6Ω/M'							5	.50	1.6
		CMP					BCCS			11.8Ω/km							10	.65	2.1
							28.0Ω/M'										20	.95	3.1
							91.8Ω/km										50	1.50	4.9
																	100	2.12	7.0
																	200	2.99	9.8
																	300	3.66	12.0
																	400	4.23	13.9
Tap marks every 2.6 meters to aid users in installation. Suitable for Outdoor and Direct Burial applications.																			

BCCS = Bare Copper Covered Steel • DCR = DC Resistance

*Duobond IV Quad Shield = Duobond + 60% aluminum braid + Duofoil® + 40% aluminum braid.

†Spools are one piece, but length may vary ±10% from length shown.

**1000' exact 1 pc.

 Not RoHS compliant at time of printing. Please check with Belden Technical Support for current compliance information at 1-800-BELDEN-1.

IEEE 802.4 MAP & Mini-MAP • IEEE 802.7**Broadband Coaxial Cables**

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation			
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m	
RG-11/U Type • 14 AWG Solid Bare Copper-covered Steel Conductor • Duobond IV* Quad Shield (100% Coverage)																				
Non-Plenum • Gas-injected Foam Polyethylene Insulation • Gray PVC Jacket																				
	3094A 	NEC:	500 **	152.4	31.0	14.1	14 AWG	.280	7.11	Duobond IV	.407	10.34	75	82%	16.2	53.1	1	.16	.5	
		CL2R,	1000 **	304.8	62.0	28.2	(solid)			Quad Shield							2	.18	.6	
		CMR	2000 †	609.6	122.0	55.3	.064"			1.5Ω/M'							5	.26	.9	
		CEC:					BCCS			4.9Ω/km							10	.38	1.2	
		CMG					11.0Ω/M'										20	.55	1.8	
							36.1Ω/km										50	.83	2.7	
																	100	1.17	3.8	
																	200	1.60	5.3	
																	300	1.99	6.6	
																	400	2.30	7.6	
Tap marks every 2.6 meters to aid users in installation.																				
Plenum • Foam FEP Insulation • Gray Fluorocopolymer Jacket																				
150°C	3095A 	NEC:	1000 **	304.8	76.0	34.5	14 AWG	.280	7.11	Duobond IV	.387	9.83	75	82%	16.5	54.1	1	.17	.6	
		CMP					(solid)			Quad Shield							2	.22	.7	
		CEC:					.064"			3.9Ω/M'							5	.28	.9	
		CMP					BCCS			12.8Ω/km							10	.40	1.3	
							11.0Ω/M'										20	.60	2.0	
							36.1Ω/km										50	1.20	3.9	
																	100	1.70	5.6	
																	200	2.50	8.2	
																	300	3.04	10.0	
																	400	3.50	11.5	
Tap marks every 2.6 meters to aid users in installation.																				
Suitable for Outdoor and Direct Burial applications.																				

BCCS = Bare Copper Covered Steel • DCR = DC Resistance

*Duobond IV Quad Shield = Duobond + 60% aluminum braid + Duofoil® + 40% aluminum braid.

†Spools are one piece, but length may vary ±10% from length shown.

**500' & 1000' exact 1 pc.

 Not RoHS compliant at time of printing. Please check with Belden Technical Support for current compliance information at 1-800-BELDEN-1.

IEEE 802.5; ISO/IEC 8802.5

IBM Cabling System

Types 1A and 1

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		AWG (stranding) Diameter Nom. DCR	Shielding	Nom. Imped. (Ω)	Nominal Capacitance		Freq. (MHz)	Maximum Attenuation		Min. NEXT	
				Ft.	m	Lbs.	kg	Inch	mm				* pF/Ft.	* pF/m		(dB/ 1000')	(dB/ 100m)	(dB/ 3280')	(dB/ 1000m)

IBM Type 1A • 22 AWG Solid BC Conductors • Each Pair Individually Beldfoil® Shielded + Overall TC Braid Shield (65% Coverage) • Rip Cord**Non-Plenum • Flame-retardant Foam Polyethylene Insulation • Black PVC Jacket**

IBM Part No.	9688	NEC:	2	500†	152.4	26.5	12.0	.296	7.52	22	100%	150	8.5	27.9	4	6.7	2.2	58.0	58.0
4716748		CMG		1000†	304.8	50.0	22.7	x	x	(solid)	Beldfoil				16	13.4	4.4	50.4	50.4
33G2772		CEC:		2000†	609.8	102.0	46.3	.431	10.95	BC	Each Pair				100	37.5	12.3	38.5	38.5
		CMG		3600†	1097.6	190.8	86.5			.026"	+ 65%				300	65.2	21.4	31.3	31.3
										16.7Ω/M'	TC Braid				100††	40.8	13.4	—	—
										54.7Ω/km	Overall				300††	71.0	23.3	—	—
															600††	100.3	32.9	—	—



Rip Cord

Meets IEEE 802.5 and TIA/EIA-568-A specifications, ETL verified. For Token Ring (4/16 Mbps), FDDI over copper, and video applications.
IBM qualified Type 1A Media cable for use in IBM Cabling Systems. For Non-suffix "A" Type IBM Product, see 1634A below.

Plenum • Foam FEP Teflon® Insulation • Black Flamarrest® Jacket

IBM Part No.	82688	NEC:	2	1000†	304.8	47.0	21.4	.248	6.30	22	100%	150	8.5	27.9	4	6.7	2.2	58.0	58.0
4716749		CMP						x	x	(solid)	Beldfoil				16	13.4	4.4	50.4	50.4
33G8220		CEC:						.348	8.84	BC	Each Pair				100	37.5	12.3	38.5	38.5
		CMP								.026"	+ 65%				300	65.2	21.4	31.3	31.3
										16.7Ω/M'	TC Braid				100††	40.8	13.4	—	—
										54.7Ω/km	Overall				300††	71.0	23.3	—	—
															600††	100.3	32.9	—	—



Rip Cord

Meets IEEE 802.5 and TIA/EIA-568-A specifications, ETL verified.
IBM qualified Type 1A Media cable for use in IBM Cabling Systems. For Token Ring (4/16 Mbps), FDDI over copper, and video applications.

IBM Type 1 • 22 AWG Solid BC Conductors • Each Pair Individually Beldfoil Shielded + Overall TC Braid Shield (65% Coverage) • Rip Cord**Non-Plenum • Flame-retardant Foam Polyethylene Insulation • Black PVC Jacket**

IBM Part No.	1634A	NEC:	2	1000†	304.8	50.0	22.7	.296	7.52	22	100%	150	8.5	27.9	4	6.7	2.2	58.0	58.0
4716748		CMG		2000†	609.8	102.0	46.4	x	x	(solid)	Beldfoil				16	13.4	4.4	40.0	40.0
		CEC:		3600†	1097.6	190.8	86.7	.431	10.95	BC	Each Pair								
		CMG								.026"	+ 65%								
										17.4Ω/M'	TC Braid								
										57.1Ω/km	Overall								



Rip Cord

Meets IEEE 802.5 and TIA/EIA-568-A specifications, ETL verified. For Token Ring (4/16 Mbps), FDDI over copper, and video applications.
IBM qualified Type 1 Media cable for use in IBM Cabling Systems. For Suffix A counterpart see 9688 above.

DCR = DC Resistance • BC = Bare Copper • NEXT = Near-end Crosstalk • TC = Tinned Copper

* Capacitance between conductors

† Spools are one piece, but length may vary ±10% from length shown.

†† Common mode

 Not RoHS compliant at time of printing. Please check with Belden Technical Support for current compliance information at 1-800-BELDEN-1.

Teflon is a DuPont trademark.

BELDEN

For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com


Belden114@CableCon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr

IEEE 802.5; ISO/IEC 8802.5**IBM Cabling System****Types 2A and 6A**

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Standard Lengths		Standard Unit Wt.		Nominal OD		AWG (stranding) Diameter Nom. DCR	Shielding	Nom. Imped. (Ω)	Nominal Capacitance		Freq. (MHz)	Maximum Attenuation		Min. NEXT	
				Ft.	m	Lbs.	kg	Inch	mm				* pF/Ft.	* pF/m		(dB/ 1000')	(dB/ 100m)	(dB/ 3280')	(dB/ 1000m)

IBM Type 2A • 22 AWG Solid Bare Copper Conductors • Each Pair Individually Beldfoil® Shielded + Overall TC Braid Shield (65% Coverage)**Non-Plenum • Flame-retardant Foam Polyethylene Insulation • Black PVC Jacket**


IBM Part No.	9689	NEC:	6*	1000 [†]	304.8	80.0	36.4	.324	8.23	22	100%	150	8.5	27.9	1k**	.390	.128	—	—
4716739		CMG		3600 [†]	1097.6	298.8	135.8	x	x	(solid)	Beldfoil	@ 1MHz	(data)	(data)	4	6.7	2.2	58.0	58.0
33G2773		CEC:						.466	11.84	BC	Each Pair	(data)			16	13.4	4.4	50.4	50.4
		CMG								.026"	+ 65%	600			100	37.5	12.3	38.5	38.5
										16.7Ω/M'	TC Braid	@ 1kHz			300	65.2	21.4	31.3	31.3
										54.7Ω/km	Overall	(voice)			100 ^{††}	40.8	13.4	—	—
											(data only)				300 ^{††}	71.0	23.3	—	—
															600 ^{††}	100.3	32.9	—	—

For Plenum version of 9689,
see 82689.

IBM qualified Type 2A Media cable for use in IBM Cabling Systems.

Plenum • Foam FEP Teflon® Insulation • Black Flamarrest® Jacket

IBM Part No.	82689	NEC:	6*	1000 [†]	304.8	79.0	35.9	.324	8.23	22	100%	150	8.5	27.9	1k**	.390	.128	—	—
4716738		CMP						x	x	(solid)	Beldfoil	@ 1MHz	(data)	(data)	4	6.7	2.2	58.0	58.0
33G8221		CEC:						.460	11.68	BC	Each Pair	(data)			16	13.4	4.4	50.4	50.4
		CMP								.026"	+ 65%	600			100	37.5	12.3	38.5	38.5
										16.7Ω/M'	TC Braid	@ 1kHz			300	65.2	21.4	31.3	31.3
										54.7Ω/km	Overall	(voice)			100 ^{††}	40.8	13.4	—	—
											(data only)				300 ^{††}	71.0	23.3	—	—
															600 ^{††}	100.3	32.9	—	—



IBM qualified Type 2A Media cable for use in IBM Cabling Systems.

IBM Type 6A • 26 AWG Stranded (7x34) BC Conductors • Twisted Pairs • Beldfoil Shielded Pairs + Overall TC Braid Shield (65% Coverage)**Non-Plenum • Datalene® Insulation • Striated Black PVC Jacket**

IBM Part No.	1215A	NEC:	2	1000 [†]	304.8	46.0	20.9	.325	8.26	26	100%	150	8.5	27.9	4	10	3.3	52.0	52.0
4716743		CL2, CM								(7x34)	Beldfoil				16	20	6.6	44.0	44.0
33G2775		CEC:								BC	Each Pair				100	57	18.7	33.0	33.0
		CM								.019"	+ 65%	300			300	100	32.3	25.0	25.0
										38.7Ω/M'	TC Braid								
										127.0Ω/km	Overall								



IBM qualified Type 6A Office cable for use in IBM Cabling Systems.

BC = Bare Copper • DCR = DC Resistance • NEXT = Near-end Crosstalk • TC = Tinned Copper

* Capacitance between conductors

**Voice pairs (1 kHz); Data pairs (4–600 MHz)

† Spools are one piece, but length may vary ±10% from length shown.

†† Common mode

^ (2) shielded Data-grade pairs; (4) unshielded Voice-grade media pairs

Not RoHS compliant at time of printing. Please check with Belden Technical Support for current compliance information at 1-800-BELDEN-1.

Teflon is a DuPont trademark.

BELDENFor more information, contact **Belden Technical Support: 1-800-BELDEN-1 • www.belden.com****Belden114@CableCon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr**