


CSA Instrumentation Cable

300V CIC

Description	Part Number	No. of Pairs or Triads	Cable Weight		Jacket Thickness		Nominal OD	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm

16 AWG Pairs Stranded (7x24) TC Conductors • Individual Beldfoil® + Polyester Isolation Tape • Overall Beldfoil Shield (100% Coverage)**PVC Insulation • Black PVC Jacket** (Color Code: Black and White with Numbers)


CSA C22.2#239, Type CIC	22646*	1	122	182	.045	1.14	.320	8.13
CSA C22.2 #0.3 Clause 4.31 Low Acid Gas FT4 Flame Test	22628	2	262	390	.045	1.14	.520	13.21
	22629	4	438	652	.060	1.52	.628	15.95
	22630	6	603	897	.060	1.52	.740	18.80
	22631	8	752	1119	.060	1.52	.800	20.32
	22632	12	1148	1708	.080	2.03	1.010	25.65
	22685	16	1461	2174	.080	2.03	1.120	28.45
	22686	24	2091	3112	.080	2.03	1.380	35.05



-25°C Installed
-40°C to +105°C (Dry) (75°C Wet)

16 AWG Triads Stranded (7x24) TC Conductors • Individual Beldfoil + Polyester Isolation Tape • Overall Beldfoil Shield (100% Coverage)**PVC Insulation • Black PVC Jacket** (Color Code: Black, White and Red with Numbers)

CSA C22.2#239, Type CIC	22603*	1	152	226	.045	1.14	.329	8.36
CSA C22.2 #0.3 Clause 4.31 Low Acid Gas FT4 Flame Test	22687	2	344	512	.045	1.14	.580	14.73
	22675	4	564	839	.060	1.52	.670	17.02
	22688	6	819	1219	.060	1.52	.780	19.81
	22689	8	1063	1582	.080	2.03	.940	23.88
	22690	12	1524	2268	.080	2.03	1.080	27.43



-25°C Installed
-40°C to +105°C (Dry) (75°C Wet)

TC = Tinned Copper

*One pair/triad cables have one shield and drain wire