


CSA Instrumentation Cable

600V CIC

Description	Part Number	No. of Pairs or Triads	Cable Weight		Jacket Thickness		Nominal OD	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm

18 AWG Pairs Stranded (7x26) TC Conductors • Individual Beldfoil® + Polyester Isolation Tape • Overall Beldfoil Shield (100% Coverage)**PVC Insulation • Black PVC Jacket** (Color Code: Black and White with Numbers)


CSA C22.2#239, Type CIC	22417*	1	109	162	.045	1.14	.32	8.13
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	22405	2	229	341	.045	1.14	.51	12.95
	22404	4	374	557	.060	1.52	.63	16.00
	22418	8	632	941	.060	1.52	.79	20.07
	22421	12	970	1444	.080	2.03	1.00	25.40
	22419	24	1741	2591	.080	2.03	1.36	34.54



-25°C Installed
-40°C to +105°C (Dry) (75°C Wet)

18 AWG Triads Stranded (7x26) TC Conductors • Individual Beldfoil + Polyester Isolation Tape • Overall Beldfoil Shield (100% Coverage)**PVC Insulation • Black PVC Jacket** (Color Code: Black, White and Red with Numbers)


CSA C22.2#239, Type CIC	22442*	1	131	195	.045	1.14	.34	8.64
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	22443	2	299	445	.060	1.52	.58	14.73
	22444	4	476	708	.060	1.52	.68	17.27
	22445	8	893	1329	.080	2.03	.88	22.35



-25°C Installed
-40°C to +105°C (Dry) (75°C Wet)

16 AWG Pairs Stranded (7x24) TC Conductors • Individual Beldfoil + Polyester Isolation Tape • Overall Beldfoil Shield (100% Coverage)**PVC Insulation • Black PVC Jacket** (Color Code: Black and White with Numbers)


CSA C22.2#239, Type CIC	22416*	1	129	192	.045	1.14	.34	8.64
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	22409	2	229	341	.045	1.14	.59	14.99
	22410	4	469	698	.060	1.52	.68	17.27
	22446	6	667	993	.060	1.52	.79	20.07
	22411	8	841	1252	.080	2.03	.90	22.86
	22412	12	1235	1838	.080	2.03	1.09	27.69
	22447	24	2250	3349	.080	2.03	1.49	37.85



-25°C Installed
-40°C to +105°C (Dry) (75°C Wet)

16 AWG Triads Stranded (7x24) TC Conductors • Individual Beldfoil + Polyester Isolation Tape • Overall Beldfoil Shield (100% Coverage)**PVC Insulation • Black PVC Jacket** (Color Code: Black, White and Red with Numbers)

CSA C22.2#239, Type CIC	22413*	1	167	249	.045	1.14	.36	9.14
CSA C22.2#0.3, Clause 4.31 Low Acid Gas FT4 Flame Test	22448	2	372	554	.045	1.14	.62	15.88
	22414	4	606	902	.060	1.52	.72	18.29
	22415	8	1144	1703	.080	2.03	.96	24.38



-25°C Installed
-40°C to +105°C (Dry) (75°C Wet)

TC = Tinned Copper

*One pair/triad cables have one foil shield and drain wire