


CSA Instrumentation Cable**600V ACIC Armored Cables**

Description	Part No.		No. of Pairs/Triads	Cable Weight Aluminum Armor		Cable Weight Steel Armor		Insulation Thickness		Nominal OD Inner Jacket		Nominal OD Outer Jacket	
	Aluminum Armor	Steel Armor		Lbs./1000 Ft.	kg/km	Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm

18 AWG Pairs Stranded (7x26) TC Cond. • Individual Beldfoil® + Polyester Isolation Tape • Overall Beldfoil Shield (100% Coverage)

Interlocked Armor • PVC Insulation* • PVC Inner Jacket • Chrome PVC Outer Jacket

CSA C22.2#239, Type ACIC	24511**	25506**	1	154	229	257	382	.030	.76	.32	8.13	.61	15.49
CSA C22.2#174, HLBCD	24512	25514	2	238	354	387	575	.030	.76	.51	12.95	.82	20.83
CSA C22.2#0.3, Clause 4.31	24513	25503	4	335	499	504	750	.030	.76	.63	16.00	.93	23.62
Low Acid Gas, FT4 Flame Test	24514	25505	8	536	798	829	1233	.030	.76	.79	20.27	1.15	29.21
	24515	25501	12	739	1100	1092	1624	.030	.76	1.00	25.40	1.36	34.54
	24520	25517	24	1169	1740	1674	2490	.030	.76	1.36	34.54	1.75	44.45




-25°C Installed • -40°C to +105°C (Dry) (75°C Wet)

18 AWG Triads Stranded (7x26) TC Conductors • Individual Beldfoil + Polyester Isolation Tape • Overall Beldfoil Shield (100% Coverage)

Interlocked Armor • PVC Insulation* • PVC Inner Jacket • Chrome PVC Outer Jacket

CSA C22.2#239, Type ACIC	24516**	25500**	1	166	247	276	411	.030	.76	.34	8.64	.63	16.00
CSA C22.2#174, HLBCD	24517	25522	2	293	436	455	677	.030	.76	.58	14.73	.89	22.61
CSA C22.2#0.3, Clause 4.31	24518	25520	4	391	582	572	851	.030	.76	.66	16.76	.99	25.15
Low Acid Gas, FT4 Flame Test	24519	25523	8	673	1002	988	1470	.030	.76	.88	22.35	1.29	32.77




-25°C Installed • -40°C to +105°C (Dry) (75°C Wet)

16 AWG Pairs Stranded (7x24) TC Cond. • Individual Beldfoil + Polyester Isolation Tape • Overall Beldfoil Shield (100% Coverage)

Interlocked Armor • PVC Insulation* • PVC Inner Jacket • Chrome PVC Outer Jacket

CSA C22.2#239, Type ACIC	24500**	25504**	1	171	254	279	415	.030	.76	.34	8.64	.64	16.26
CSA C22.2#174, HLBCD	24505	25510	2	299	445	455	677	.030	.76	.59	14.99	.89	22.61
CSA C22.2#0.3, Clause 4.31	24502	25511	4	450	670	583	868	.030	.76	.68	17.27	.98	24.89
Low Acid Gas, FT4 Flame Test	24506	25512	6	576	857	880	1310	.030	.76	.79	20.07	1.16	29.46
	24503	25513	8	679	1010	1005	1496	.030	.76	.90	22.86	1.27	32.26
	24504	25518	12	908	1351	1280	1905	.030	.76	1.09	27.69	1.46	37.08
	24510	25519	24	1502	2235	2030	3021	.030	.76	1.49	37.85	1.88	47.75




-25°C Installed • -40°C to +105°C (Dry) (75°C Wet)

16 AWG Triads Stranded (7x24) TC Conductors • Individual Beldfoil + Polyester Isolation Tape • Overall Beldfoil Shield (100% Coverage)

Interlocked Armor • PVC Insulation* • PVC Inner Jacket • Chrome PVC Outer Jacket

CSA C22.2#239, Type ACIC	24501**	25502**	1	195	290	309	460	.030	.76	.36	9.14	.66	16.76
CSA C22.2#174, HLBCD	24507	25507	2	339	505	465	692	.030	.76	.62	15.75	.94	23.88
CSA C22.2#0.3, Clause 4.31	24508	25509	4	464	691	793	1180	.030	.76	.72	18.29	1.05	26.67
Low Acid Gas, FT4 Flame Test	24509	25508	8	807	1201	1250	1860	.030	.76	.96	24.38	1.33	33.78



-25°C Installed • -40°C to +105°C (Dry) (75°C Wet)

Color Code: Pairs — Black and White with Numbers.
Triads — Black, White and Red with Numbers.

TC = Tinned Copper

*Note: Add D suffix for XLPE insulation. Example: 24511D.
**One pair/triad cables have one foil shield and drain wire


BELDEN

For more information, contact **Belden Technical Support: 1-800-BELDEN-1 • www.belden.com**


Belden114@CableCon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr

CSA Control Cable

600V ACIC Cables

Description	Part No.	No. of Cond.	Cable Weight		Inner Jacket OD		Armor OD		Outer Jacket		Maximum Pull Tension		Minimum Bend Radius	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm	Lbs.	N	Inch	mm
18 AWG Stranded (7x26) Bare Copper Conductors • 18 AWG Bare Copper Ground Wire														
Aluminum Interlocked Armor • .030" (.76mm) XLPE Insulation • PVC Inner Jacket • Blue PVC Outer Jacket														
CSA C22.2#239 FT4 Flame Test	29030	2	163	243	.32	8.13	.52	13.21	.62	15.75	44	196	7.4	187.96
 Rip Cord	29031	3	177	263	.34	8.64	.54	13.72	.64	16.26	66	294	7.6	193.04
	29032	4	195	290	.37	9.40	.57	14.48	.67	17.02	88	392	8.0	203.20
	29033	5	219	326	.41	10.41	.61	15.49	.71	18.03	110	490	8.5	215.90
	29034	6	239	356	.45	11.43	.65	16.51	.75	19.05	132	587	9.0	228.60
	29035	7	245	365	.45	11.43	.65	16.51	.75	19.05	154	685	9.0	228.60
	29036	8	266	396	.48	12.19	.68	17.27	.78	19.81	176	783	9.3	236.22
	29038	10	331	493	.56	14.22	.76	19.30	.87	22.10	220	979	10.6	269.24
	29040	12	353	525	.62	15.75	.82	20.83	.93	23.62	264	1175	11.1	281.94
	29043	15	401	597	.65	16.51	.85	21.59	.96	24.38	330	1469	11.5	292.10
	29048	20	466	694	.73	18.54	.93	23.62	1.04	26.42	440	1958	12.4	314.96
HAZ LOC CSA C22.2#0.3 Clause 4.31 Low Acid Gas	29053	25	589	877	.79	20.07	1.05	26.67	1.16	29.46	550	2448	13.9	353.06
	29058	30	698	1039	.88	22.35	1.14	28.96	1.25	31.75	660	2937	15.0	381.00
	29068	40	827	1231	.97	24.64	1.23	31.24	1.35	34.29	880	3916	16.2	411.48
	29078	50	965	1436	1.09	27.69	1.35	34.29	1.47	37.34	1100	4895	17.6	447.04

16 AWG Stranded (7x24) Bare Copper Conductors • 16 AWG Bare Copper Ground Wire

Description	Part No.	No. of Cond.	Cable Weight		Inner Jacket OD		Armor OD		Outer Jacket		Maximum Pull Tension		Minimum Bend Radius	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm	Lbs.	N	Inch	mm
16 AWG Stranded (7x24) Bare Copper Conductors • 16 AWG Bare Copper Ground Wire														
Aluminum Interlocked Armor • .030" (.76mm) XLPE Insulation • PVC Inner Jacket • Blue PVC Outer Jacket														
CSA C22.2#239 FT4 Flame Test	29017	2	202	301	.34	8.64	.54	13.72	.65	16.51	70	312	7.7	195.58
 Rip Cord	29004	3	221	329	.36	9.14	.56	14.22	.66	16.76	105	467	7.9	200.66
	29018	4	242	360	.39	9.91	.59	14.99	.70	17.78	140	623	8.3	210.82
	29019	5	264	393	.42	10.67	.62	15.75	.73	18.54	175	779	8.6	218.44
	29005	6	292	435	.46	11.68	.66	16.76	.77	19.56	210	935	9.1	231.14
	29020	7	314	467	.47	11.94	.67	17.02	.77	19.56	245	1090	9.2	233.68
	29021	8	364	542	.50	12.70	.70	17.78	.80	20.32	280	1246	9.6	243.84
	29022	10	412	613	.61	15.49	.81	20.57	.92	23.37	350	1558	10.9	276.86
	29006	12	441	656	.63	16.00	.83	21.08	.94	23.88	420	1869	11.2	284.48
	29023	15	502	748	.68	17.27	.88	22.35	1.00	25.40	525	2336	11.9	302.26
	29007	20	636	947	.77	19.56	1.03	26.16	1.13	28.70	700	3115	13.7	347.98
HAZ LOC CSA C22.2#0.3 Clause 4.31 Low Acid Gas	29024	25	845	1258	.89	22.61	1.15	29.21	1.26	32.00	875	3894	15.1	383.54
	29008	30	922	1372	.94	23.88	1.20	30.48	1.30	33.02	1050	4673	15.8	401.32
	29009	40	1109	1650	1.06	26.92	1.32	33.53	1.41	35.81	1400	6230	17.3	439.42
	29016	50	1306	1944	1.19	30.23	1.45	36.83	1.54	39.12	1750	7788	18.8	477.52
	29025	60	1390	2070	1.27	32.26	1.53	38.86	1.66	42.16	2100	9345	19.9	505.46

XLPE = Cross-linked Polyethylene

Color Code: #1 conductor is white; remaining conductors are black with number coding. Other color codes available upon request.