



CSA Control Cable

600V ACIC Cables

Description	Part No.	No. of Cond.	Cable Weight		Inner Jacket OD		Armor OD		Outer Jacket		Maximum Pull Tension		Minimum Bend Radius	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm	Lbs.	N	Inch	mm
18 AWG Stranded (7x26) Bare Copper Conductors • 18 AWG Bare Copper Ground Wire														
Aluminum Interlocked Armor • .030" (.76mm) XLPE Insulation • PVC Inner Jacket • Blue PVC Outer Jacket														
CSA C22.2#239 FT4 Flame Test	29030	2	163	243	.32	8.13	.52	13.21	.62	15.75	44	196	7.4	187.96
 Rip Cord	29031	3	177	263	.34	8.64	.54	13.72	.64	16.26	66	294	7.6	193.04
	29032	4	195	290	.37	9.40	.57	14.48	.67	17.02	88	392	8.0	203.20
	29033	5	219	326	.41	10.41	.61	15.49	.71	18.03	110	490	8.5	215.90
	29034	6	239	356	.45	11.43	.65	16.51	.75	19.05	132	587	9.0	228.60
	29035	7	245	365	.45	11.43	.65	16.51	.75	19.05	154	685	9.0	228.60
	29036	8	266	396	.48	12.19	.68	17.27	.78	19.81	176	783	9.3	236.22
	29038	10	331	493	.56	14.22	.76	19.30	.87	22.10	220	979	10.6	269.24
	29040	12	353	525	.62	15.75	.82	20.83	.93	23.62	264	1175	11.1	281.94
	29043	15	401	597	.65	16.51	.85	21.59	.96	24.38	330	1469	11.5	292.10
	29048	20	466	694	.73	18.54	.93	23.62	1.04	26.42	440	1958	12.4	314.96
HAZ LOC CSA C22.2#0.3 Clause 4.31 Low Acid Gas	29053	25	589	877	.79	20.07	1.05	26.67	1.16	29.46	550	2448	13.9	353.06
	29058	30	698	1039	.88	22.35	1.14	28.96	1.25	31.75	660	2937	15.0	381.00
	29068	40	827	1231	.97	24.64	1.23	31.24	1.35	34.29	880	3916	16.2	411.48
29078	50	965	1436	1.09	27.69	1.35	34.29	1.47	37.34	1100	4895	17.6	447.04	

16 AWG Stranded (7x24) Bare Copper Conductors • 16 AWG Bare Copper Ground Wire

Description	Part No.	No. of Cond.	Cable Weight		Inner Jacket OD		Armor OD		Outer Jacket		Maximum Pull Tension		Minimum Bend Radius	
			Lbs./1000 Ft.	kg/km	Inch	mm	Inch	mm	Inch	mm	Lbs.	N	Inch	mm
16 AWG Stranded (7x24) Bare Copper Conductors • 16 AWG Bare Copper Ground Wire														
Aluminum Interlocked Armor • .030" (.76mm) XLPE Insulation • PVC Inner Jacket • Blue PVC Outer Jacket														
CSA C22.2#239 FT4 Flame Test	29017	2	202	301	.34	8.64	.54	13.72	.65	16.51	70	312	7.7	195.58
 Rip Cord	29004	3	221	329	.36	9.14	.56	14.22	.66	16.76	105	467	7.9	200.66
	29018	4	242	360	.39	9.91	.59	14.99	.70	17.78	140	623	8.3	210.82
	29019	5	264	393	.42	10.67	.62	15.75	.73	18.54	175	779	8.6	218.44
	29005	6	292	435	.46	11.68	.66	16.76	.77	19.56	210	935	9.1	231.14
	29020	7	314	467	.47	11.94	.67	17.02	.77	19.56	245	1090	9.2	233.68
	29021	8	364	542	.50	12.70	.70	17.78	.80	20.32	280	1246	9.6	243.84
	29022	10	412	613	.61	15.49	.81	20.57	.92	23.37	350	1558	10.9	276.86
	29006	12	441	656	.63	16.00	.83	21.08	.94	23.88	420	1869	11.2	284.48
	29023	15	502	748	.68	17.27	.88	22.35	1.00	25.40	525	2336	11.9	302.26
	29007	20	636	947	.77	19.56	1.03	26.16	1.13	28.70	700	3115	13.7	347.98
HAZ LOC CSA C22.2#0.3 Clause 4.31 Low Acid Gas	29024	25	845	1258	.89	22.61	1.15	29.21	1.26	32.00	875	3894	15.1	383.54
	29008	30	922	1372	.94	23.88	1.20	30.48	1.30	33.02	1050	4673	15.8	401.32
	29009	40	1109	1650	1.06	26.92	1.32	33.53	1.41	35.81	1400	6230	17.3	439.42
	29016	50	1306	1944	1.19	30.23	1.45	36.83	1.54	39.12	1750	7788	18.8	477.52
	29025	60	1390	2070	1.27	32.26	1.53	38.86	1.66	42.16	2100	9345	19.9	505.46

XLPE = Cross-linked Polyethylene

Color Code: #1 conductor is white; remaining conductors are black with number coding. Other color codes available upon request.