

Line Level Analog Audio Cable

Double-Pair Cables



Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

22 AWG Stranded (7x30) TC Conductors • Twisted Pairs • Individual Beldfoil® Shield (100% Coverage) • Stranded TC Common Drain Wire

Polypropylene Insulation • Chrome PVC Jacket (Pairs Cabled on Common Axis to Reduce Diameter)

<p>Z-Fold®</p>	300V RMS 60°C	8723	NEC: CM	2	Red/Black, Green/White	100	30.5	2.3	1.0	.008	.20	—	—	.160	4.06	35	115	62	203
			CEC: CM			U-500	U-152.4	10.5	4.8										
						500	152.4	10.0	4.5										
						U-1000	U-304.8	20.0	9.1										
						1000	304.8	20.0	9.1										
						1640	499.9	32.8	14.9										
						U-2000	U-609.6	38.0	17.2										
						2000	609.6	40.0	18.2										
						3280	999.7	65.6	29.8										
						5000	1524.0	95.0	43.2										
					10000	3048.0	200.0	90.9											

For Plenum versions of 8723, see 88723, 87723 or 82723.

Polypropylene Insulation • Black Low-Smoke, Zero-Halogen Jacket (Pairs Cabled on Common Axis to Reduce Diameter)

<p>Z-Fold®</p>	LSZH and ABS Type Approved 300V RMS 60°C	8723SB new	NEC: CMG-LS	2	Red & Black, Green & White	1000	304.8	26.0	11.8	—	—	—	—	.196	4.98	35	115	62	203
			CEC: CMG-LS FT4 Limited Smoke																

Polypropylene Insulation • Black Low-Smoke, Zero-Halogen Jacket

<p>Z-Fold®</p>	LSZH and ABS Type Approved 300V RMS	8777SB new	NEC: CMG-LS	3	See Chart 3	1000†	304.8	39.0	17.7	.010	.25	—	—	.273	6.93	30	98	55	180
			CEC: CMG-LS FT4 Limited Smoke		(Tech Info Section)														

Plenum • FEP Insulation • Red FEP Jacket (Pairs Cabled on Common Axis to Reduce Diameter)

<p>Z-Fold®</p>	300V RMS 200°C	88723	NEC: CMP	2	Red/Black, Green/White	100†	30.5	3.4	1.5	.006	.15	—	—	.148	3.76	35	115	67	220
			CEC: CMP FT6			500†	152.4	11.0	5.0										
						1000†	304.8	19.0	8.6										

Plenum • FEP Insulation • Red Fluorocopolymer Jacket (Pairs Cabled on Common Axis to Reduce Diameter)

<p>Z-Fold®</p>	300V RMS 150°C	87723	NEC: CMP	2	Red/Black, Green/White	500†	152.4	11.0	5.0	.006	.15	—	—	.148	3.76	35	115	67	220
			CEC: CMP FT6			1000†	304.8	18.0	8.2										

Plenum • FEP Insulation • Natural Flamarrest® Jacket (Pairs Cabled on Common Axis to Reduce Diameter)

<p>Z-Fold®</p>	300V RMS 75°C	82723	NEC: CMP	2	Red/Black, Green/White	U-500†	U-152.4	10.5	4.8	.006	.15	—	—	.153	3.89	43	141	75	246
			CEC: CMP FT6			U-1000†	U-304.8	20.0	9.1										
						1000†	304.8	19.0	8.6										
						U-2000†	U-609.6	40.0	18.1										

FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper

* Capacitance between conductors.

** Capacitance between one conductor and other conductors connected to shield.

† Spools and/or UnReel® cartons are one piece, but length may vary ±10% for spools and ±5% for UnReel from length shown.