

Analog Multi-Pair Snake Cable

Flexible, CM Rated Cables
 Individually Shielded and Jacketed Twisted Pairs



Individually Shielded and Jacketed Pairs

NEC: CM (CEC: CM)

Product Description

24 AWG stranded (7x32) tinned copper conductor. Polyolefin insulation. Twisted pairs individual Beldfoil® shield (100% coverage) and have numbered and color-coded PVC jackets (see Chart 7 in Technical Information Section for colors). Jackets and shields are bonded so both strip simultaneously. Overall Beldfoil shield and 24 AWG tinned copper drain wire, plus overall Matte Black PVC jacket and nylon rip cord.


Color Code: Red, Black.

Specifications

Nominal OD — Conductor	.024" (.61mm)
Nominal OD — Insulation	.040" (1.02mm)
Inner Pair Jacket OD	.111" (2.82mm)
Approvals	
NEC	CM
CEC	CM
Nominal DCR	
Conductor	23.3Ω/M' (76.4Ω/km)
Shield (Inner Pair)	15.9Ω/M' (52.2Ω/km)
Voltage Rating	300V RMS
Temperature Rating	75°C
Nominal Impedance	50Ω
Nominal Velocity of Propagation	66%
Nominal Capacitance	
Between Conductors	31 pF/Ft. (102 pF/m)
Between Conductor/Shield*	58 pF/Ft. (191 pF/m)

DCR = DC Resistance

*Capacitance between one conductor and other conductors connected to shield.



Part No.	No. of Pairs	Standard Lengths		Standard Unit Weight		Nominal OD	
		Ft.	m	Lbs.	kg	Inch	mm

Flexible, CM Rated Twisted Pairs NEC: CM (CEC: CM)

24 AWG							
1509C	2	500	152.4	24.0	10.9	.301	7.65
		1000	304.8	46.0	20.9		
1510C	4	500	152.4	35.5	16.1	.352	8.94
		1000	304.8	72.0	32.6		
1511C	6	500	152.4	52.0	23.6	.418	10.61
		1000	304.8	102.0	46.3		
1512C	8	500	152.4	65.5	29.7	.452	11.48
		1000	304.8	124.0	56.3		
1513C (DT-12)	12	500	152.4	89.5	40.6	.561	14.25
		1000	304.8	178.0	80.7		
1514C	16	500	152.4	122.5	55.6	.628	15.95
		1000	304.8	241.0	109.3		
1515C	20	500	152.4	142.5	64.6	.710	19.56
		1000	304.8	288.0	130.6		
1516C	24	500	152.4	180.5	81.9	.807	20.50
		1000	304.8	371.0	168.3		
1517C	26	500	152.4	187.5	85.1	.823	20.90
		1000	304.8	385.0	174.6		
1518C	32	500	152.4	236.5	107.3	.897	22.78
		1000	304.8	481.0	218.2		
1519C	52	500	152.4	372.5	169.0	1.117	28.37
		1000	304.8	731.0	331.6		