

Speaker Wire and Cable

Electrolytic Tough Pitch (ETP) High-Conductivity Copper Speaker Cables
Parallel Zip Constructions




Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
				Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

24 AWG Stranded (7x32) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

PVC Insulation (Available in Clear, White, Brown or Chrome)

300V 60°C (Clear)	8782	—	2	U-1000 [▲]	U-304.8	7.0	3.2	.017	.43	.058	1.47
300V 75°C (Chrome, Brown, White)				1000 [◆]	304.8	6.0	2.7			x	x
										.116	2.95




[▲]U-1000 ft. put-up available in Brown or Chrome only.

[◆]1000 ft. put-up available in White or Clear only.

22 AWG Stranded (7x30) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

Clear PVC Insulation


300V 60°C	9712	—	2	1000	304.8	9.0	4.1	.017	.43	.065	1.65
										x	x
										.130	3.30



20 AWG Stranded (7x28) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

Clear or Chrome PVC Insulation


300V 60°C (Clear)	8649	—	2	1000	304.8	12.0	5.5	.018	.46	.073	1.85
300V 75°C (Chrome)										x	x
VW-1										.146	3.71



18 AWG Stranded (16x30) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

Clear PVC Insulation


300V 60°C	9708	—	2	U-500	U-152.4	11.0	5.0	.032	.81	.110	2.79
				500	152.4	10.5	4.8			x	x
				U-1000	U-304.8	21.0	9.5			.220	5.59
				1000	304.8	21.0	9.5				



16 AWG Stranded (26x30) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

Clear PVC Insulation


300V 60°C	9716	—	2	U-1000	U-304.8	27.0	12.2	.027	.69	.115	2.92
				1000	304.8	26.0	11.8			x	x
										.230	5.84



14 AWG Stranded (19x27) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

Clear PVC Insulation


300V 60°C	9717	—	2	U-1000	U-304.8	42.0	19.1	.035	.89	.146	3.71
				1000	304.8	42.0	19.1			x	x
										.292	7.42



12 AWG Stranded (65x30) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

Clear PVC Insulation

300V 60°C	9718	—	2	500	152.4	33.0	15.0	.045	1.14	.185	4.70
				1000	304.8	66.0	30.0			x	x
										.370	9.40



Speaker Wire and Cable

Electrolytic Tough Pitch (ETP) High-Conductivity Copper Speaker Cables
Open Twisted Construction



Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
				Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

22 AWG Stranded (7x30) ETP High-conductivity Copper Conductors • Cabled: (1) Tinned, (1) Bare

PVC Insulation • (Color Code: White)

UL Listed. Wires Misc. 90V 90°C VW-1	9151	—	2	U-1000	U-304.8	7.0	3.2	.012	.30	.108	2.74
--	-------------	---	---	--------	---------	-----	-----	------	-----	------	------



18 AWG Stranded (7x26) ETP High-conductivity Tinned Copper Conductors • Cabled

PVC Insulation • (Color Code: Black, Natural)

UL AWM Style 1007 (300V 80°C) VW-1	8460	—	2	U-1000 1000	U-304.8 304.8	18.0	8.2	.020	.51	.180	4.57
--	-------------	---	---	----------------	------------------	------	-----	------	-----	------	------



18 AWG Stranded (19x30) ETP High-conductivity Bare Copper Conductors • Cabled

Plenum • Flamarrest® Insulation • (Color Code: Black, Natural)

75°C	1863A	NEC: CL2P	2	1000	304.8	19.0	8.6	.022	.56	.178	4.52
------	--------------	--------------	---	------	-------	------	-----	------	-----	------	------



16 AWG Stranded (19x29) ETP High-conductivity Tinned Copper Conductors • Cabled

PVC Insulation • (Color Code: Black & Natural for 8470; Black & Orange for 9497)

UL AWM Style 1007 (300V 80°C) VW-1	8470	—	2	500 U-1000	152.4 U-304.8	13.0	5.9	.023	.58	.210	5.33
--	-------------	---	---	---------------	------------------	------	-----	------	-----	------	------



	9497	—	2	1000	304.8	30.0	13.6	.023	.58	.210	5.33
--	-------------	---	---	------	-------	------	------	------	-----	------	------

16 AWG Stranded (19x29) ETP High-conductivity Bare Copper Conductors • Cabled

Plenum • Flamarrest Insulation • (Color Code: Black, Natural)

75°C	1862A	NEC: CL2P	2	1000	304.8	26.0	11.8	.022	.56	.202	5.13
------	--------------	--------------	---	------	-------	------	------	------	-----	------	------



Speaker Wire and Cable

Electrolytic Tough Pitch (ETP) High-Conductivity Copper Speaker Cables
Open Twisted Construction



Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
				Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

14 AWG Stranded (19x27) ETP High-conductivity Bare Copper Conductors • Cabled

Plenum • Flamarrest® Insulation • (Color Code: Black, Natural)

150V RMS 75°C,	1861A	NEC: CL2P	2	1000	304.8	36.0	16.3	.022	.56	.236	5.99
----------------	--------------	--------------	---	------	-------	------	------	------	-----	------	------



12 AWG Stranded (19x25) ETP High-conductivity Bare Copper Conductors • Cabled

Plenum • Flamarrest Insulation • (Color Code: Black, Natural)


150V RMS 75°C,	1860A	NEC: CL2P	2	1000	304.8	58.0	26.4	.022	.56	.270	6.86
----------------	--------------	--------------	---	------	-------	------	------	------	-----	------	------



Speaker Wire and CableElectrolytic Tough Pitch (ETP) High-Conductivity Copper Speaker Cables
Twisted Jacketed Construction


Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD	
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm

22 AWG Stranded (7x30) Tinned Copper Conductors • Conductors Cabled**PVC Insulation • Chrome PVC Jacket**


300V RMS 60°C	8442	NEC:	2	Black,	100	30.5	2.4	1.0	.015	.38	.025	.64	.170	4.32
		CMG:		Red	U-500	U-152.4	7.5	3.4						
		CEC:			500	152.4	7.5	3.4						
		CMG FT4			U-1000	U-304.8	15.0	6.8						
					1000	304.8	15.0	6.8						
					10000	3048.0	150.0	68.2						

For Plenum versions of 8442, see 88442 or 82442.


20 AWG Stranded (7x28) Tinned Copper Conductors • Twisted Pair**PVC Insulation • Chrome PVC Jacket**

300V RMS 80°C	8205	NEC:	2	Black,	100	30.5	2.6	1.2	.013	.33	.025	.64	.180	4.57
		CMG:		Red	U-500	U-152.4	9.0	4.1						
		CEC:			500	152.4	9.0	4.1						
		CMG FT4			U-1000	U-304.8	17.0	7.7						
					1000	304.8	18.0	8.2						


18 AWG Stranded (7x26) Tinned Copper Conductors • Twisted Pair**PVC Insulation • Chrome PVC Jacket**

300V RMS 80°C	8461	NEC:	2	Black,	100	30.5	3.2	1.4	.022	.56	.028	.71	.234	5.94
		CMG:		White	U-500	U-152.4	13.5	6.1						
		CEC:			500	152.4	13.5	6.1						
		CMG FT4			U-1000	U-304.8	26.0	11.8						
					1000	304.8	27.0	12.2						

16 AWG Stranded (19x29) Tinned Copper Conductors • Twisted Pair**PVC Insulation • Chrome PVC Jacket**


UL AWM Style 2598 (300V 60°C) (80°C non-UL)	8471	NEC:	2	Black,	U-500	U-152.4	20.0	9.1	.023	.58	.032	.81	.274	6.96
		CMG:		White	500	152.4	20.0	9.1						
		CEC:			U-1000	U-304.8	38.0	17.2						
		CMG FT4			1000	304.8	40.0	18.2						

14 AWG Stranded (42x30) Tinned Copper Conductors • Twisted Pair**PVC Insulation • Chrome PVC Jacket**

UL AWM Style 2587 (600V 90°C)	8473	NEC:	2	Black,	U-500	U-152.4	29.0	13.2	.031	.79	.032	.81	.340	8.64
		CL3		White	500	152.4	30.5	13.9						
		CEC:			1000	304.8	58.0	26.4						
		FAS 90 FT4												

See NEC Guidelines for applicable CL3 voltage ratings (300V RMS).

12 AWG Stranded (65x30) Tinned Copper Conductors • Twisted Pair**PVC Insulation • Chrome PVC Jacket**

UL AWM Style 2587 (600V 90°C)	8477	NEC:	2	Black,	U-500	U-152.4	41.5	18.8	.032	.81	.035	.89	.386	9.80
		CL3R		White	500	152.4	43.5	19.7						
					1000	304.8	85.0	38.6						

See NEC Guidelines for applicable CL3 voltage ratings (300V RMS).