

Security and Alarm Cable

Commercial Applications

Shielded



Shielded Multi-conductor

CMR/CMG FT4 Rated

Product Description

Bare copper conductors, PVC insulation, cabled, Beldfoil® shield tape (foil side out) with drain wire, Gray PVC jacket with rip cord. Sequential footage marking every two feet.

Color Code: See chart below.


Specifications

Conductor	Bare Copper
Insulation	PVC
Insulation Thickness	.010" (.254mm)
Shield	Beldfoil
Jacket	PVC
Approvals	
NEC	CMR
CEC	CMG FT4
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications


- Security Systems
- Intercom/PA Systems
- Sound/Audio Systems
- Power-Limited Controls

Solid Conductor



Shorting Fold

Stranded Conductor



Shorting Fold

Color Code Chart

Cond. No.	Color
1	Black
2	Red
3	White
4	Green
5	Brown
6	Blue
7	Orange
8	Yellow
9	Purple
10	Gray

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

Shielded Multi-conductor (NEC CMR and CEC CMG FT4)

24 AWG										
5600FE	2	7	U-1000 1000	U-305 305	11.0 10.0	5.0 4.5	.015	.38	.120	3.05
22 AWG										
5520FE	2	solid	C-500 C-1000 U-1000 1000	C-152 C-305 U-305 305	6.5 13.0 14.0 14.0	3.0 5.9 6.4 6.4	.015	.38	.125	3.18
5500FE	2	7	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	5.5 6.5 6.5 12.0 12.0	2.5 3.0 3.0 5.4 5.4	.015	.38	.130	3.30
5521FE	3	solid	U-1000 1000	U-305 305	12.0 12.0	5.4 5.4	.015	.38	.132	3.35
5501FE	3	7	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	7.0 8.0 7.5 15.0 15.0	3.2 3.6 3.4 6.8 6.8	.015	.38	.138	3.51
5502FE	4	7	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	8.5 9.5 9.5 18.0 18.0	3.9 4.3 4.3 8.2 8.2	.015	.38	.152	3.86
5503FE	5	7	1000	305	22.0	10.0	.015	.38	.165	4.19
5504FE	6	7	C-500 U-500 U-1000 1000	C-152 U-152 U-305 305	13.5 15.0 29.0 29.0	6.1 6.8 13.2 13.2	.015	.38	.179	4.55
5506FE	8	7	U-500 U-1000 1000	U-152 U-305 305	16.5 32.0 32.0	7.5 14.5 14.5	.015	.38	.196	4.98
5508FE	10	7	U-500 U-1000 1000	U-152 U-305 305	19.5 38.0 44.0	8.9 17.2 20.0	.015	.38	.230	5.84
20 AWG										
5400FE	2	7	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	8.0 9.0 8.5 17.0 17.0	3.6 4.1 3.9 7.2 7.2	.015	.38	.145	3.68
5401FE	3	7	U-500 500 U-1000 1000	U-152 152 U-305 305	11.0 10.5 21.0 21.0	5.0 4.8 9.5 9.5	.015	.38	.153	3.89
5402FE	4	7	C-500 U-500 500 U-1000 1000	C-152 U-152 152 U-305 305	12.0 12.5 13.0 25.0 26.0	5.4 5.7 5.9 11.3 11.8	.015	.38	.168	4.27
5403FE	5	7	U-1000 1000	U-305 305	30.0 30.0	13.6 13.6	.015	.38	.184	4.67
5405FE	7	7	U-1000 1000	U-305 305	39.0 40.0	17.7 18.2	.015	.38	.201	5.11
5407FE	9	7	1000	305	51.0	23.2	.015	.38	.236	5.99