

## Communication and Control Cable

Pro Audio and Intercom Systems  
 Overall Shielded, Plenum-Rated



### Overall Shielded Pairs

CMP FT6 Rated

### Product Description

Bare copper conductors, FEP insulation, twisted pairs cabled with a Beldfoil® shield tape (foil side out) and drain wire. Natural Flamarrest® jacket.

**Color Code:** Black & Red and Black & White pairs.

### Specifications

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	FEP
<b>Insulation Thickness</b>	.0060" (.152mm)
<b>Shield</b>	Beldfoil
<b>Jacket</b>	Flamarrest
<b>Approvals</b>	
NEC	CMP
CEC	CMP FT6
<b>NEC Articles</b>	800
<b>Voltage Rating</b>	300V
<b>Temperature Rating</b>	75°C

### Applications

- Pro Audio Systems
- Intercom/PA Systems
- Security Systems



Part No.	No. of Pairs	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

### Overall Shielded Pairs (NEC CMP and CEC CMP FT6)

24 AWG										
<b>6641FC</b>	2	7	U-500	U-152	8.0	3.6	.015	.38	.164	4.17