

Access Control Banana Peel® Cable

Lock Power, Card Reader, Door Contact, REX Applications
Plenum-Rated



**Composite
Shielded Multi-Conductors**
CMP FT6 Rated

Product Description


Stranded bare copper conductors, Flamarrest® insulation and jackets. No overall jacket. All cables are Beldfoil® shielded (100% coverage) with drain wire and rip cord. Cable jackets are color coded by application. Individual jacket is sequentially marked at two foot intervals.

Specifications

Conductor	Bare Copper
Insulation	Flamarrest
Shield	Beldfoil
Individual Jackets	Flamarrest
Overall Jacket	None
Approvals	
NEC	CMP
CEC	CMP FT6
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Security Systems
- Power-Limited Controls
- Access Control
- Card Reader
- Lock Power
- Door Control
- REX

**Individual Cable Jacket Color Coding System**

Jacket Color	Print Legend	Cable Type
Orange	Card Reader	3/P, 18 or 22 AWG, Shielded
White	Door Contact	2/C, 18 or 22 AWG, Shielded
Blue	Rex/Spare	4/C, 18 or 22 AWG, Shielded
Gray	Lock Power	4/C, 16 or 18 AWG, Shielded

Part No.	Component Descriptions	Insulation Material & (Color Code)	Jacket Material & Component OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Composite Shielded Multi-Conductors (NEC CMP and CEC CMP FT6)

(3) Shielded Multi-Conductors • (1) Shielded Multi-Pair										
658AFS <small>NEW</small>	(1) 3-Pair 22 AWG Stranded (7x30) Bare Copper Shielded	Flamarrest (Black & Red, White & Green, Orange & Brown)	Orange Flamarrest	.420	10.67	500	152	60	27.2	
				.218	5.54	1000	304	113	51.3	
	(1) 2-Cond. 22 AWG Stranded (7x30) Bare Copper Shielded	Flamarrest (Black, Red)	White Flamarrest	.131	3.33					
	(1) 4-Cond. 22 AWG Stranded (7x30) Bare Copper Shielded	Flamarrest (Black, Red, White, Green)	Blue Flamarrest	.150	3.81					
638AFS <small>NEW</small>	(1) 3-Pair 18 AWG Stranded (7x26) Bare Copper Shielded	Flamarrest (Black & Red, White & Green, Orange & Brown)	Orange Flamarrest	.542	13.77	1000	305	189	85.7	
				.291	7.39					
	(1) 2-Cond. 18 AWG Stranded (7x26) Bare Copper Shielded	Flamarrest (Black, Red)	White Flamarrest	.168	4.27					
	(1) 4-Cond. 18 AWG Stranded (7x26) Bare Copper Shielded	Flamarrest (Black, Red, White, Green)	Blue Flamarrest	.197	5.00					
638AFS <small>NEW</small>	(1) 4-Cond. 16 AWG Stranded (19x30) Bare Copper Shielded	Flamarrest (Black, Red, White, Green)	Gray Flamarrest	.224	5.69					

U.S. Patent 7,049,523

Access Control Banana Peel® Cable

Lock Power, Card Reader, Door Contact, REX Applications
Riser-Rated



**Composite
Shielded Multi-Conductors**
CMR/CMG Rated

Product Description


Stranded bare copper conductors, PVC or Flame-retardant PVC insulation and jackets. No overall jacket. All cables are Beldfoil® shielded (100% coverage) with drain wire and rip cord. Cable jackets are color coded by application. Individual jacket is sequentially marked at two foot intervals.

Specifications

Conductor	Bare Copper
Insulation	PVC or FR-PVC
Shield	Beldfoil
Individual Jackets	PVC or FR-PVC
Overall Jacket	None
Approvals	
NEC	CMR
CEC	CMG
NEC Articles	800
Voltage Rating	300V
Temperature Rating	75°C

Applications

- Security Systems
- Power-Limited Controls
- Access Control
- Card Reader
- Lock Power
- Door Control
- REX

**Individual Cable Jacket Color Coding System**

Jacket Color	Print Legend	Cable Type
Orange	Card Reader	3/P, 18 or 22 AWG, Shielded
White	Door Contact	2/C, 18 or 22 AWG, Shielded
Blue	Rex/Spare	4/C, 18 or 22 AWG, Shielded
Gray	Lock Power	4/C, 16 or 18 AWG, Shielded

Part No.	Component Descriptions	Insulation Material & (Color Code)	Jacket Material & Component OD		Overall Nom. OD		Standard Lengths		Standard Unit Weight	
			Inch	mm	Inch	mm	Ft.	m	Lbs.	kg

Composite Shielded Multi-Conductors (NEC CMR and CEC CMG)

(3) Shielded Multi-Conductors • (1) Shielded Multi-Pair										
558AFS <small>NEW</small>	(1) 3-Pair 22 AWG Stranded (7x30) Bare Copper Shielded	F-R PVC (Black & Red, White & Green, Orange & Brown)	Orange FR-PVC .233	11.38	.448	500	152	59	26.5	
	(1) 2-Cond. 22 AWG Stranded (7x30) Bare Copper Shielded	F-R PVC (Black, Red)	White FR-PVC .140	3.56		1000	305	108	49.0	
	(1) 4-Cond. 22 AWG Stranded (7x30) Bare Copper Shielded	F-R PVC (Black, Red, White, Green)	Blue FR-PVC .161	4.09						
	(1) 4-Cond. 18 AWG Stranded (7x26) Bare Copper Shielded	F-R PVC (Black, Red, White, Green)	Gray FR-PVC .202	5.13						
538AFS <small>NEW</small>	(1) 3-Pair 18 AWG Stranded (7x26) Bare Copper Shielded	PVC (Black & Red, White & Green, Orange & Brown)	Orange PVC .285	13.11	.516	1000	305	182	82.6	
	(1) 2-Cond. 18 AWG Stranded (7x26) Bare Copper Shielded	PVC (Black, Red)	White PVC .175	4.45						
	(1) 4-Cond. 18 AWG Stranded (7x26) Bare Copper Shielded	PVC (Black, Red, White, Green)	Blue PVC .202	5.13						
	(1) 4-Cond. 16 AWG Stranded (19x30) Bare Copper Shielded	PVC (Black, Red, White, Green)	Gray PVC .230	5.84						

F-R = Flame-retardant

U.S. Patent 7,049,523