

## Fire Alarm Cable

Commercial Applications  
Unshielded, Power-Limited



### Unshielded Multi-conductor

FPLR/CMG FT4 Rated

#### Product Description

Bare copper conductors, PVC insulation, conductors cabled together, Red PVC jacket with rip cord. Sequential footage marking every two feet.

**Color Code:** See chart below.

#### Specifications

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	PVC
<b>Jacket</b>	PVC
<b>Jacket Thickness</b>	.015" (.381mm)
<b>Approvals</b>	
NEC	FPLR
CEC (22–16 AWG only)	CMG FT4
California State Fire Marshall	
<b>NEC Articles</b>	760
<b>Voltage Rating</b>	300V
<b>Temperature Rating</b>	75°C

#### Applications

- Fire Protection
- Alarm
- Signal
- Monitor/Detection
- Audio Circuits
- Control Circuits
- Initiating Circuits
- Notification Circuits



#### Color Code Chart

Cond. No.	Color
1	Black
2	Red
3	Brown
4	Blue
5	Orange
6	Yellow
7	Purple
8	Green
9	Red/Black
10	Red/White
11	Red/Green
12	Red/Blue

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

#### Unshielded Multi-conductor (NEC FPLR and CEC CMG FT4)

22 AWG										
5522UL	4	solid	C-500	C-152	7.0	3.2	.010	.25	.125	3.18
			U-1000	U-305	16.0	7.3				
			1000	305	16.0	7.3				
5524UL	6	solid	C-500	C-152	10.0	4.6	.010	.25	.168	4.27
			U-1000	U-305	21.0	9.5				
18 AWG										
5320UL	2	solid	C-500	C-152	8.0	3.6	.010	.25	.151	3.84
			U-500	U-152	9.0	4.1				
			500	152	9.0	4.1				
5322UL	4	solid	C-250	C-76	7.0	3.2	.010	.25	.176	4.47
			C-500	C-152	14.0	6.0				
			U-500	U-152	15.5	7.0				
5324UL	6	solid	U-1000	U-305	30.0	13.6				
			1000	305	30.0	13.6				
5326UL	8	solid	500	152	23.5	10.7	.010	.25	.212	5.38
			U-1000	U-305	43.0	19.5				
			1000	305	44.0	20.0				
5328UL	10	solid	1000	305	71.0	32.3	.010	.25	.272	6.91
5329UL	12	solid	1000	305	83.0	37.7	.010	.25	.281	7.14
16 AWG										
5220UL*	2	solid	500	152	13.0	5.9	.010	.25	.174	4.42
			U-1000	U-305	24.0	10.9				
			1000	305	25.0	11.4				
5222UL	4	solid	1000	305	45.0	20.4	.010	.25	.204	5.18
14 AWG										
5120UL*	2	solid	500	152	19.0	8.6	.013	.33	.213	5.41
			1000	305	38.0	17.3				
5122UL	4	solid	1000	305	70.0	31.8	.013	.33	.251	6.38
12 AWG										
5020UL	2	solid	1000	305	55.0	25.0	.013	.33	.247	6.27

\*Also available in other jacket colors. Consult [www.belden.com](http://www.belden.com).

## Fire Alarm Cable

Commercial Applications  
Shielded, Power-Limited



### Shielded Multi-conductor

FPLR/CMG FT4 Rated

#### Product Description

Bare copper conductors, PVC insulation, conductors cabled together, Beldfoil® shield and drain wire, Red PVC jacket with rip cord. Sequential footage marking every two feet.

**Color Code:** See chart below.

#### Specifications

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	PVC
<b>Shield</b>	Beldfoil
<b>Jacket</b>	PVC
<b>Jacket Thickness</b>	.015" (.381mm)
<b>Approvals</b>	
NEC	FPLR
CEC (22–16 AWG only)	CMG FT4
California State Fire Marshall	
<b>NEC Articles</b>	760
<b>Voltage Rating</b>	300V
<b>Temperature Rating</b>	75°C

#### Applications

- Fire Protection
- Alarm
- Signal
- Monitor/Detection
- Audio Circuits
- Control Circuits
- Initiating Circuits
- Notification Circuits



Shorting Fold

#### Color Code Chart

Cond. No.	Color
1	Black
2	Red
3	Brown
4	Blue

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

#### Shielded Multi-conductor (NEC FPLR and CEC CMG FT4)

22 AWG										
5522FL	4	solid	C-500	C-152	9.0	4.1	.010	.25	.145	3.68
			U-1000	U-305	19.0	8.6				
			1000	305	19.0	8.6				
18 AWG										
5320FL*	2	solid	C-500	C-152	10.5	4.8	.010	.25	.155	3.94
			U-500	U-152	11.5	5.2				
			500	152	11.5	5.2				
			U-1000	U-305	22.0	10.0				
			1000	305	22.0	10.0				
5322FL	4	solid	C-500	C-152	15.5	7.0	.010	.25	.170	4.32
			500	152	16.5	7.5				
			U-1000	U-305	32.0	14.5				
			1000	305	34.0	15.4				
16 AWG										
5220FL*	2	solid	1000	305	29.0	13.2	.010	.25	.178	4.52
5222FL	4	solid	1000	305	50.0	22.7	.010	.25	.208	5.28
14 AWG										
5120FL*	2	solid	500	152	22.0	10.0	.013	.33	.217	5.51
			1000	305	43.0	19.5				
5122FL	4	solid	1000	305	79.0	35.9	.013	.33	.255	6.48
12 AWG										
5020FL	2	solid	1000	305	60.0	27.2	.013	.33	.251	6.38

\*Also available in other jacket colors. Consult [www.belden.com](http://www.belden.com).

## Fire Alarm Cable

Commercial Applications, Addressable Systems  
Unshielded or Shielded, Power-Limited, Mid-Capacitance



### Unshielded Multi-conductor

FPL Rated

#### Product Description

Bare copper conductors, foam high-density polyethylene insulation, cabled together, Red PVC jacket with rip cord. Sequential footage marking every two feet.

**Color Code:** Black, Red.

### Shielded Multi-conductor

FPL Rated

#### Product Description

Bare copper conductors, foam high-density polyethylene insulation, cabled together, Beldfoil® shield tape (foil side out), Red PVC jacket with rip cord. Sequential footage marking every two feet.

**Color Code:** See chart below.

#### Specifications

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	FHDPE
<b>Shield</b> (where applicable)	Beldfoil
<b>Jacket</b>	PVC
<b>Jacket Thickness</b>	.033" (.838mm)
<b>Approvals</b>	
NEC	FPL
California State Fire Marshall	
<b>NEC Articles</b>	760
<b>Voltage Rating</b>	300V
<b>Temperature Rating</b>	75°C
<b>Nominal Capacitance*</b>	
Unshielded†	13 pF/ft.
Shielded††	20–36 pF/ft.

\*Capacitance between conductors.

†60% lower capacitance than cables on page 20.55

††60% lower capacitance than cables on page 20.56

#### Applications

- Addressable Fire Systems
- Data Circuits
- Audio Circuits
- Control Circuits
- Initiating Circuits
- Notification Circuits

#### Color Code Chart

Cond. No.	Color
1	Black
2	Red
3	Brown
4	Blue

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

#### Unshielded Multi-conductor (NEC FPL)

18 AWG										
5320UJ	2	solid	U-1000	U-305	22.0	10.0	.015	.38	.206	5.23
16 AWG										
5220UJ	2	solid	500	152	16.0	7.3	.015	.38	.230	5.84
			1000	305	32.0	14.5				


#### Shielded Multi-conductor (NEC FPL)

18 AWG										
5320FJ	2	solid	U-1000	U-305	27.0	12.3	.015	.38	.211	5.36
			1000	305	28.0	12.7				
5322FJ	4	solid	1000	305	43.0	19.5	.015	.38	.240	6.10
16 AWG										
5220FJ	2	solid	500	152	18.0	8.2	.015	.38	.235	5.97
			U-1000	U-305	35.0	15.9				
			1000	305	37.0	16.8				
5222FJ	4	solid	1000	305	59.0	26.8	.015	.38	.269	6.83
14 AWG										
5120FJ	2	solid	1000	305	49.0	22.3	.020	.51	.279	7.09
12 AWG										
5020FJ	2	solid	1000	305	69.0	31.3	.020	.51	.317	8.05

#### Unshielded



#### Shielded



## Fire Alarm Cable

NPLF Systems

Unshielded or Shielded, Non-Power-Limited Signaling Cable



### Unshielded Multi-conductor

NPLF Rated

150V Max. Per NEC Article 760

Indoor (Non-conduit per NEC)

#### Product Description

Bare copper conductors, PVC/Nylon insulation, cabled together, Red PVC jacket with rip cord. Sequential footage marking every two feet.

**Color Code:** See chart below.

### Shielded Multi-conductor

NPLF Rated

150V Max. Per NEC Article 760

Indoor (Non-conduit per NEC)

#### Product Description

Bare copper conductors, PVC/Nylon insulation, cabled together, Beldfoil® shield tape (aluminum side out) plus drain wire, Red PVC jacket with rip cord. Sequential footage marking every two feet.

**Color Code:** See chart below.

#### Specifications

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	PVC/Nylon
<b>Insulation Thickness</b>	.021" (.533mm)
<b>Shield (where applicable)</b>	Beldfoil
<b>Jacket</b>	PVC
<b>Approvals</b>	
NEC	NPLF
<b>NEC Articles</b>	760
<b>Voltage Rating</b>	150V
<b>Temperature Rating</b>	75°C

#### Applications

- Fire Alarm
- Audio Circuits
- Control Circuits
- Initiating Circuits
- Notification Circuits

#### Color Code Chart

Cond. No.	Color
1	Black
2	Red
3	Brown
4	Blue

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

#### Unshielded Multi-conductor (NEC NPLF)

18 AWG										
5320UN	2	solid	500	152	14.0	6.4	.037	.94	.239	6.07
			1000	305	31.0	14.1				
5322UN	4	solid	500	152	28.0	12.7	.042	1.07	.283	7.19
			1000	305	53.0	24.0				
16 AWG										
5220UN	2	solid	500	152	22.0	10.0	.037	.94	.262	6.65
			1000	305	40.0	18.1				
5222UN	4	solid	1000	305	71.0	32.3	.042	1.07	.311	7.90
14 AWG										
5120UN	2	solid	500	152	28.5	13.0	.042	1.07	.299	7.59
			1000	305	53.0	24.1				


#### Shielded Multi-conductor (NEC NPLF)

18 AWG										
5320FN	2	solid	500	152	15.5	7.0	.037	.94	.243	6.17
			1000	305	35.0	15.9				
5322FN	4	solid	500	152	31.0	14.1	.042	1.07	.287	7.29
			1000	305	57.0	25.9				
16 AWG										
5220FN	2	solid	500	152	23.5	10.7	.037	.94	.266	6.76
			1000	305	45.0	20.5				
5222FN	4	solid	1000	305	76.0	34.5	.042	1.07	.315	8.00
14 AWG										
5120FN	2	solid	500	152	32.0	14.5	.042	1.07	.303	7.70
			1000	305	61.0	27.7				
5122FN	4	solid	500	152	50.5	23.0	.042	1.07	.348	8.84
			1000	305	102.0	46.4				
12 AWG										
5020FN	2	solid	500	152	43.0	19.5	.042	1.07	.337	8.56
			1000	305	83.0	37.7				

#### Unshielded



#### Shielded



## Fire Alarm Cable

Commercial Applications

Unshielded or Shielded, Plenum-Rated, Power-Limited



### Unshielded or Shielded Multi-conductor FPLP Rated

#### Product Description

Bare copper conductors, Flamarrest® insulation, cabled together, Red Flamarrest jacket with rip cord. Shielded version has overall Beldfoil® shield tape (foil side out) and drain wire. Sequential footage marking every two feet.

**Color Code:** See chart below.

#### Specifications

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	Flamarrest
<b>Shield</b> (where applicable)	Beldfoil
<b>Jacket</b>	Flamarrest
<b>Jacket Thickness</b>	.015" (.381mm)
<b>Approvals</b>	FPLP
NEC	
California State Fire Marshall	
<b>NEC Articles</b>	760
<b>Voltage Rating</b>	300V
<b>Temperature Rating</b>	75°C

#### Applications

- Fire Protection
- Alarm
- Signal
- Monitor/Detection
- Audio Circuits
- Control Circuits
- Initiating Circuits
- Notification Circuits

#### Unshielded



#### Shielded



Shorting Fold

#### Color Code Chart

Cond. No.	Color	Cond. No.	Color
1	Black	6	Yellow
2	Red	7	Purple
3	Brown	8	Green
4	Blue	9	Red/Black
5	Orange	10	Red/White

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

#### Unshielded Multi-conductor (NEC FPLP)

##### 22 AWG

<b>6522UL</b>	4	solid	U-1000 1000	U-305 305	17.0 16.0	7.7 7.3	.009	.23	.136	3.45
<b>6524UL</b>	6	solid	C-500 U-1000 1000	C-152 U-305 305	10.5 22.0 22.0	4.8 10.0 10.0	.009	.23	.162	4.12

##### 18 AWG

<b>6320UL*</b>	2	solid	C-500 U-500 U-1000 1000	C-152 U-152 U-305 305	8.0 9.0 18.0 17.0	3.6 4.1 8.2 7.7	.010	.25	.151	3.84
<b>6321UL</b>	3	solid	1000	305	28.0	12.7	.010	.25	.160	4.06

<b>6322UL</b>	4	solid	C-250 C-500 1000	C-76 C-152 305	7.2 14.5 31.0	3.3 6.6 14.1	.010	.25	.183	4.64
<b>6324UL</b>	6	solid	U-1000 1000	U-305 305	44.0 46.0	20.0 20.9	.010	.25	.211	5.36

<b>6326UL</b>	8	solid	1000	305	63.0	28.6	.010	.25	.230	5.84
<b>6328UL</b>	10	solid	1000	305	73.0	33.1	.010	.25	.272	6.91

##### 16 AWG

<b>6220UL*</b>	2	solid	C-500 500 U-1000 1000	C-152 152 U-305 305	12.0 12.5 25.0 26.0	5.4 5.7 11.4 11.8	.010	.25	.174	4.42
<b>6222UL</b>	4	solid	500 1000	152 305	24.5 47.0	11.1 21.3	.010	.25	.204	5.18

##### 14 AWG

<b>6120UL*</b>	2	solid	500 1000	152 305	19.0 38.0	8.6 17.3	.011	.28	.205	5.21
<b>6122UL</b>	4	solid	500 1000	152 305	35.5 70.0	16.1 31.8	.011	.28	.241	6.12

##### 12 AWG

<b>6020UL</b>	2	solid	1000	305	59.0	26.8	.011	.28	.239	6.07
---------------	---	-------	------	-----	------	------	------	-----	------	------

#### Shielded Multi-conductor (NEC FPLP)

##### 18 AWG

<b>6320FL*</b>	2	solid	C-500 U-1000 1000	C-152 U-305 305	10.5 22.0 22.0	4.8 10.0 10.0	.010	.25	.158	4.01
<b>6322FL</b>	4	solid	1000	305	36.0	16.4	.010	.25	.183	4.65

##### 16 AWG

<b>6220FL*</b>	2	solid	C-500 1000	C-152 305	14.5 31.0	6.6 14.1	.010	.25	.181	4.60
<b>6222FL</b>	4	solid	1000	305	58.0	26.3	.010	.25	.211	5.36

##### 14 AWG

<b>6120FL*</b>	2	solid	500 1000	152 305	23.5 45.0	10.7 20.4	.011	.28	.209	5.31
<b>6122FL</b>	4	solid	500 1000	152 305	42.0 77.0	19.1 35.0	.011	.28	.245	6.22

##### 12 AWG

<b>6020FL</b>	2	solid	500 1000	152 305	30.5 61.0	13.9 27.7	.011	.28	.243	6.17
---------------	---	-------	-------------	------------	--------------	--------------	------	-----	------	------

\*Also available in other jacket colors. Consult [www.belden.com](http://www.belden.com).

## Fire Alarm Cable

Commercial Applications, Addressable Systems

Unshielded and Shielded, Plenum-Rated, Power-Limited, Mid-Capacitance



### Unshielded Multi-conductor

FPLP Rated

#### Product Description

Bare copper conductors, FEP insulation, cabled together, Red Flam arrest® jacket with rip cord. Sequential footage marking every two feet.

**Color Code:** Black, Red.

### Shielded Multi-conductor

FPLP Rated

#### Product Description

Bare copper conductors, FEP insulation, cabled together, Beldfoil® shield tape (aluminum side out) with tinned copper drain wire, Red Flam arrest jacket with rip cord. Sequential footage marking every two feet.

**Color Code:** Black, Red.

#### Specifications

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	FEP
<b>Shield</b> (where applicable)	Beldfoil
<b>Jacket</b>	Flam arrest
<b>Jacket Thickness</b>	.015" (.381mm)
<b>Approvals</b>	
NEC	FPLP
California State Fire Marshall	
<b>NEC Articles</b>	760
<b>Voltage Rating</b>	300V
<b>Temperature Rating</b>	75°C
<b>Nominal Capacitance*</b>	
Unshielded†	26 pF/ft.
Shielded††	26–31 pF/ft.

\*Capacitance between conductors.

†20% lower capacitance than cables on page 13.39

††60% lower capacitance than cables on page 13.39

#### Applications

- Addressable Fire Systems
- Data Circuits
- Monitor/Detection
- Control Circuits
- Initiating Circuits
- Notification Circuits

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

#### Unshielded Multi-conductor (NEC FPLP)

18 AWG										
6320UJ	2	solid	1000	305	16.0	7.3	.007	.18	.138	3.51
16 AWG										
6220UJ	2	solid	1000	305	24.0	10.9	.007	.18	.162	4.11
14 AWG										
6120UJ	2	solid	1000	305	32.0	14.5	.007	.18	.186	4.72


#### Shielded Multi-conductor (NEC FPLP)

18 AWG										
6320FK	2	solid	500	152	14.0	6.4	.018	.46	.185	4.70
			U-1000	U-305	28.0	12.7				
			1000	305	27.0	12.2				
16 AWG										
6220FK	2	solid	1000	305	37.0	16.8	.018	.46	.210	5.33

#### Unshielded



#### Shielded



Shorting Fold

**Circuit Integrity in Conduit (CIC) Safe-T-Line® Cable**

Commercial Applications, Addressable Systems

Unshielded, Riser-Rated

**Unshielded Multi-conductor**

FPLR-CIC Rated

**Product Description**

Bare copper conductors, ceramifiable silicone rubber insulation, Red FRPE (Low-Smoke, Non-Halogen) jacket. Sequential footage marking every two feet.

**Color Code:** Black, Red.

**Specifications**

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	Silicone Rubber
<b>Shield</b>	Unshielded
<b>Jacket</b>	FRPE
<b>Jacket Thickness</b>	.035" (.889mm)
<b>Approvals</b>	
NEC	FPLR-CIC
<b>NEC Articles</b>	760
<b>Voltage Rating</b>	300V
<b>Temperature Rating</b>	105°C

Note: 2-conductor versions are color-coded black and red.  
4 or more conductor versions are all black and numbered.

**Applications**

- Circuit Integrity
- Fire Alarm Circuit Integrity
- Survivability
- Survivability from Attack by Fire

**Stranded****Solid**

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

**Unshielded Multi-conductor (NEC FPLR-CIC)**

<b>16 AWG</b>										
<b>5200UZ</b> <small>NEW</small>	2	7	1000	305	68.0	30.9	.056	1.42	.37	9.40
<b>5220UZ</b> <small>NEW</small>	2	solid	1000	305	64.0	29.0	.056	1.42	.35	8.89
<b>14 AWG</b>										
<b>5100UZ</b> <small>NEW</small>	2	7	1000	305	87.0	39.5	.056	1.42	.40	10.16
<b>5120UZ</b> <small>NEW</small>	2	solid	1000	305	79.0	35.8	.056	1.42	.38	9.65
<b>12 AWG</b>										
<b>5000UZ</b> <small>NEW</small>	2	7	1000	305	108.0	50.0	.056	1.42	.37	9.40
<b>5020UZ</b> <small>NEW</small>	2	solid	1000	305	101.0	45.8	.056	1.42	.42	10.67

FRPE = Flame-retardant Polyethylene

**Circuit Integrity in Conduit (CIC) Safe-T-Line® Cable**

Commercial Applications, Addressable Systems

Shielded, Riser-Rated

**Shielded Multi-conductor**

FPLR-CIC Rated

**Product Description**

Bare copper conductors, ceramifiable silicone rubber insulation, overall Beldfoil® Shield (100% coverage), tinned copper drain wire, Red FRPE (Low-Smoke, Non-Halogen) jacket, Sequential footage marking every two feet.

**Color Code:** Black, Red. (see note)


**Specifications**

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	Silicone Rubber
<b>Shield</b>	Beldfoil
<b>Jacket</b>	FRPE
<b>Jacket Thickness</b>	.035" (.889mm)
<b>Approvals</b>	
NEC	FPLR-CIC
<b>NEC Articles</b>	760
<b>Voltage Rating</b>	300V
<b>Temperature Rating</b>	105°C

Note: 2-conductor versions are color-coded black and red.  
4 or more conductor versions are all black and numbered.

**Applications**

- Circuit Integrity
- Fire Alarm Circuit Integrity
- Survivability
- Survivability from Attack by Fire

**Stranded****Solid**

Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Outer Jacket Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

**Shielded Multi-conductor (NEC FPLR-CIC)**

<b>16 AWG</b>										
<b>5200FZ</b> <small>NEW</small>	2	7	1000	305	75.0	34.0	.056	1.42	.37	9.40
<b>5220FZ</b> <small>NEW</small>	2	solid	1000	305	71.0	32.2	.056	1.42	.36	9.14
<b>5222FZ</b> <small>NEW</small>	4	solid	1000	305	108.0	50.0	.056	1.42	.41	10.41
<b>14 AWG</b>										
<b>5100FZ</b> <small>NEW</small>	2	7	1000	305	97.0	44.0	.056	1.42	.41	10.41
<b>5120FZ</b> <small>NEW</small>	2	solid	1000	305	90.0	40.8	.056	1.42	.38	9.65
<b>12 AWG</b>										
<b>5000FZ</b> <small>NEW</small>	2	7	1000	305	122.0	55.3	.056	1.42	.44	11.18
<b>5020FZ</b> <small>NEW</small>	2	solid	1000	305	117.0	53.1	.056	1.42	.42	10.67
<b>5022FZ</b> <small>NEW</small>	4	solid	1000	305	187.0	84.8	.056	1.42	.48	12.19

FRPE = Flame-retardant Polyethylene



**Circuit Integrity (CI) Safe-T-Line® Cable**Commercial Applications, Addressable Systems  
Unshielded, Riser-Rated**Unshielded Multi-conductor**

FPLR-CI Rated

**Product Description**

Solid bare copper conductors, ceramifiable silicone rubber insulation, Red FRPE (Low-Smoke, Non-Halogen) jacket. Sequential footage marking every two feet.

**Color Code:** Black, Red. (see note)

**Specifications**

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	Silicone Rubber
<b>Shield</b>	Unshielded
<b>Jacket</b>	FRPE
<b>Jacket Thickness</b>	.045" (1.143mm)
<b>Approvals</b>	NEC FPLR-CI California State Fire Marshall
<b>NEC Articles</b>	760
<b>Voltage Rating</b>	300V
<b>Temperature Rating</b>	105°C
<b>Nominal Capacitance</b>	
18 AWG	17 pF/ft.
16 AWG	19 pF/ft.
14 AWG	21 pF/ft.
12 AWG	23 pF/ft.

Note: 2-conductor versions are color-coded black and red.  
4 or more conductor versions are all black and numbered.

**Applications**

- Circuit Integrity
- Fire Alarm Circuit Integrity
- Survivability
- Survivability from Attack by Fire



Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

**Unshielded Multi-conductor (NEC FPLR-CI)**

<b>18 AWG</b>										
<b>5320UM</b> <small>NEW</small>	2	solid	1000	305	47.0	21.3	.034	.86	.31	7.87
<b>5322UM</b> <small>NEW</small>	4	solid	1000	305	73.0	33.1	.034	.86	.35	8.89
<b>5324UM</b> <small>NEW</small>	6	solid	1000	305	100.0	45.4	.034	.86	.42	10.67
<b>5326UM</b> <small>NEW</small>	8	solid	1000	305	123.0	55.8	.034	.86	.45	11.43
<b>16 AWG</b>										
<b>5220UM</b> <small>NEW</small>	2	solid	1000	305	59.0	26.8	.034	.86	.33	8.38
<b>5222UM</b> <small>NEW</small>	4	solid	1000	305	97.0	44.0	.034	.86	.38	9.65
<b>14 AWG</b>										
<b>5120UM</b> <small>NEW</small>	2	solid	1000	305	73.0	33.1	.034	.86	.36	9.14
<b>5122UM</b> <small>NEW</small>	4	solid	1000	305	123.0	55.8	.034	.86	.41	10.41
<b>12 AWG</b>										
<b>5020UM</b> <small>NEW</small>	2	solid	1000	305	96.0	43.6	.034	.86	.39	9.91
<b>5022UM</b> <small>NEW</small>	4	solid	1000	305	167.0	75.8	.034	.86	.45	11.43

FRPE = Flame-retardant Polyethylene

**Circuit Integrity (CI) Safe-T-Line® Cable**

Commercial Applications, Addressable Systems  
Shielded, Riser-Rated

**Shielded Multi-conductor**

FPLR-CI Rated

**Product Description**

Bare copper conductors, ceramifiable silicone rubber insulation, Beldfoil® shield (100% coverage), Red FRPE (Low-Smoke, Non-Halogen) jacket, drain wire. Sequential footage marking every two feet.

**Color Code:** Black, Red.

**Specifications**

<b>Conductor</b>	Bare Copper
<b>Insulation</b>	Silicone Rubber
<b>Shield</b>	Beldfoil
<b>Jacket</b>	FRPE
<b>Jacket Thickness</b>	.045" (1.143mm)
<b>Approvals</b>	FPLR-CI
NEC	
California State Fire Marshall	
<b>NEC Articles</b>	760
<b>Voltage Rating</b>	300V
<b>Temperature Rating</b>	105°C
<b>Nominal Capacitance</b>	
18 AWG	27 pF/ft.
16 AWG	31 pF/ft.
14 AWG	33 pF/ft.
12 AWG	37 pF/ft.*
	40 pF/ft.**

\* 5020FM and 5022FM

\*\* 5000FM and 5002FM

Note: 2-conductor versions are color-coded black and red.  
4 or more conductor versions are all black and numbered.

**Applications**

- Circuit Integrity
- Fire Alarm Circuit Integrity
- Survivability
- Survivability from Attack by Fire



Part No.	No. of Cond.	Stranding	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
			Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

**Shielded Multi-conductor (NEC FPLR-CI)**

<b>18 AWG</b>										
<b>5320FM</b> <small>NEW</small>	2	solid	1000	305	50.0	22.7	.034	.86	.31	7.87
<b>5322FM</b> <small>NEW</small>	4	solid	1000	305	78.0	35.4	.034	.86	.36	9.14
<b>5324FM</b> <small>NEW</small>	6	solid	1000	305	106.0	48.1	.034	.86	.42	10.67
<b>5326FM</b> <small>NEW</small>	8	solid	1000	305	129.0	58.5	.034	.86	.46	11.61
<b>5300FM</b> <small>NEW</small>	2	(7x26)	1000	305	57.0	25.9	.034	.86	.32	8.13
<b>5302FM</b> <small>NEW</small>	4	(7x26)	1000	305	103.0	46.7	.034	.86	.37	9.40
<b>5304FM</b> <small>NEW</small>	6	(7x26)	1000	305	122.0	55.3	.034	.86	.44	11.18
<b>5306FM</b> <small>NEW</small>	8	(7x26)	1000	305	148.0	67.1	.034	.86	.47	11.94
<b>16 AWG</b>										
<b>5220FM</b> <small>NEW</small>	2	solid	1000	305	66.0	29.9	.034	.86	.33	8.38
<b>5222FM</b> <small>NEW</small>	4	solid	1000	305	103.0	46.7	.034	.86	.38	9.65
<b>5200FM</b> <small>NEW</small>	2	(7x24)	1000	305	71.0	32.2	.034	.86	.35	8.89
<b>5202FM</b> <small>NEW</small>	4	(7x24)	1000	305	112.0	50.8	.034	.86	.40	10.16
<b>14 AWG</b>										
<b>5120FM</b> <small>NEW</small>	2	solid	1000	305	84.0	38.1	.034	.86	.36	9.14
<b>5122FM</b> <small>NEW</small>	4	solid	1000	305	133.0	60.3	.034	.86	.41	10.41
<b>5100FM</b> <small>NEW</small>	2	(7x22)	1000	305	93.0	42.2	.034	.86	.38	9.65
<b>5102FM</b> <small>NEW</small>	4	(7x22)	1000	305	149.0	67.6	.034	.86	.44	11.18
<b>12 AWG</b>										
<b>5020FM</b> <small>NEW</small>	2	solid	1000	305	112.0	50.8	.034	.86	.39	9.91
<b>5022FM</b> <small>NEW</small>	4	solid	1000	305	183.0	83.0	.034	.86	.46	11.68
<b>5000FM</b> <small>NEW</small>	2	(7x20)	1000	305	117.0	53.1	.034	.86	.42	10.67
<b>5002FM</b> <small>NEW</small>	4	(7x20)	1000	305	189.0	85.7	.034	.86	.48	12.19

FRPE = Flame-retardant Polyethylene