


Speaker Cable

Multi-conductor Cables for Residential, Light Commercial and Institutional Applications


Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Outer Jacket Thickness		Nominal OD	
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm

Multi-conductor • 16 AWG Stranded (19x29) Bare Copper Conductors • Rip Cord

Non-Plenum • PVC Insulation • Gray PVC Jacket


 <p>Rip Cord</p>	300V 75°C	5200UE	NEC: CMR CEC: CMG FT4	2	Black, Red	C-500	C-152.4	11.5	5.2	.010	.25	.015	.38	.184	4.67	
						U-500	U-152.4	13.0	5.9							
						500	152.4	12.5	5.7							
						U-1000	U-304.8	25.0	11.4							
						1000	304.8	25.0	11.4							

Jacket sequentially marked at 2 ft. intervals.

 <p>Rip Cord</p>	300V 75°C	5202UE	NEC: CMR CEC: CMG FT4	4	Black, Red, White, Green	U-500	U-152.4	23.5	10.7	.010	.25	.015	.38	.216	5.49	
						500	152.4	23.0	10.4							
						U-1000	U-304.8	45.0	20.4							
						1000	304.8	47.0	21.3							

Jacket sequentially marked at 2 ft. intervals.


Plenum • Flamarrest® Insulation • Natural Flamarrest Jacket

 <p>Rip Cord</p>	300V 75°C	6200UE	NEC: CMP CEC: CMP FT6	2	Black, Red	500	152.4	13.0	5.9	.009	.23	.015	.38	.180	4.57	
						U-1000	U-304.8	25.0	11.4							
						1000	304.8	26.0	11.8							

Jacket sequentially marked at 2 ft. intervals.

Multi-conductor • 14 AWG Stranded (19x27) Bare Copper Conductors • Rip Cord

Non-Plenum • PVC Insulation • PVC Jacket (Available in Red* or Gray)


 <p>Rip Cord</p>	300V 75°C	5100UE	NEC: CL3R FPLR*	2	Black, White	500 [†]	152.4	20.0	9.1	.014	.36	.015	.38	.234	5.94
						U-1000 [†]	U-304.8	38.0	17.2						
						1000	304.8	40.0	18.2						

[†]500 ft. and U-1000 ft. put-ups available in Gray only.

*Red jacket only suitable for Fire Alarm applications.

Jacket sequentially marked at 2 ft. intervals.


Plenum • Flamarrest Insulation • Natural Flamarrest Jacket

 <p>Rip Cord</p>	150V 75°C	6100UE	NEC: CL2P	2	Black, White	500	152.4	19.5	8.9	.011	.28	.015	.38	.222	5.64
						U-1000	U-304.8	38.0	17.2						
						1000	304.8	38.0	17.2						
						5000	1524.0	195.0	88.5						

Jacket sequentially marked at 2 ft. intervals.

Multi-conductor • 12 AWG Stranded (19x25) Bare Copper Conductors • Rip Cord

Non-Plenum • PVC Insulation • PVC Jacket (Available in Red* or Gray)

 <p>Rip Cord</p>	300V 75°C	5000UE	NEC: CL3R FPLR*	2	Black, White	500 [†]	152.4	29.0	13.2	.014	.36	.015	.38	.268	6.81
						1000	304.8	57.0	25.9						

[†]500 ft. put-up available in Gray only.

*Red jacket only suitable for Fire Alarm applications.

Jacket sequentially marked at 2 ft. intervals.

For additional selection of Belden® Security, Alarm and Communications Cables, refer to the New Generation® Cables section of this catalog.