

Speaker Cable


High-Conductivity Electrolytic Tough Pitch (ETP) Copper Speaker Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Standard Lengths		Standard Unit Weight		Insulation Thickness		Nominal OD	
				Ft.	m	Lbs.	kg	Inch	mm	Inch	mm

16 AWG Stranded (26x30) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

PVC Insulation • Clear PVC Jacket


Parallel Zip Construction 300V 60°C	9716		2	U-1000 1000	U-304.8 304.8	27.0 26.0	12.3 11.8	.027	.69	.115 x .230	2.92 x 5.84
--	-------------	--	---	----------------	------------------	--------------	--------------	------	-----	-------------------	-------------------



14 AWG Stranded (19x27) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

PVC Insulation • Clear PVC Jacket

Parallel Zip Construction 60°C	9717		2	U-1000 1000	U-304.8 304.8	42.0 42.0	19.1 19.1	.035	.89	.146 x .292	3.71 x 7.42
-----------------------------------	-------------	--	---	----------------	------------------	--------------	--------------	------	-----	-------------------	-------------------



12 AWG Stranded (65x30) ETP High-conductivity Copper Conductors • Parallel: (1) Tinned, (1) Bare

PVC Insulation • Clear PVC Jacket

Parallel Zip Construction 60°C	9718		2	500 1000	152.4 304.8	33.0 66.0	15.0 30.0	.045	1.14	.185 x .370	4.70 x 9.40
-----------------------------------	-------------	--	---	-------------	----------------	--------------	--------------	------	------	-------------------	-------------------

