

Overall Foil/Braid Shield


Computer Cables for EIA RS-232 Applications and IEEE 488 Interface,
Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-423 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Nominal OD		Nominal DCR		Nom. Vel. of Prop.	Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Cond.	Shield		* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

28 AWG Stranded (7x36) Tinned Copper Conductors • Overall Beldfoil® (100% Coverage) + Tinned Copper Braid Shield (65% Coverage)


Semi-rigid PVC Insulation • Chrome PVC Jacket

UL AWM Style 2464 (300V 80°C)	9637	NEC: CL2	25	See Chart 2R (Tech Info Section)	100	30.5	6.2	2.8	.305	7.75	64.9Ω/M'	4.5Ω/M'	66%	30	98	50	164
CSA AWM I B FT4					500	152.4	30.0	13.6			212.9Ω/km	14.8Ω/km					
					1000	304.8	59.0	26.8									



Low Cap 28 AWG Stranded (7x36) TC Conductors • Overall Beldfoil (100% Coverage) + TC Braid Shield (65% Coverage) • Drain Wire†

Datalene® Insulation • Chrome PVC Jacket																	
UL AWM Style 2919 (30V 80°C)	9791	NEC: CL2	6	See Chart 1 (Tech Info Section)	500	152.4	13.0	6.0	.225	5.72	64.9Ω/M'	6.15Ω/M'	78%	12	39.4	22	72.2
VW-1					1000	304.8	29.0	13.2			212.9Ω/km	20.2Ω/km					



†28 AWG Stranded TC Drain Wire

IEEE 488 • 26 AWG & 24 AWG Stranded (7x34 & 7x32) TC Cond. • Overall Beldfoil (100% Coverage) + TC Braid Shield (90% Coverage) • Drain Wire

Semi-rigid PVC Insulation • Gray PVC Jacket																	
UL AWM Style 2464 (300V 80°C)	9641	NEC: CMG	23: (6)	See Chart 1 (Tech Info Section)	1000	304.8	82.0	37.4	.350	8.89	26 AWG: 37.3Ω/M'	2.6Ω/M'	66%	—	—	—	—
CSA AWM I A		CEC: CMG FT4	26 AWG Pairs								122.4Ω/km	8.5Ω/km					
			(10)								24 AWG: 23.3Ω/M'						
			26 AWG Cond.								76.4Ω/km						
			(1)														
			24 AWG Cond.														

TC = Tinned Copper


*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to ground.

Datalene insulation features include a low dielectric constant and a low dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-423 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Nominal OD		Nominal DCR		Nom. Vel. of Prop.	Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Cond.	Shield		* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) TC Conductors • Overall Beldfoil® (100% Coverage) + TC Braid Shield (65% Coverage) • Drain Wire††																	
Datalene® Insulation • Chrome PVC Jacket																	
 Z-Fold®	9925	NEC:	3	See Chart 1 (Tech Info Section)	100	30.5	3.5	1.6	.215	5.46	24.0Ω/M'	5.2Ω/M'	78%	12	39.4	22	72.2
		CM			500	152.4	12.0	5.5			78.7Ω/km	17.0Ω/km					
		CEC: CM			1000	304.8	24.0	10.9									
	9927	NEC:	4	See Chart 1 (Tech Info Section)	100	30.5	3.6	1.6	.230	5.84	24.0Ω/M'	5.3Ω/M'	78%	12	39.4	22	72.2
		CM			500	152.4	14.5	6.6			78.7Ω/km	17.4Ω/km					
		CEC: CM			1000	304.8	32.0	14.5									
	9929	NEC:	5	See Chart 1 (Tech Info Section)	100	30.5	4.0	1.8	.246	6.25	24.0Ω/M'	4.2Ω/M'	78%	12	39.4	22	72.2
		CM			500	152.4	16.0	7.3			78.7Ω/km	13.9Ω/km					
		CEC: CM			1000	304.8	36.0	16.3									
	9931	NEC:	6	See Chart 1 (Tech Info Section)	100	30.5	4.2	1.9	.265	6.73	24.0Ω/M'	4.4Ω/M'	78%	12	39.4	22	72.2
CM		500			152.4	17.5	8.0			78.7Ω/km	14.4Ω/km						
CEC:		1000			304.8	39.0	17.7										
CM		10000			3048.0	410.0	186.1										
9932	NEC:	7	See Chart 1 (Tech Info Section)	100	30.5	4.5	2.0	.265	6.73	24.0Ω/M'	4.4Ω/M'	78%	12	39.4	22	72.2	
	CM			500	152.4	18.5	8.4			78.7Ω/km	14.4Ω/km						
	CEC: CM			1000	304.8	41.0	18.6										
9933	NEC:	8	See Chart 1 (Tech Info Section)	100	30.5	4.9	2.2	.280	7.11	24.0Ω/M'	4.4Ω/M'	78%	12	39.4	22	72.2	
	CM			500	152.4	21.0	9.6			78.7Ω/km	14.4Ω/km						
	CEC:			1000	304.8	46.0	20.9										
	CM			10000†	3048.0	480.0	217.9										
9934	NEC:	9	See Chart 1 (Tech Info Section)	100	30.5	5.2	2.4	.300	7.62	24.0Ω/M'	3.9Ω/M'	78%	12	39.4	22	72.2	
	CM			500	152.4	22.0	10.0			78.7Ω/km	12.6Ω/km						
	CEC: CM			1000	304.8	48.0	21.8										
9935	NEC:	10	See Chart 1 (Tech Info Section)	100	30.5	5.7	2.6	.306	7.77	24.0Ω/M'	3.2Ω/M'	78%	12	39.4	22	72.2	
	CM			500	152.4	28.0	12.7			78.7Ω/km	10.4Ω/km						
	CEC: CM			1000	304.8	53.0	24.1										
9936	NEC:	15	See Chart 2R (Tech Info Section)	100	30.5	7.2	3.3	.350	8.89	24.0Ω/M'	3.6Ω/M'	78%	12	39.4	22	72.2	
	CM			500	152.4	35.0	15.9			78.7Ω/km	11.7Ω/km						
	CEC: CM			1000	304.8	68.0	30.9										
9937	NEC:	25	See Chart 2R (Tech Info Section)	100	30.5	9.9	4.5	.445	11.30	24.0Ω/M'	2.8Ω/M'	78%	12	39.4	22	72.2	
	CM			500	152.4	54.5	24.8			78.7Ω/km	9.1Ω/km						
	CEC: CM			1000	304.8	108.0	49.0										
9938	NEC:	37	See Chart 2R (Tech Info Section)	100	30.5	12.9	5.9	.500	12.7	24.0Ω/M'	2.4Ω/M'	78%	12	39.4	22	72.2	
	CM			500	152.4	71.5	32.5			78.7Ω/km	7.8Ω/km						
	CEC: CM			1000	304.8	139.0	63.1										

†24 AWG Stranded TC Drain Wire

†24 AWG Stranded TC Drain Wire

DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.


**Nominal capacitance conductor to conductor and shield.

††Final put-up may vary -10% to +20%. May contain two pieces, minimum length of any one piece is 1500 ft.

Datalene insulation features include a low dielectric constant and a low dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

Overall Beldfoil® Shield

Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-485 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
28 AWG Stranded (7x36) TC Conductors • Twisted Pairs • Overall Beldfoil Shield (100% Coverage) • 28 AWG Stranded TC Drain Wire																		
Datalene® Insulation • Chrome PVC Jacket																		
 Z-Fold®	8132FO	NEC: CL2	2	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	8.5 20.0	3.9 9.1	65.0Ω/M' 213.0Ω/km	23.1Ω/M' 75.8Ω/km	.215 5.46	120	78%	11.0	36.1	20.0	65.6	
	8133FO	NEC: CL2	3	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	11.0 24.0	5.0 11.0	65.0Ω/M' 213.0Ω/km	23.1Ω/M' 75.8Ω/km	.250 6.35	120	78%	11.0	36.1	20.0	65.6	
	8134FO	NEC: CL2	4	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	13.5 31.0	6.1 14.1	65.0Ω/M' 213.0Ω/km	20.0Ω/M' 65.6Ω/km	.270 6.86	120	78%	11.0	36.1	20.0	65.6	
	8135FO	NEC: CL2	5	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	14.0 32.0	6.4 14.5	65.0Ω/M' 213.0Ω/km	20.0Ω/M' 65.6Ω/km	.280 7.11	120	78%	11.0	36.1	20.0	65.6	
	8138FO	NEC: CL2	8	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	22.0 42.0	10.0 19.1	65.0Ω/M' 213.0Ω/km	17.7Ω/M' 58.1Ω/km	.310 7.88	120	78%	11.0	36.1	20.0	65.6	
	8142FO	NEC: CL2	12.5 (12 pairs + 1 single)	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	27.5 54.0	12.5 24.5	65.0Ω/M' 213.0Ω/km	17.7Ω/M' 58.1Ω/km	.385 9.78	120	78%	11.0	36.1	20.0	65.6	
	8148FO	NEC: CL2	18	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	38.5 77.0	17.5 34.0	65.0Ω/M' 213.0Ω/km	15.8Ω/M' 51.8Ω/km	.445 11.31	120	78%	11.0	36.1	20.0	65.6	
	8155FO	NEC: CL2	25	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	42.0 84.0	19.1 34.0	65.0Ω/M' 213.0Ω/km	14.3Ω/M' 4.7Ω/km	.545 13.85	120	78%	11.0	36.1	20.0	65.6	

DCR = DC Resistance • TC = Tinned Copper



*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Datalene insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

Overall Beldfoil® Shield

Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-422 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Overall Beldfoil Shield (100% Coverage) • 24 AWG Stranded TC Drain Wire																		
Polyethylene Insulation • Chrome PVC Jacket																		
	9680	NEC: CM CEC: CM	3	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	17.0 38.0	7.7 17.3	24.0Ω/M' 78.7Ω/km	14.4Ω/M' 47.2Ω/km	.282 7.16	100	66%	15.5	50.8	27.5	90.2	
	9681	NEC: CM CEC: CM	4	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	24.0 45.0	10.9 20.5	24.0Ω/M' 78.7Ω/km	14.4Ω/M' 47.2Ω/km	.307 7.80	100	66%	15.5	50.8	27.5	90.2	
	9682	NEC: CM CEC: CM	6	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	29.5 56.0	13.4 25.5	24.0Ω/M' 78.7Ω/km	13.1Ω/M' 43.0Ω/km	.342 8.69	100	66%	15.5	50.8	27.5	90.2	
	9683	NEC: CM CEC: CM	9	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	38.0 79.0	17.2 35.9	24.0Ω/M' 78.7Ω/km	12.0Ω/M' 39.4Ω/km	.397 10.10	100	66%	15.5	50.8	27.5	90.2	
	9684	NEC: CM CEC: CM	12.5 (12 prs.+ 1 single)	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	49.5 97.0	22.6 44.1	24.0Ω/M' 78.7Ω/km	12.0Ω/M' 39.4Ω/km	.445 11.30	100	66%	15.5	50.8	27.5	90.2	
Datalene® Insulation • Chrome PVC Jacket																		
	1419A	NEC: CM CEC: CM FT1	2	See Chart 5 (Tech Info Section)	500 1000 10000	152.4 304.8 3048.0	13.5 30.0 310.0	6.1 13.6 140.9	24.0Ω/M' 78.7Ω/km	15.1Ω/M' 49.5Ω/km	.248 6.30	100	78%	13	42.7	22	72	
	1420A	NEC: CM CEC: CM FT 1	3	See Chart 5 (Tech Info Section)	500 1000 10000	152.4 304.8 3048.0	15.0 34.0 340.0	6.8 15.5 154.5	24.0Ω/M' 78.7Ω/km	15.1Ω/M' 49.5Ω/km	.261 6.63	100	78%	13	42.7	22	72	
	1421A	NEC: CM CEC: CM	4	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	16.5 37.0	7.5 16.8	24.0Ω/M' 78.7Ω/km	14.4Ω/M' 47.2Ω/km	.280 7.11	100	78%	13	42.7	22	72	
	1422A	NEC: CM CEC: CM	5	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	23.0 43.0	10.5 19.5	24.0Ω/M' 78.7Ω/km	14.4Ω/M' 47.2Ω/km	.294 7.47	100	78%	13	42.7	22	72	
	1423A	NEC: CM CEC: CM	6	See Chart 5 (Tech Info Section)	500 1000 10000	152.4 304.8 3048.0	25.0 48.0 500.0	11.4 21.8 227.3	24.0Ω/M' 78.7Ω/km	13.0Ω/M' 42.7Ω/km	.319 8.10	100	78%	13	42.7	22	72	
	1424A	NEC: CM CEC: CM	12.5 (12 prs.+ 1 single)	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	43.0 85.0	19.5 38.6	24.0Ω/M' 78.7Ω/km	13.0Ω/M' 42.7Ω/km	.418 10.62	100	78%	13	42.7	22	72	
	1425A	NEC: CM CEC: CM	15	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	53.0 99.0	24.1 45.0	24.0Ω/M' 78.7Ω/km	11.2Ω/M' 36.7Ω/km	.473 12.01	100	78%	13	42.7	22	72	

DCR = DC Resistance • TC = Tinned Copper


*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Datalene insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-422 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
28 AWG Stranded (7x36) TC Conductors • Overall Beldfoil® (100% Coverage) + TC Braid Shield (90% Coverage) • 28 AWG Stranded TC Drain Wire																		
Polypropylene Insulation • Chrome PVC Jacket																		
	9804	NEC: CL2	2	See Chart 3 (Tech Info Section)	100	30.5	3.9	1.8	64.9Ω/M'	4.9Ω/M'	.214	5.44	100	66%	15.5	50.9	27.5	90.2
					500	152.4	14.5	6.6	212.9Ω/km	16.1Ω/km								
					1000	304.8	32.0	14.5										
	9805	NEC: CL2	3	See Chart 3 (Tech Info Section)	100	30.5	4.2	1.9	64.9Ω/M'	4.2Ω/M'	.222	5.64	100	66%	15.5	50.9	27.5	90.2
					500	152.4	15.5	7.0	212.9Ω/km	13.8Ω/km								
					1000	304.8	35.0	15.9										
	9806	NEC: CL2	4	See Chart 3 (Tech Info Section)	100	30.5	4.3	2.0	64.9Ω/M'	4.0Ω/M'	.237	6.02	100	66%	15.5	50.9	27.5	90.2
					500	152.4	17.5	7.9	212.9Ω/km	13.1Ω/km								
					1000	304.8	39.0	17.7										
	9807	NEC: CL2	5	See Chart 3 (Tech Info Section)	100	30.5	4.3	2.0	64.9Ω/M'	4.2Ω/M'	.240	6.10	100	66%	15.5	50.9	27.5	90.2
500					152.4	18.0	8.2	212.9Ω/km	13.8Ω/km									
1000					304.8	39.0	17.7											
9808	NEC: CL2	7	See Chart 3 (Tech Info Section)	100	30.5	4.9	2.2	64.9Ω/M'	3.7Ω/M'	.256	6.50	100	66%	15.5	50.9	27.5	90.2	
				500	152.4	20.5	9.3	212.9Ω/km	12.1Ω/km									
				1000	304.8	44.0	20.0											
9809	NEC: CL2	9	See Chart 3 (Tech Info Section)	100	30.5	5.7	2.6	64.9Ω/M'	3.1Ω/M'	.290	7.37	100	66%	15.5	50.9	27.5	90.2	
				500	152.4	25.0	11.3	212.9Ω/km	10.2Ω/km									
				1000	304.8	53.0	24.1											
9812	NEC: CL2	12	See Chart 3 (Tech Info Section)	100	30.5	6.7	3.0	64.9Ω/M'	2.8Ω/M'	.319	8.10	100	66%	15.5	50.9	27.5	90.2	
				500	152.4	31.0	14.1	212.9Ω/km	9.2Ω/km									
				1000	304.8	62.0	28.2											
9813	NEC: CL2	13	See Chart 3 (Tech Info Section)	100	30.5	7.0	3.2	64.9Ω/M'	2.2Ω/M'	.336	8.53	100	66%	15.5	50.9	27.5	90.2	
				500	152.4	34.0	15.5	212.9Ω/km	7.2Ω/km									
				1000	304.8	66.0	30.0											
9819	NEC: CL2	18	See Chart 3 (Tech Info Section)	100	30.5	8.3	3.8	64.9Ω/M'	2.0Ω/M'	.365	9.27	100	66%	15.5	50.9	27.5	90.2	
				500	152.4	41.0	18.6	212.9Ω/km	6.7Ω/km									
				1000	304.8	82.0	37.3											
9825	NEC: CL2	25	See Chart 3 (Tech Info Section)	100	30.5	9.9	4.5	64.9Ω/M'	1.9Ω/M'	.429	10.90	100	66%	15.5	50.9	27.5	90.2	
				500	152.4	54.5	24.8	212.9Ω/km	6.2Ω/km									
				1000	304.8	108.0	49.1											
9814	NEC: CL2	31	See Chart 3 (Tech Info Section)	100	30.5	11.8	5.4	64.9Ω/M'	2.1Ω/M'	.462	11.73	100	66%	15.5	50.9	27.5	90.2	
				500	152.4	64.0	29.1	212.9Ω/km	6.9Ω/km									
				1000	304.8	127.0	57.7											


DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-485 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
28 AWG Stranded (7x36) TC Conductors • Overall Beldfoil® (100% Coverage) + TC Braid Shield (65% Coverage) • 28 AWG Stranded TC Drain Wire																		
Datalene® Insulation • Chrome PVC Jacket																		
 Shorting Fold	8132	NEC: CL2	2	See Chart 5 (Tech Info Section)	100	30.5	3.6	1.6	65.0Ω/M'	5.1Ω/M'	.220	5.59	120	78%	11.0	36.1	20.0	65.6
					500	152.4	14.5	6.6	213.0Ω/km	16.6Ω/km								
					1000	304.8	29.0	13.2										
	8133	NEC: CL2	3	See Chart 5 (Tech Info Section)	100	30.5	3.8	1.7	65.0Ω/M'	5.2Ω/M'	.270	6.86	120	78%	11.0	36.1	20.0	65.6
					500	152.4	15.0	6.8	213.0Ω/km	17.1Ω/km								
					1000	304.8	34.0	15.5										
	8134	NEC: CL2	4	See Chart 5 (Tech Info Section)	100	30.5	4.3	2.0	65.0Ω/M'	4.4Ω/M'	.290	7.37	120	78%	11.0	36.1	20.0	65.6
					500	152.4	18.0	8.2	213.0Ω/km	14.3Ω/km								
					1000	304.8	39.0	17.7										
	8135	NEC: CL2	5	See Chart 5 (Tech Info Section)	100	30.5	4.6	2.1	65.0Ω/M'	4.2Ω/M'	.300	7.62	120	78%	11.0	36.1	20.0	65.6
500					152.4	21.0	9.5	213.0Ω/km	13.8Ω/km									
1000					304.8	42.0	19.1											
8138	NEC: CL2	8	See Chart 5 (Tech Info Section)	100	30.5	5.6	2.5	65.0Ω/M'	3.7Ω/M'	.330	8.38	120	78%	11.0	36.1	20.0	65.6	
				500	152.4	27.0	12.3	213.0Ω/km	12.3Ω/km									
				1000	304.8	52.0	23.6											
8142	NEC: CL2	12.5 (12 pairs + 1 single)	See Chart 5 (Tech Info Section)	100	30.5	6.8	3.1	65.0Ω/M'	3.1Ω/M'	.375	9.53	120	78%	11.0	36.1	20.0	65.6	
				500	152.4	33.0	15.0	213.0Ω/km	10.1Ω/km									
				1000	304.8	66.0	29.9											
8148	NEC: CL2	18	See Chart 5 (Tech Info Section)	100	30.5	8.5	3.9	65.0Ω/M'	2.6Ω/M'	.465	11.81	120	78%	11.0	36.1	20.0	65.6	
				500	152.4	47.5	21.6	213.0Ω/km	8.4Ω/km									
				1000	304.8	92.0	41.8											
8155	NEC: CL2	25	See Chart 5 (Tech Info Section)	100	30.5	11.1	5.0	65.0Ω/M'	2.3Ω/M'	.565	14.35	120	78%	11.0	36.1	20.0	65.6	
				500	152.4	64.0	29.1	213.0Ω/km	7.6Ω/km									
				1000	304.8	121.0	55.0											

DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.




**Capacitance between one conductor and other conductors connected to shield.

Datalene insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-485 Applications

Plenum-Rated and Non-Plenum

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) TC Conductors • Overall Beldfoil® (100% Coverage) + TC Braid Shield (90% Coverage) • 24 AWG Stranded TC Drain Wire																		
Polyethylene Insulation • Chrome PVC Jacket																		
	9841	NEC:	1	See Chart 5 (Tech Info Section)	100	30.5	4.3	2.0	24.0Ω/M'	3.4Ω/M'	.232	5.89	120	66%	12.8	42.0	23.0	75.5
		CM			500	152.4	20.0	9.1	78.7Ω/km	11.0Ω/km								
		CEC:			1000	304.8	40.0	18.2										
		CM									For Plenum versions of 9841, see 82841 or 89841.							
	9842	NEC:	2	See Chart 5 (Tech Info Section)	100	30.5	5.8	2.6	24.0Ω/M'	2.2Ω/M'	.340	8.64	120	66%	12.8	42.0	23.0	75.5
		CM			500	152.4	29.5	13.4	78.7Ω/km	7.2Ω/km								
		CEC:			1000	304.8	57.0	25.9										
		CM									For Plenum versions of 9842, see 82842.							
	9843	NEC:	3	See Chart 5 (Tech Info Section)	100	30.5	7.1	3.2	24.0Ω/M'	2.3Ω/M'	.360	9.14	120	66%	12.8	42.0	23.0	75.5
		CM			500	152.4	34.5	15.7	78.7Ω/km	7.7Ω/km								
		CEC:			1000	304.8	67.0	30.5										
		CM																
	9844	NEC:	4	See Chart 5 (Tech Info Section)	500	152.4	43.0	19.5	24.0Ω/M'	2.1Ω/M'	.390	9.91	120	66%	12.8	42.0	23.0	75.5
		CM			1000	304.8	83.0	37.7	78.7Ω/km	6.9Ω/km								
		CEC:																
		CM																
Plenum • Foam FEP Insulation • Natural Flamarrest® Jacket																		
	82841	NEC:	1	See Chart 5 (Tech Info Section)	500	152.4	13.0	6.0	24.0Ω/M'	3.1Ω/M'	.204	5.18	120	76%	12	39.4	22	72.2
		CMP			1000	304.8	26.0	11.8	78.7Ω/km	10.2Ω/km								
	82842	NEC:	2	See Chart 5 (Tech Info Section)	500	152.4	19.0	8.6	24.0Ω/M'	2.4Ω/M'	.273	6.93	120	76%	12	39.4	22	72.2
		CMP			1000	304.8	42.0	19.1	78.7Ω/km	7.9Ω/km								
	82842	CEC:																
		CMP FT6																
Plenum • Foam FEP Insulation • Red FEP Jacket																		
	89841	NEC:	1	See Chart 5 (Tech Info Section)	500	152.4	13.5	6.1	24.0Ω/M'	3.1Ω/M'	.202	5.13	120	76%	12	39.4	22	72.2
		CMP			1000	304.8	27.0	12.3	78.7Ω/km	10.2Ω/km								
	89842 new	NEC:	2	See Chart 5 (Tech Info Section)	500	152.4	25.5	11.6	24.0Ω/M'	3.1Ω/M'	.305	7.75	120	76%	12	39.4	22	72.2
		CMP			1000	304.8	49.0	22.2	78.7Ω/km	10.2Ω/km								
		CEC:																
		CMP FT6																


DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-232 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Overall Beldfoil® (100% Coverage) + TC Braid Shield (65% Coverage)																		
Semi-rigid PVC Insulation • Chrome PVC Jacket																		
 Z-Fold®	8332	NEC:	2	See	100	30.5	4.1	1.9	24.0Ω/M'	5.4Ω/M'	.250	6.35	75	60%	30	98	50	164
		CMG		Chart 5	500	152.4	16.5	7.5	78.7Ω/km	17.7Ω/km								
	CEC:		(Tech Info	1000	304.8	37.0	16.8											
	CMG FT4		Section)															
	8333	NEC:	3	See	100	30.5	4.8	2.2	24.0Ω/M'	6.6Ω/M'	.265	6.73	75	60%	30	98	50	164
		CMG		Chart 5	500	152.4	20.5	9.3	78.7Ω/km	21.7Ω/km								
	CEC:		(Tech Info	1000	304.8	44.0	20.1											
	CMG FT4		Section)															
	8334	NEC:	4	See	100	30.5	5.3	2.4	24.0Ω/M'	4.5Ω/M'	.288	7.32	75	60%	30	98	50	164
		CMG		Chart 5	500	152.4	22.5	10.2	78.7Ω/km	14.8Ω/km								
CEC:		(Tech Info	1000	304.8	49.0	22.3												
CMG FT4		Section)																
8335	NEC:	5	See	100	30.5	6.0	2.7	24.0Ω/M'	4.6Ω/M'	.295	7.49	75	60%	30	98	50	164	
	CMG		Chart 5	500	152.4	29.5	13.4	78.7Ω/km	15.1Ω/km									
CEC:		(Tech Info	1000	304.8	57.0	25.9												
CMG FT4		Section)																
8336	NEC:	6	See	100	30.5	6.5	3.0	24.0Ω/M'	4.7Ω/M'	.310	7.87	75	60%	30	98	50	164	
	CMG		Chart 5	500	152.4	31.5	14.3	78.7Ω/km	15.4Ω/km									
CEC:		(Tech Info	1000	304.8	62.0	28.2												
CMG FT4		Section)																
8337	NEC:	7	See	100	30.5	6.8	3.1	24.0Ω/M'	4.7Ω/M'	.321	8.15	75	60%	30	98	50	164	
	CMG		Chart 5	500	152.4	33.0	14.9	78.7Ω/km	15.4Ω/km									
CEC:		(Tech Info	1000	304.8	65.0	29.5												
CMG FT4		Section)																
8340	NEC:	10	See	100	30.5	9.1	4.1	24.0Ω/M'	3.5Ω/M'	.385	9.78	75	60%	30	98	50	164	
	CMG		Chart 5	500	152.4	43.5	19.7	78.7Ω/km	11.5Ω/km									
CEC:		(Tech Info	1000	304.8	90.0	40.9												
CMG FT4		Section)																
8342	NEC:	12.5	See	100	30.5	11.0	5.0	24.0Ω/M'	3.6Ω/M'	.405	10.29	75	60%	30	98	50	164	
	CMG	(12 pairs + 1 single)	Chart 5	500	152.4	55.0	25.0	78.7Ω/km	11.8Ω/km									
CEC:		(Tech Info	1000	304.8	109.0	49.5												
CMG FT4		Section)																
8345	NEC:	15	See	500	152.4	61.5	28.0	24.0Ω/M'	3.2Ω/M'	.445	11.30	75	60%	30	98	50	164	
	CMG		Chart 5	1000	304.8	123.0	55.9	78.7Ω/km	10.5Ω/km									
CEC:		(Tech Info																
CMG FT4		Section)																
8348	NEC:	18	See	100	30.5	14.2	6.4	24.0Ω/M'	2.7Ω/M'	.480	12.19	75	60%	30	98	50	164	
	CMG		Chart 5	500	152.4	78.5	35.8	78.7Ω/km	8.9Ω/km									
CEC:		(Tech Info	1000	304.8	152.0	69.3												
CMG FT4		Section)																
8355	NEC:	25	See	500	152.4	96.5	43.9	24.0Ω/M'	2.5Ω/M'	.550	13.97	75	60%	30	98	50	164	
	CMG		Chart 5	1000	304.8	195.0	88.6	78.7Ω/km	8.2Ω/km									
CEC:		(Tech Info																
CMG FT4		Section)																


DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-422 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Overall Beldfoil® (100% Coverage) + TC Braid Shield (65% Coverage) • TC Drain Wire†																		
Polyethylene Insulation • Chrome PVC Jacket																		
 UL AWM Style 2919 (30V 80°C) Z-Fold®	9829	NEC: CM CEC: CM CM	2	See Chart 5 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	4.7 22.0 43.0	2.1 10.0 19.5	24.0Ω/M' 78.7Ω/km	4.4Ω/M' 14.4Ω/km	.291 7.39	100	66%	15.5	50.9	27.5	90.2	
	9830	NEC: CM CEC: CM CM	3	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	26.5 53.0	12.0 24.1	24.0Ω/M' 78.7Ω/km	4.4Ω/M' 14.4Ω/km	.305 7.74	100	66%	15.5	50.9	27.5	90.2	
	9831	NEC: CM CEC: CM CM	4	See Chart 5 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	6.2 30.0 58.0	2.8 13.6 26.4	24.0Ω/M' 78.7Ω/km	3.9Ω/M' 12.8Ω/km	.330 8.38	100	66%	15.5	50.9	27.5	90.2	
	9832	NEC: CM CEC: CM CM	5	See Chart 5 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	6.6 32.5 65.0	3.0 14.8 29.5	24.0Ω/M' 78.7Ω/km	3.9Ω/M' 12.8Ω/km	.338 8.59	100	66%	15.5	50.9	27.5	90.2	
	9839	NEC: CM CEC: CM CM	6	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	35.5 69.0	16.1 31.4	24.0Ω/M' 78.7Ω/km	2.1Ω/M' 6.9Ω/km	.364 9.25	100	66%	15.5	50.9	27.5	90.2	
	9833	NEC: CM CEC: CM CM	7	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	38.5 77.0	17.5 35.0	24.0Ω/M' 78.7Ω/km	3.7Ω/M' 12.1Ω/km	.370 9.40	100	66%	15.5	50.9	27.5	90.2	
	9834	NEC: CM CEC: CM CM	9	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	47.0 93.0	21.4 42.3	24.0Ω/M' 78.7Ω/km	3.0Ω/M' 9.8Ω/km	.419 10.64	100	66%	15.5	50.9	27.5	90.2	
	9835	NEC: CM CEC: CM CM	10	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	51.5 102.0	23.4 46.4	24.0Ω/M' 78.7Ω/km	2.8Ω/M' 9.2Ω/km	.451 11.46	100	66%	15.5	50.9	27.5	90.2	
	9836	NEC: CM CEC: CM CM	12	See Chart 5 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	10.4 57.0 114.0	4.7 25.9 51.8	24.0Ω/M' 78.7Ω/km	2.8Ω/M' 9.2Ω/km	.464 11.79	100	66%	15.5	50.9	27.5	90.2	
	9837	NEC: CM CEC: CM CM	18	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	87.5 174.0	39.8 79.1	24.0Ω/M' 78.7Ω/km	2.0Ω/M' 6.6Ω/km	.567 14.40	100	66%	15.5	50.9	27.5	90.2	
9838	NEC: CM CEC: CM CM	25	See Chart 5 (Tech Info Section)	500	152.4	113.0	51.4	24.0Ω/M' 78.7Ω/km	1.9Ω/M' 6.2Ω/km	.670 17.02	100	66%	15.5	50.9	27.5	90.2		

†24 AWG stranded TC drain wire.

†24 AWG stranded TC drain wire.


DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-422 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Overall Beldfoil® (100% Coverage) + TC Braid Shield (65% Coverage) • Drain Wire†																		
Datalene® Insulation • Chrome PVC Jacket																		
UL AWM Style 2919 (30V 80°C)  Shorting Fold	8102	NEC:	2	See	100	30.5	4.1	1.9	24.0Ω/M'	4.6Ω/M'	.270	6.86	100	78%	12.5	41	22	72.2
		CM		Chart 5	500	152.4	17.0	7.7	78.7Ω/km	15.1Ω/km								
		CEC:		(Tech Info	1000	304.8	38.0	17.3										
		CM		Section)	10000	3048.0	380.0	172.7										
	8103	NEC:	3	See	100	30.5	4.6	2.1	24.0Ω/M'	3.8Ω/M'	.283	7.19	100	78%	12.5	41	22	72.2
		CM		Chart 5	500	152.4	19.5	8.9	78.7Ω/km	12.5Ω/km								
		CEC:		(Tech Info	1000	304.8	42.0	19.1										
		CM		Section)	10000	3048.0	430.0	195.5										
	8104	NEC:	4	See	100	30.5	5.1	2.3	24.0Ω/M'	4.1Ω/M'	.302	7.67	100	78%	12.5	41	22	72.2
		CM		Chart 5	500	152.4	21.0	9.5	78.7Ω/km	13.5Ω/km								
		CEC:		(Tech Info	1000	304.8	46.0	20.9										
		CM		Section)	10000	3048.0	490.0	222.7										
	8105	NEC:	5	See	100	30.5	5.8	2.6	24.0Ω/M'	4.2Ω/M'	.316	8.03	100	78%	12.5	41	22	72.2
		CM		Chart 5	500	152.4	28.0	12.7	78.7Ω/km	13.8Ω/km								
		CEC:		(Tech Info	1000	304.8	53.0	24.1										
CM		Section)																
8106	NEC:	6	See	100	30.5	6.3	2.9	24.0Ω/M'	3.5Ω/M'	.341	8.66	100	78%	12.5	41	22	72.2	
	CM		Chart 5	500	152.4	30.5	13.9	78.7Ω/km	11.5Ω/km									
	CEC:		(Tech Info	1000	304.8	58.0	26.4											
	CM		Section)															
8107	NEC:	7	See	100	30.5	6.8	3.1	24.0Ω/M'	3.5Ω/M'	.341	8.66	100	78%	12.5	41	22	72.2	
	CM		Chart 5	500	152.4	33.0	15.0	78.7Ω/km	11.5Ω/km									
	CEC:		(Tech Info	1000	304.8	63.0	28.6											
	CM		Section)															
8108	NEC:	8	See	100	30.5	7.6	3.5	24.0Ω/M'	2.7Ω/M'	.370	9.40	100	78%	12.5	41	22	72.2	
	CM		Chart 5	500	152.4	37.5	17.1	78.7Ω/km	8.9Ω/km									
	CEC:		(Tech Info	1000	304.8	72.0	32.8											
	CM		Section)															
8110	NEC:	10	See	100	30.5	8.1	3.7	24.0Ω/M'	2.4Ω/M'	.427	10.85	100	78%	12.5	41	22	72.2	
	CM		Chart 5	500	152.4	45.5	20.7	78.7Ω/km	7.9Ω/km									
	CEC:		(Tech Info	1000	304.8	90.0	40.9											
	CM		Section)															
8112	NEC:	12.5 (12 pairs + 1 single)	See	100	30.5	9.2	4.2	24.0Ω/M'	2.4Ω/M'	.440	11.18	100	78%	12.5	41	22	72.2	
	CM		Chart 5	500	152.4	51.0	23.3	78.7Ω/km	7.9Ω/km									
	CEC:		(Tech Info	1000	304.8	101.0	45.9											
	CM		Section)															
8115	NEC:	15	See	500	152.4	63.5	28.9	24.0Ω/M'	2.6Ω/M'	.495	12.57	100	78%	12.5	41	22	72.2	
	CM		Chart 5	1000	304.8	116.0	52.7	78.7Ω/km	8.5Ω/km									
	CEC:		(Tech Info															
	CM		Section)															
8118	NEC:	18	See	100	30.5	13.3	6.0	24.0Ω/M'	2.1Ω/M'	.537	13.64	100	78%	12.5	41	22	72.2	
	CM		Chart 5	500	152.4	70.5	32.0	78.7Ω/km	6.9Ω/km									
	CEC:		(Tech Info	1000	304.8	144.0	65.5											
	CM		Section)															
8125	NEC:	25	See	100	30.5	20.7	9.4	24.0Ω/M'	2.0Ω/M'	.632	16.05	100	78%	12.5	41	22	72.2	
	CM		Chart 5	500	152.4	98.0	44.5	78.7Ω/km	6.6Ω/km									
	CEC:		(Tech Info	1000	304.8	191.0	86.8											
	CM		Section)															

†24 AWG stranded TC drain wire.

†24 AWG stranded TC drain wire.

DCR = DC Resistance • TC = Tinned Copper



*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Datalene insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-232 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
22 AWG Stranded (7x30) Tinned Copper Conductors • Twisted Pairs • Overall Beldfoil® (100% Coverage) + TC Braid Shield (65% Coverage)																		
Semi-rigid PVC Insulation • Chrome PVC Jacket																		
UL AWM Style 2464 (300V 80°C)  Z-Fold®	8302	NEC: CMG CEC: CMG FT4	2	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	4.5 19.0 41.0	2.0 8.6 18.6	15.0Ω/M' 49.2Ω/km	5.7Ω/M' 18.7Ω/km	.260 6.60	70	60%	40	131	72	236	
	8303	NEC: CMG CEC: CMG FT4	3	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	5.2 25.5 48.0	2.4 11.6 21.8	15.0Ω/M' 49.2Ω/km	6.2Ω/M' 20.3Ω/km	.270 6.86	70	60%	35	115	63	207	
	8304	NEC: CMG CEC: CMG FT4	4	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	6.7 32.5 65.0	3.0 14.7 29.5	15.0Ω/M' 49.2Ω/km	4.9Ω/M' 16.1Ω/km	.320 8.13	70	60%	35	115	63	207	
	8305	NEC: CMG CEC: CMG FT4	5	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	7.2 35.0 67.0	3.3 15.9 30.4	15.0Ω/M' 49.2Ω/km	4.8Ω/M' 15.7Ω/km	.322 8.18	70	60%	35	115	63	207	
	8306	NEC: CMG CEC: CMG FT4	6	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	8.0 39.5 79.0	3.6 18.0 35.8	15.0Ω/M' 49.2Ω/km	5.0Ω/M' 16.4Ω/km	.348 8.84	70	60%	35	115	63	207	
	8307	NEC: CMG CEC: CMG FT4	7	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	8.6 42.0 85.0	3.9 19.0 38.6	15.0Ω/M' 49.2Ω/km	5.0Ω/M' 16.4Ω/km	.348 8.84	70	60%	35	115	63	207	
	8308	NEC: CMG CEC: CMG FT4	8	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	10.4 50.0 101.0	4.7 22.7 46.0	15.0Ω/M' 49.2Ω/km	4.4Ω/M' 14.4Ω/km	.384 9.75	70	60%	35	115	63	207	
	8310	NEC: CMG CEC: CMG FT4	10	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	11.1 60.5 121.0	5.0 27.4 54.9	15.0Ω/M' 49.2Ω/km	4.1Ω/M' 13.4Ω/km	.440 11.18	70	60%	35	115	63	207	
	8312	NEC: CMG CEC: CMG FT4	12	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	12.9 72.0 140.0	5.9 32.8 63.8	15.0Ω/M' 49.2Ω/km	4.2Ω/M' 13.8Ω/km	.455 11.56	70	60%	35	115	63	207	
	8315	NEC: CMG CEC: CMG FT4	15	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	15.7 85.5 167.0	7.1 39.0 76.1	15.0Ω/M' 49.2Ω/km	3.8Ω/M' 12.5Ω/km	.502 12.75	70	60%	35	115	63	207	
	8318	NEC: CMG CEC: CMG FT4	18	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	17.7 97.5 196.0	8.0 44.2 89.1	15.0Ω/M' 49.2Ω/km	3.0Ω/M' 9.8Ω/km	.535 13.59	70	60%	35	115	63	207	
	8325	NEC: CMG CEC: CMG FT4	25	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	23.1 126.0 246.0	10.5 57.4 112.1	15.0Ω/M' 49.2Ω/km	2.9Ω/M' 9.5Ω/km	.620 15.75	70	60%	35	115	63	207	


DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Individually Shielded

Low-Capacitance 100 Ohm Computer Cables for EIA RS-422, and Digital Audio Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance							
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m				
24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil® (100% Coverage) • 24 AWG Stranded TC Drain Wire																						
Datalene® Insulation • Chrome PVC Jacket																						
 Z-Fold®	9729	NEC:	2	See	100	30.5	4.3	2.0	24.0Ω/M'	15.0Ω/M'	.266	6.76	100	76%	12.5	41.0	23.2	76.1				
		CM		Chart 3	500	152.4	20.5	9.3	78.7Ω/km	49.2Ω/km												
	CEC:	(Tech Info	1000	304.8	39.0	17.7			For Plenum version of 9729, see 89729 or 82729.													
	CM	Section)	10000†	3048.0	390.0	177.8																
	9730	NEC:	3	See	100	30.5	5.1	2.3	24.0Ω/M'	15.0Ω/M'	.334	8.48	100	76%	12.5	41.0	23.2	76.1				
		CM		Chart 3	500	152.4	24.5	11.1	78.7Ω/km	49.2Ω/km												
		CEC:		(Tech Info	1000	304.8	46.0	20.9											For Plenum version of 9730, see 89730.			
		CM		Section)	10000†	3048.0	520.0	236.4														
	9728	NEC:	4	See	100	30.5	6.0	2.7	24.0Ω/M'	15.0Ω/M'	.363	9.22	100	76%	12.5	41.0	23.2	76.1				
		CM		Chart 3	500	152.4	29.0	13.2	78.7Ω/km	49.2Ω/km												
CEC:		(Tech Info		1000	304.8	51.0	23.1			For Plenum version of 9728, see 89728.												
CM		Section)																				
9731	NEC:	6	See	100	30.5	7.4	3.4	24.0Ω/M'	15.0Ω/M'	.421	10.69	100	76%	12.5	41.0	23.2	76.1					
	CM		Chart 3	500	152.4	42.0	19.1	78.7Ω/km	49.2Ω/km													
	CEC:		(Tech Info	1000	304.8	83.0	37.7											For Plenum version of 9731, see 89731.				
	CM		Section)																			
9732	NEC:	9	See	100	30.5	9.9	4.5	24.0Ω/M'	15.0Ω/M'	.488	12.40	100	76%	12.5	41.0	23.2	76.1					
	CM		Chart 3	500	152.4	57.0	26.0	78.7Ω/km	49.2Ω/km													
	CEC:		(Tech Info	1000	304.8	106.0	48.1											For Plenum version of 9732, see 89732.				
	CM		Section)																			
9733	NEC:	11	See	500	152.4	75.0	34.1	24.0Ω/M'	15.0Ω/M'	.575	14.61	100	76%	12.5	41.0	23.2	76.1					
	CM		Chart 3					78.7Ω/km	49.2Ω/km													
	CEC:		(Tech Info																			
	CM		Section)																			
9734	NEC:	12	See	500	152.4	79.5	36.1	24.0Ω/M'	15.0Ω/M'	.575	14.61	100	76%	12.5	41.0	23.2	76.1					
	CM		Chart 3	1000	304.8	154.0	70.0	78.7Ω/km	49.2Ω/km													
	CEC:		(Tech Info																			
	CM		Section)																			
9735	NEC:	15	See	500	152.4	95.0	43.2	24.0Ω/M'	15.0Ω/M'	.639	16.23	100	76%	12.5	41.0	23.2	76.1					
	CM		Chart 3	1000	304.8	185.0	84.1	78.7Ω/km	49.2Ω/km													
	CEC:		(Tech Info																			
	CM		Section)																			
9736	NEC:	17	See	500	152.4	103.5	47.0	24.0Ω/M'	15.0Ω/M'	.671	17.04	100	76%	12.5	41.0	23.2	76.1					
	CM		Chart 3	1000	304.8	210.0	95.5	78.7Ω/km	49.2Ω/km													
	CEC:		(Tech Info																			
	CM		Section)																			
9737	NEC:	19	See	1000	304.8	231.0	105.0	24.0Ω/M'	15.0Ω/M'	.671	17.04	100	76%	12.5	41.0	23.2	76.1					
	CM		Chart 3					78.7Ω/km	49.2Ω/km													
	CEC:		(Tech Info																			
	CM		Section)																			
9738	NEC:	27	See	1000	304.8	334.0	151.8	24.0Ω/M'	15.0Ω/M'	.797	20.24	100	76%	12.5	41.0	23.2	76.1					
	CM		Chart 3					78.7Ω/km	49.2Ω/km													
	CEC:		(Tech Info																			
	CM		Section)																			

DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

† Final put-up length may vary -10% to +20% from length shown. May contain 2 pieces. Minimum length of any one piece is 1500 ft.

See Attenuation, Rise Time and Bit Rate Data for this series on page 5.34.

Datalene insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.


Individually Shielded

Low-Capacitance Computer Cables for EIA RS-232, EIA RS-422, and Digital Audio Applications
Plenum-Rated


Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil® (100% Coverage) • 24 AWG Stranded TC Drain Wire

Plenum • Foam FEP Insulation • Gray Fluorocopolymer Jacket

	300V RMS	89729	NEC: CMP CEC: CMP FT6	2	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	17.0 31.0	7.7 14.1	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.261 6.63	100	76%	13.5	44	22.5	73.8
		89730	NEC: CMP CEC: CMP FT6	3	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	21.5 40.0	9.8 18.2	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.278 7.06	100	76%	13.5	44	22.5	73.8
		89728	NEC: CMP CEC: CMP FT6	4	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	26.5 50.0	12.0 22.7	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.307 7.80	100	76%	13.5	44	22.5	73.8
		89731	NEC: CMP CEC: CMP FT6	6	See Chart 5 (Tech Info Section)	500 1000†	152.4 304.8	35.0 71.0	15.9 32.3	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.361 9.17	100	76%	13.5	44	22.5	73.8
		89732	NEC: CMP CEC: CMP FT6	9	See Chart 5 (Tech Info Section)	1000	304.8	108.0	49.0	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.429 10.90	100	76%	13.5	44	22.5	73.8

Plenum • Foam FEP Insulation • Natural Flamarrest® Jacket

	300V RMS	82729	NEC: CMP CEC: CMP FT6	2	See Chart 5 (Tech Info Section)	U-1000 1000	U-304.8 304.8	26.0 28.0	11.8 12.7	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.255 6.48	100	76%	13.5	44	22.5	73.8
--	----------	--------------	--------------------------------	---	--	----------------	------------------	--------------	--------------	----------------------	----------------------	--------------	-----	-----	------	----	------	------

DCR = DC Resistance • TC = Tinned Copper


*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

† Spools are one piece, but length may vary ±10% from length shown.

Individually Shielded Pairs with Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-232, EIA RS-422, and Digital Audio Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) TC Conductors • Twisted Pairs Individually Beldfoil® Shielded + Overall Beldfoil (100% Coverage) + TC Braid Shield (65%) • Drain Wire▲																		
Datalene® Insulation • Chrome PVC Jacket																		
UL AWM Style 2493 (60°C) VW-1 	8162	NEC:	2	See Chart 3 (Tech Info Section)	100	30.5	6.2	2.8	24.0Ω/M'	Individual: 18.0Ω/M' 59.1Ω/km Overall: 4.3Ω/M' 14.1Ω/km	.343	8.71	100	78%	12.5	41	22	72.2
		CM			500	152.4	30.0	13.6	78.7Ω/km									
		CEC:			1000	304.8	57.0	25.9										
		CM																
	8163	NEC:	3	See Chart 3 (Tech Info Section)	100	30.5	7.0	3.2	24.0Ω/M'	Individual: 18.0Ω/M' 59.1Ω/km Overall: 4.4Ω/M' 14.4Ω/km	.359	9.12	100	78%	12.5	41	22	72.2
CM		500			152.4	34.0	15.5	78.7Ω/km										
CEC:		1000			304.8	66.0	30.0											
CM																		
	8164	NEC:	4	See Chart 3 (Tech Info Section)	100	30.5	8.2	3.7	24.0Ω/M'	Individual: 18.0Ω/M' 59.1Ω/km Overall: 3.2Ω/M' 10.5Ω/km	.388	9.86	100	78%	12.5	41	22	72.2
CM		500			152.4	39.5	18.0	78.7Ω/km										
CEC:		1000			304.8	79.0	35.9											
CM																		
	8165	NEC:	5	See Chart 3 (Tech Info Section)	100	30.5	9.0	4.1	24.0Ω/M'	Individual: 18.0Ω/M' 59.1Ω/km Overall: 3.4Ω/M' 11.2Ω/km	.413	10.49	100	78%	12.5	41	22	72.2
CM		500			152.4	45.0	20.5	78.7Ω/km										
CEC:		1000			304.8	89.0	40.5											
CM																		
	8166	NEC:	6	See Chart 3 (Tech Info Section)	100	30.5	9.0	4.1	24.0Ω/M'	Individual: 18.0Ω/M' 59.1Ω/km Overall: 2.8Ω/M' 9.2Ω/km	.446	11.33	100	78%	12.5	41	22	72.2
CM		500			152.4	50.0	22.7	78.7Ω/km										
CEC:		1000			304.8	99.0	45.0											
CM																		
	8167	NEC:	7	See Chart 3 (Tech Info Section)	500	152.4	52.5	23.9	24.0Ω/M'	Individual: 18.0Ω/M' 59.1Ω/km Overall: 2.8Ω/M' 9.2Ω/km	.446	11.33	100	78%	12.5	41	22	72.2
CM		1000			304.8	103.0	46.7	78.7Ω/km										
CEC:																		
CM																		

▲24 AWG stranded TC drain wire

[▲]24 AWG stranded TC drain wire

DCR = DC Resistance • TC = Tinned Copper


*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Datalene insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

Individually Shielded Pairs with Overall Foil/Braid Shield

Low-Capacitance Computer Cables for EIA RS-232, EIA RS-422, and Digital Audio Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) TC Conductors • Twisted Pairs Individually Beldfoil® Shielded + Overall Beldfoil (100% Coverage) + TC Braid Shield (65%) • Drain Wire [▲]																		
Datalene® Insulation • Chrome PVC Jacket																		
UL AWM Style 2493 (60°C) VW-1  Z-Fold®	8168	NEC: CM CEC: CM	8	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	10.8 61.5 115.0	4.9 28.0 52.3	24.0Ω/M' 78.7Ω/km	Individual: 18.0Ω/M' 59.1Ω/km Overall: 3.0Ω/M' 9.8Ω/km	.479	12.17	100	78%	12.5	41	22	72.2
	8170	NEC: CM CEC: CM	10	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	18.0 83.0 164.0	8.2 37.7 74.5	24.0Ω/M' 78.7Ω/km	Individual: 18.0Ω/M' 59.1Ω/km Overall: 2.7Ω/M' 8.9Ω/km	.584	14.83	100	78%	12.5	41	22	72.2
	8175	NEC: CM CEC: CM	15	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	22.6 107.5 210.0	10.3 48.9 95.5	24.0Ω/M' 78.7Ω/km	Individual: 18.0Ω/M' 59.1Ω/km Overall: 2.5Ω/M' 8.2Ω/km	.665	16.89	100	78%	12.5	41	22	72.2
	8178	NEC: CM CEC: CM	18	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	24.6 117.0 238.0	11.2 53.2 108.2	24.0Ω/M' 78.7Ω/km	Individual: 18.0Ω/M' 59.1Ω/km Overall: 2.6Ω/M' 8.5Ω/km	.686	17.42	100	78%	12.5	41	22	72.2
	8185	NEC: CM CEC: CM	25	See Chart 3 (Tech Info Section)	100 500 1000	30.5 152.4 304.8	32.3 160.5 356.0	14.7 73.0 161.8	24.0Ω/M' 78.7Ω/km	Individual: 18.0Ω/M' 59.1Ω/km Overall: 2.4Ω/M' 7.9Ω/km	.822	20.88	100	78%	12.5	41	22	72.2

▲24 AWG stranded TC drain wire

[▲]24 AWG stranded TC drain wire

DCR = DC Resistance • TC = Tinned Copper


*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Plenum-Rated

Overall Beldfoil® Shield

Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-422 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) Tinned Copper Conductors • Twisted Pairs • Overall Beldfoil Shield (100% Coverage) • 24 AWG Stranded TC Drain Wire																		
Plenum • Foam FEP Insulation • Gray Fluorocopolymer Jacket																		
	300V RMS	88102	NEC: CMP CEC: CMP FT6	2	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	10.0 20.0	4.5 9.1	24.0Ω/M' 78.7Ω/km	15.5Ω/M' 50.9Ω/km	.203 5.16	100	78%	12.95	42.5	23.3	76.4
		88103	NEC: CMP CEC: CMP FT6	3	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	13.5 31.0	6.1 14.1	24.0Ω/M' 78.7Ω/km	15.5Ω/M' 50.9Ω/km	.239 6.07	100	78%	12.95	42.5	23.3	76.4
		88104	NEC: CMP CEC: CMP FT6	4	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	17.0 38.0	7.7 17.3	24.0Ω/M' 78.7Ω/km	14.0Ω/M' 45.9Ω/km	.259 6.58	100	78%	12.95	42.5	23.3	76.4
		88105	NEC: CMP CEC: CMP FT6	5	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	23.5 44.0	10.7 20.0	24.0Ω/M' 78.7Ω/km	14.0Ω/M' 45.9Ω/km	.267 6.78	100	78%	12.95	42.5	23.3	76.4
		88106	NEC: CMP CEC: CMP FT6	6	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	26.5 50.0	12.0 22.7	24.0Ω/M' 78.7Ω/km	14.0Ω/M' 45.9Ω/km	.293 7.44	100	78%	12.95	42.5	23.3	76.4
		88107	NEC: CMP CEC: CMP FT6	7.5 (7 pairs + 1 single)	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	31.0 59.0	14.1 26.8	24.0Ω/M' 78.7Ω/km	14.0Ω/M' 45.9Ω/km	.293 7.44	100	78%	12.95	42.5	23.3	76.4
		88109	NEC: CMP CEC: CMP FT6	9	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	36.5 74.0	16.6 33.6	24.0Ω/M' 78.7Ω/km	13.0Ω/M' 42.7Ω/km	.352 8.94	100	78%	12.95	42.5	23.3	76.4
		88112	NEC: CMP CEC: CMP FT6	12.5 (12 pairs + 1 single)	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	48.0 97.0	21.8 44.1	24.0Ω/M' 78.7Ω/km	11.8Ω/M' 38.7Ω/km	.397 10.08	100	78%	12.95	42.5	23.3	76.4
		88118	NEC: CMP CEC: CMP FT6	18.5 (18 pairs + 1 single)	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	71.0 148.0	32.2 67.3	24.0Ω/M' 78.7Ω/km	11.0Ω/M' 36.1Ω/km	.482 12.24	100	78%	12.95	42.5	23.3	76.4
		88125	NEC: CMP CEC: CMP FT6	25	See Chart 5 (Tech Info Section)	500 [†] 1000 [†]	152.4 304.8	98.0 195.0	44.5 88.6	24.0Ω/M' 78.7Ω/km	9.6Ω/M' 31.5Ω/km	.581 14.76	100	78%	12.95	42.5	23.3	76.4

DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

† Spools are one piece, but length may vary ±10% from length shown.

Plenum-Rated

Overall Foil/Braid Shield

Low-Capacitance Computer and Computer P.O.S. Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ ft.	* pF/ m	** pF/ ft.	** pF/ m

Low Cap 24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Overall Beldfoil® (100% Coverage) + TC Braid Shield (90% Cov.) • Drain Wire

Plenum • Foam FEP Insulation • Natural Flamarrest® Jacket

300V RMS 	82841	NEC:	1	See Chart 5 (Tech Info Section)	500	152.4	13.0	6.0	24.0Ω/M'	3.1Ω/M'	.204	5.18	120	76%	12	39.4	22	72.2
		CMP CEC: CMP FT6			1000	304.8	26.0	11.8	78.7Ω/km	10.2Ω/km								

300V RMS 	82842	NEC:	2	See Chart 5 (Tech Info Section)	500	152.4	19.0	8.6	24.0Ω/M'	2.4Ω/M'	.273	6.93	120	76%	12	39.4	22	72.2
		CMP CEC: CMP FT6			1000	304.8	42.0	19.1	78.7Ω/km	7.9Ω/km								

Plenum • Foam FEP Insulation • Red FEP Jacket

300V RMS 	89841	NEC:	1	See Chart 5 (Tech Info Section)	500	152.4	13.5	6.1	24.0Ω/M'	3.1Ω/M'	.202	5.13	120	76%	12	39.4	22	72.2
		CMP CEC: CMP FT6			1000	304.8	27.0	12.3	78.7Ω/km	10.2Ω/km								

300V RMS 	89842 new	NEC:	2	See Chart 5 (Tech Info Section)	500	152.4	25.5	11.6	24.0Ω/M'	3.1Ω/M'	.305	7.75	120	76%	12	39.4	22	72.2
		CMP CEC: CMP FT6			1000	304.8	49.0	22.2	78.7Ω/km	10.2Ω/km								

22 AWG Solid TC Conductors • Twisted Pairs • Overall Beldfoil (100% Coverage) + TC Braid Shield (90% Coverage) • 22 AWG TC Drain Wire

Plenum • Solid FEP Insulation • Black FEP Jacket

300V RMS 	1269A	NEC:	2	Red & Blue, Black & Yellow	1000	304.8	48.0	21.8	16.5Ω/M'	2.1Ω/M'	.240	6.10	100	69.5%	15.5	50.9	27	88.6
		MPP, CMP CEC: MPP, CMP FT6							54.1Ω/km	6.9Ω/km								

22 AWG Solid TC Conductors • Twisted Pairs • Overall Beldfoil (100% Coverage) + TC Braid Shield (55% Cov.) + Polyester Tape • 22 AWG Drain Wire

Plenum • Solid FEP Insulation • Black FEP Jacket

300V RMS 	89855	NEC:	2	1 Pair: Red & Blue	500	152.4	22.5	10.2	16.5Ω/M'	4.9Ω/M'	.272	6.91	100	69.5%	15.5	50.9	27	88.6
		MPP, CMP CEC: MPP, CMP FT6			1000	304.8	42.0	19.1	54.1Ω/km	16.1Ω/km								

22 AWG Solid BC Conductors • Twisted Pairs • Overall Beldfoil (100% Coverage) + TC Braid Shield (55% Coverage) • 22 AWG Solid TC Drain Wire

Plenum • Solid FEP Insulation • Black FEP Jacket

300V RMS 	89696	NEC:	2	1 Pair: Blue & White with Blue Stripe	500	152.4	25.0	11.4	16.5Ω/M'	4.2Ω/M'	.262	6.65	100	69.5%	15.5	50.9	27	88.6
		MPP, CMP CEC: MPP, CMP FT6			1000	304.8	46.0	20.9	54.1Ω/km	13.8Ω/km								

BC = Bare Copper • DCR = DC Resistance • TC = Tinned Copper



*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Plenum-Rated

Individually Shielded Pairs

Low-Capacitance Computer Cables for EIA RS-232, EIA RS-422, and Digital Audio Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil® (100% Coverage) • 24 AWG Stranded TC Drain Wire																		
Plenum • Foam FEP Insulation • Gray Fluorocopolymer Jacket																		
300V RMS 	89729	NEC: CMP CEC: CMP FT6	2	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	17.0 31.0	7.7 14.1	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.261 6.63	100	76%	13.5	44	22.5	73.8	
	89730	NEC: CMP CEC: CMP FT6	3	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	21.5 40.0	9.8 18.2	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.278 7.06	100	76%	13.5	44	22.5	73.8	
	89728	NEC: CMP CEC: CMP FT6	4	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	26.5 50.0	12.0 22.7	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.307 7.80	100	76%	13.5	44	22.5	73.8	
	89705	NEC: CMP CEC: CMP FT6	5	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	30.5 62.0	13.9 28.2	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.333 8.50	100	76%	13.5	44	22.5	73.8	
	89731	NEC: CMP CEC: CMP FT6	6	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	35.0 71.0	15.9 32.3	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.361 9.17	100	76%	13.5	44	22.5	73.8	
	89757	NEC: CMP CEC: CMP FT6	7	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	39.5 80.0	18.0 36.4	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.361 9.17	100	76%	13.5	44	22.5	73.8	
	89732	NEC: CMP CEC: CMP FT6	9	See Chart 5 (Tech Info Section)	1000	304.8	108.0	49.2	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.433 10.90	100	76%	13.5	44	22.5	73.8	
	89734	NEC: CMP CEC: CMP FT6	12	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	71.0 140.0	32.3 63.6	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.498 12.65	100	76%	13.5	44	22.5	73.8	
	89758	NEC: CMP CEC: CMP FT6	18	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	100.5 204.0	45.7 92.7	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.616 15.65	100	76%	13.5	44	22.5	73.8	
Plenum • Foam FEP Insulation • Natural Flamarrest® Jacket																		
300V RMS 	82729	NEC: CMP CEC: CMP FT6	2	See Chart 5 (Tech Info Section)	U-1000 1000	U-304.8 304.8	26.0 28.0	11.8 12.7	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.255 6.48	100	76%	13.5	44	22.5	73.8	

DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Line Level Analog Audio Cable

Single-Pair Cables



Belden analog audio cables are used for connecting line level audio equipment in either permanent or semi-permanent installations. They consist of one or two individually foil-shielded, twisted pairs. Once installed, they are not intended to be moved while in service. For cables that are in motion during use, refer to the Microphone and Musical Instrument Cable section in this catalog.

Belden's analog audio cable offering consists of a selection of designs to handle a variety of audio applications. Belden part

no. 8451 utilizes a paper tape separator to facilitate easy long length jacket stripping. Part no. 9451 comes with a bonded Beldfoil® shield so that the shield and jacket strip simultaneously. A special matte PVC jacket material is employed on part no. 1508A making it a highly flexible construction. Double pair cables are available in a round construction (part no. 8723) or in a ZIP cord style (part no. 1504A) for easy separation in two-channel or stereo hook-ups.

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

24 AWG Stranded (7x32) TC Conductors • Twisted Pair • Overall Beldfoil Shield (100% Coverage) • 24 AWG Stranded TC Drain Wire

Polypropylene Insulation • PVC Jacket (Available in Brown, Red, Green, Lt. Blue, Purple, Gray, White or Black)

300V RMS 60°C	1883A	NEC: CMR CEC: CMG FT4	1	Black, Red	U-1000 1000 ▲	U-304.8 304.8	11.0 11.0	5.0 5.0	.008 .008	.20 .20	.020 .020	.51 .51	.123 3.12	31	102	58	190
---------------	--------------	--------------------------------	---	---------------	------------------	------------------	--------------	------------	--------------	------------	--------------	------------	--------------	----	-----	----	-----



Z-Fold®

For cross-connect use with 1408R (et al.)
Snake Cables, see page 19.18.

▲1000 ft. put-up available in Gray only.

Jacket and shield are bonded so both can be removed with automatic stripping equipment.

Polyolefin Insulation • Black Matte PVC Jacket

High-Flex 300V RMS 60°C	1508A	NEC: CM CEC: CM	1	Black, Red	500 1000	152.4 304.8	6.5 11.0	2.9 5.0	.008 .008	.20 .20	.024 .024	.61 .61	.131 3.33	31	102	58	190
----------------------------	--------------	--------------------------	---	---------------	-------------	----------------	-------------	------------	--------------	------------	--------------	------------	--------------	----	-----	----	-----



For cross-connect use with 1408R (et al.)
Snake Cables, see page 19.18.

Jacket and shield are bonded so both can be removed with automatic stripping equipment.

24 AWG Stranded (7x32) TC Conductors • Twisted Pair • Overall Beldfoil Shield (100% Coverage) • 24 AWG Stranded TC Drain Wire**

Polyethylene Insulation • Chrome PVC Jacket

Low-Capacitance UL AWM Style 2092 (300V RMS 60°C)	8641	NEC: CM CEC: CM	1	Black, Clear	100 U-500 500 U-1000 1000 2000	30.5 U-152.4 152.4 U-304.8 304.8 609.6	2.3 7.5 7.0 14.0 14.0 28.0	1.0 3.4 3.2 6.4 6.4 12.7	.016 .016 .016 .016 .016 .016	.41 .41 .41 .41 .41 .41	.025 .025 .025 .025 .025 .025	.64 .64 .64 .64 .64 .64	.168 4.27	22	72	42	138
---	-------------	--------------------------	---	-----------------	---	---	---	---	--	--	--	--	--------------	----	----	----	-----



For Plenum versions of 8641,
see 88641 or 82641.

Plenum • FEP Insulation • Red FEP Jacket

300V RMS 200°C, Non-conduit	88641	NEC: CMP CEC: CMP FT6	1	Black, Red	100 500 † 1000 †	30.5 152.4 304.8	2.4 6.0 9.0	1.1 2.7 4.1	.006 .006 .006	.15 .15 .15	.014 .014 .014	.36 .36 .36	.106 2.69	31	102	59	194
-----------------------------	--------------	--------------------------------	---	---------------	------------------------	------------------------	-------------------	-------------------	----------------------	-------------------	----------------------	-------------------	--------------	----	-----	----	-----



Plenum • FEP Insulation • Natural Flamarrest® Jacket

300V RMS 60°C, Non-conduit	82641	NEC: CMP CEC: CMP FT6	1	Black, Red	U-1000 †† 1000 ††	U-304.8 304.8	9.0 8.0	4.1 3.6	.006 .006	.15 .15	.014 .014	.36 .36	.106 2.69	31	102	59	194
----------------------------	--------------	--------------------------------	---	---------------	----------------------	------------------	------------	------------	--------------	------------	--------------	------------	--------------	----	-----	----	-----



FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

†Spools and/or UnReel® cartons are one piece, but length may vary ±10% for spools and ±5% for UnReel from length shown.

††Length may vary ±10% for UnReel.

Line Level Analog Audio Cable

Single-Pair Cables



Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

22 AWG Stranded (7x30) TC Conductors • Twisted Pair • Overall Beldfoil® Shield (100% Coverage) • 22 AWG Stranded TC Drain Wire

Polyethylene Insulation • Chrome PVC Jacket

Low-Capacitance UL AWM Style 2092 (300V RMS 60°C)  Z-Fold®	8761	NEC:	1	Black,	U-500	U-152.4	9.0	4.1	.016	.41	.025	.64	.175	4.45	24	79	47	154	
		CM		Clear	500	152.4	9.0	4.1											
		CEC:			U-1000	U-304.8	17.0	7.7											
		CM			1000	304.8	18.0	8.2											
					2000	609.6	36.0	16.3											
					5000	1524.0	90.0	40.9											
					10000††	3048.0	170.0	77.3											
For Plenum versions of 8761, see 88761, 87761 or 82761.																			

For Plenum versions of 8761,
see 88761, 87761 or 82761.

Plenum • FEP Insulation • Red FEP Jacket

300V RMS 200°C 	88761	NEC:	1	Black, Red	100	30.5	2.7	1.2	.006	.15	.014	.36	.119	3.02	35	115	67	220
		CMP			U-500▲	U-152.4	7.5	3.4										
		CEC:			500†	152.4	7.5	3.4										
		CMP FT6			U-1000▲	U-304.8	15.0	6.8										
					1000†	304.8	12.0	5.4										

Plenum • FEP Insulation • Red Fluorocopolymer Jacket

300V RMS 150°C 	87761	NEC:	1	Black, Red	500†	152.4	7.0	3.2	.006	.15	.014	.36	.116	2.95	35	115	67	220
		CMP			1000†	304.8	11.0	5.0										
		CEC:																
		CMP FT6																

Plenum • FEP Insulation • Natural Flamarrest® Jacket

300V RMS 75°C 	82761	NEC:	1	Black, Red	U-500▲	U-152.4	7.0	3.2	.006	.15	.014	.36	.116	2.95	35	115	67	220
		CMP			U-1000■	U-304.8	14.0	6.4										
		CEC:			1000†	304.8	11.0	5.0										
		CMP FT6																

Polyethylene Insulation • Chrome PVC Jacket

Low-Capacitance UL AWM Style 2092 (300V RMS 60°C) 	9461	NEC:	1	Black, Clear	U-500	U-152.4	11.0	5.0	.016	.41	.026	.66	.180	4.57	24	79	47	154
		CM			U-1000	U-304.8	21.0	9.6										
		CEC:																
		CM																

The jacket and shield are bonded so both can be removed on automatic stripping equipment.

22 AWG Stranded (7x30) Tinned Copper Conductors • Twisted Pair • Tinned Copper Spiral Wrapped Shield (85% Coverage)

PVC Insulation • Chrome PVC Jacket

UL AWM Style 2095 (300V RMS 80°C) 	8737	NEC:	1	Black, Red	U-500	U-152.4	10.5	4.8	.015	.38	.025	.64	.180	4.57	40	131	70	230
		CMG			500	152.4	10.0	4.5										
		CEC:			U-1000	U-304.8	20.0	9.1										
		CMG FT4			1000	304.8	20.0	9.1										

FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper

* Capacitance between conductors.

** Capacitance between one conductor and other conductors connected to shield.

† Spools and/or UnReel® cartons are one piece, but length may vary ±10% for spools and ±5% for UnReel from length shown.

†† Length may vary -10% to +20% and may contain 2 pieces. Minimum length of any piece is 1500 ft.

▲ Length may vary ±10% for UnReel® cartons.

■ Length may vary -10% to +5% from length shown.

Line Level Analog Audio Cable

Single-Pair Cables



Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

18 AWG Stranded (16x30) TC Conductors • Twisted Pair • Overall Beldfoil® Shield (100% Coverage) • 20 AWG Stranded TC Drain Wire

Polyethylene Insulation • Chrome PVC Jacket

Low-Capacitance UL AWM Style 2092 (300V RMS 60°C)	9460	NEC:	1	Black, Clear	U-500	U-152.4	18.5	8.4	.019	.48	.030	.76	.230	5.84	30	98	44	144
		CM			U-1000	U-304.8	36.0	16.4										



The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is on the inside of foil shield.

Low-Capacitance UL AWM Style 2092 (300V RMS 60°C)	8760	NEC:	1	Black, Clear	250	76.2	6.8	3.1	.019	.48	.028	.71	.222	5.64	30	98	44	144
		CM			U-500	U-152.4	13.5	6.1										
		CEC:			500	152.4	13.0	5.9										
		CM			U-1000	U-304.8	25.0	11.3										
					1000	304.8	26.0	11.8										
					2000	609.6	50.0	22.7										
					5000	1524.0	135.0	61.4										
					10000	3048.0	260.0	118.2										



Shorting Fold

For Plenum versions of 8760,
see 88760, 87760 or 82760.

18 AWG Stranded (19x30) TC Conductors • Twisted Pair • Overall Beldfoil Shield (100% Coverage) • 20 AWG Stranded TC Drain Wire

Plenum • FEP Insulation • Red FEP Jacket

300V RMS 200°C	88760	NEC:	1	Black, Red	100	30.5	3.7	1.7	.007	.18	.014	.36	.153	3.89	51	167	97	318
		CMP			U-500†	U-152.4	12.5	5.7										
		CEC:			500†	152.4	11.0	5.0										
		CMP FT6			U-1000†	U-304.8	24.0	10.9										
					1000†	304.8	22.0	10.0										



Z-Fold®

Plenum • FEP Insulation • Red Fluorocopolymer Jacket

300V RMS 150°C	87760	NEC:	1	Black, Red	U-500†	U-152.4	12.5	5.7	.007	.18	.014	.36	.150	3.81	51	167	97	318
		CMP			500†	152.4	10.5	4.8										
		CEC:			1000†	304.8	21.0	9.5										
		CMP FT6																



Z-Fold®

Plenum • FEP Insulation • Natural Flamarrest® Jacket

300V RMS 75°C	82760	NEC:	1	Black, Red	U-500†	U-152.4	12.0	5.5	.007	.18	.014	.36	.150	3.81	51	167	97	318
		CMP			U-1000††	U-304.8	22.0	10.0										
		CEC:			1000†	304.8	21.0	9.5										
		CMP FT6																



Z-Fold®

18 AWG Stranded (7x26) Tinned Copper Conductors • Twisted Pair • Tinned Copper Spiral Wrapped Shield (85% Coverage)

PVC Insulation • Chrome PVC Jacket

300V RMS 60°C	8790	NEC:	1	Red, White	U-500	U-152.4	17.5	7.9	.022	.56	.028	.71	.241	6.12	53	174	92	302
		CMG			500	152.4	17.0	7.7										
		CEC:			U-1000	U-304.8	33.0	15.0										
		CMG FT4			1000	304.8	35.0	15.9										



FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

† Spools and/or UnReel® cartons are one piece, but length may vary ±10% for spools and ±5% for UnReel from length shown.

†† Spools and/or UnReel® cartons are one piece, but length may vary -0% to +10%.

Line Level Analog Audio Cable

Single-Pair Cables



Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

16 AWG Stranded (19x29) Tinned Copper Conductors • Twisted Pair • Tinned Copper Spiral Wrapped Shield (85% Coverage)

PVC Insulation • Chrome PVC Jacket

300V RMS 60°C	8780	NEC:	1	Black,	500	152.4	23.5	10.7	.023	.58	.030	.76	.280	7.11	57	187	98	322
		CMG		White	U-1000	U-304.8	44.0	20.0										
		CEC:			1000	304.8	46.0	20.9										
		CMG FT4																



16 AWG Stranded (19x29) TC Conductors • Twisted Pair • Overall Beldfoil® Shield (100% Coverage) • 18 AWG Stranded TC Drain Wire

Polyethylene Insulation • Chrome PVC Jacket

Low-Capacitance	8719	NEC:	1	Black,	U-500	U-152.4	24.0	10.9	.032	.81	.032	.81	.313	7.95	23	75	44	144
UL AWM Style 20253		CM, CL2		Clear	500	152.4	25.5	11.6										
(600V RMS 80°C)		CEC:			U-1000	U-304.8	47.0	21.3										
		CM			1000	304.8	50.0	22.7										
					2000	609.6	100.0	45.5										
					5000	1524.0	245.0	111.4										
					10000†	3048.0	510.0	231.3										



Shorting Fold

14 AWG Stranded (19x27) TC Conductors • Twisted Pair • Overall Beldfoil Shield (100% Coverage) • 16 AWG Stranded TC Drain Wire

Polyethylene Insulation • Chrome PVC Jacket

Low-Capacitance	8720	NEC:	1	Black,	U-500	U-152.4	34.0	15.4	.032	.81	.035	.89	.355	9.02	24	79	47	154
UL AWM Style 20253		CL2		Clear	500	152.4	35.0	15.9										
(600V RMS 80°C)					1000	304.8	71.0	32.3										
					2000	609.6	138.0	62.7										



Z-Fold®

12 AWG Stranded (19x25) TC Conductors • Twisted Pair • Overall Beldfoil Shield (100% Coverage) • 14 AWG Stranded TC Drain Wire

Polyethylene Insulation • Chrome PVC Jacket

Low-Capacitance	8718	NEC	1	Black,	U-500	U-152.4	47.5	21.6	.037	.94	.040	1.02	.400	10.16	25	82	49	161
UL AWM Style 20253		CL2		Clear	500	152.4	50.5	22.9										
(600V RMS 80°C)					1000	304.8	100.0	45.5										
					2000	609.6	198.0	90.0										



Z-Fold®

TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

† Final put-up length may vary -10% to +20% from length shown. May contain 2 pieces. Minimum length of any one piece is 1500 ft.

Analog Multi-Pair Snake Cable

Flexible, Low-Capacitance Cables

Individually Shielded and Jacketed Twisted Pairs



Individually Shielded and Jacketed Pairs

Not NEC Rated

Product Description

22 AWG stranded (7x30) tinned copper conductor. Datalene® insulation. Twisted pairs individual Beldfoil® shield (100% Coverage) and have numbered and color-coded PVC jackets (see Chart 7 in Technical Information Section for colors). Pair jackets and shields are bonded so both strip simultaneously with automatic stripping equipment. Overall Matte Black PVC jacket and nylon rip cord.

Datalene insulation features include a low dielectric constant and a low dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.


Color Code: Red, Black.

Specifications

Nominal OD — Conductor	.030" (.76mm)
Nominal OD — Insulation	.060" (1.52mm)
Inner Pair Jacket OD	.153" (3.89mm)
Nominal DCR	
Conductor	15.0Ω/M' (52.5Ω/km)
Shield (Inner Pair)	10.6Ω/M' (34.8Ω/km)
Voltage Rating	150V RMS
Temperature Rating	60°C
Nominal Impedance	70Ω
Nominal Velocity of Propagation	78%
Nominal Capacitance	
Between Conductors	19 pF/Ft. (62 pF/m)
Between Conductor/Shield*	35 pF/Ft. (115 pF/m)

DCR = DC Resistance

*Capacitance between one conductor and other conductors connected to shield.



Part No.	No. of Pairs	Standard Lengths		Standard Unit Weight		Nominal OD	
		Ft.	m	Lbs.	kg	Inch	mm

Flexible, Low-Capacitance Twisted Pairs

22 AWG							
1217B	4	500 1000	152.4 304.8	53.0 107.0	24.0 48.5	.458	11.63
1218B	6	500 1000	152.4 304.8	79.5 152.0	36.1 68.9	.578	14.68
1219B	9	500 1000	152.4 304.8	115.5 234.0	52.4 106.1	.700	17.78
1220B	12	500 1000	152.4 304.8	141.0 286.0	70.0 129.7	.760	19.30
1222B	16	500 1000	152.4 304.8	188.0 384.0	85.3 174.2	.852	21.64
1225B	20	500 1000	152.4 304.8	240.0 471.0	108.8 213.6	.960	24.38
1427B	24	1000	304.8	588.0	266.7	1.088	27.64
1221B	28	500 1000	152.4 304.8	335.0 676.0	152.0 306.6	1.140	28.96
1226B	32	500 1000	152.4 304.8	369.0 744.0	167.4 337.5	1.183	30.05
1428B†	52	1000	304.8	1141.0	517.5	1.496	38.00

†1428B available by special order. Please contact Belden for lead time.

Speaker Wire and Cable

Low-Capacitance Oxygen-Free, High-Conductivity (OFHC) Speaker Cable
Twisted Jacketed Construction



Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance*	
				Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	pF/Ft.	pF/m

Low Cap • 16 AWG Stranded (65x34) Oxygen-free High-Conductivity Bare Copper Conductors • Conductors Cabled • Unshielded

Polyolefin Insulation • PVC Jacket (Available in Black, White, Gray, Blue or Green)



1307A new	NEC: CMR, CL3R CEC: CMG FT4	2	U-500 1000†	U-152.4 304.8	15.0 29.0	6.8 13.2	.013 .32	.022 .56	.210 5.33	19.9	65.3
----------------------------	--------------------------------------	---	----------------	------------------	--------------	-------------	-------------	-------------	--------------	------	------

Suitable for Direct Burial applications. White and Black jackets are Sunlight-resistant.



1308A new	NEC: CMR, CL3R CEC: CMG FT4	4	U-500 1000†	U-152.4 304.8	26.5 54.0	12.0 24.5	.013 .32	.026 .66	.270 6.86	19.9	65.3
----------------------------	--------------------------------------	---	----------------	------------------	--------------	--------------	-------------	-------------	--------------	------	------

Suitable for Direct Burial applications. White and Black jackets are Sunlight-resistant.

Low Cap • 14 AWG Stranded (105x34) Oxygen-free High-Conductivity Bare Copper Conductors • Conductors Cabled • Unshielded

Polyolefin Insulation • PVC Jacket (Available in Black, White, Gray, Blue or Green)

For Audio Use Only



1309A new	NEC: CMR, CL3R CEC: CMG FT4	2	U-500 1000†	U-152.4 304.8	22.5 46.0	10.2 20.9	.016 .39	.027 .69	.264 6.71	20.5	67.3
----------------------------	--------------------------------------	---	----------------	------------------	--------------	--------------	-------------	-------------	--------------	------	------

Suitable for Direct Burial applications. White and Black jackets are Sunlight-resistant.



1310A new	NEC: CMR, CL3R CEC: CMG FT4	4	U-500 1000†	U-152.4 304.8	41.5 84.0	18.8 38.1	.016 .39	.033 .94	.319 8.10	20.5	67.3
----------------------------	--------------------------------------	---	----------------	------------------	--------------	--------------	-------------	-------------	--------------	------	------

Suitable for Direct Burial applications. White and Black jackets are Sunlight-resistant.

Low Cap • 12 AWG Stranded (168x34) Oxygen-free High-Conductivity Bare Copper Conductors • Conductors Cabled • Unshielded

Polyolefin Insulation • PVC Jacket (Available in Black, White or Gray)

For Audio Use Only



1311A new	NEC: CMR, CL3R CEC: CMG FT4	2	U-500 500 1000†	U-152.4 152.4 304.8	36.5 36.5 74.0	16.6 16.6 33.6	.018 .46	.036 .91	.352 8.94	22.3	73.2
----------------------------	--------------------------------------	---	-----------------------	---------------------------	----------------------	----------------------	-------------	-------------	--------------	------	------

Suitable for Direct Burial applications. White and Black jackets are Sunlight-resistant.



1312A new	NEC: CMR, CL3R CEC: CMG FT4	4	500 1000†	152.4 304.8	66.5 132.0	30.2 59.9	.018 .46	.043 1.09	.423 10.74	22.3	73.2
----------------------------	--------------------------------------	---	--------------	----------------	---------------	--------------	-------------	--------------	---------------	------	------

Suitable for Direct Burial applications. White and Black jackets are Sunlight-resistant.

Low Cap • 10 AWG Stranded (259x34) Oxygen-free High-Conductivity Bare Copper Conductors • Conductors Cabled

Polyolefin Insulation • PVC Jacket (Available in Black, White or Gray)

For Audio Use Only



1313A new	NEC: CMR, CL3R CEC: CMG FT4	2	500 1000†	152.4 304.8	55.0 109.0	25.0 49.5	.019 .48	.044 1.12	.428 10.87	23.2	76.1
----------------------------	--------------------------------------	---	--------------	----------------	---------------	--------------	-------------	--------------	---------------	------	------

Suitable for Direct Burial applications. White and Black jackets are Sunlight-resistant.

OFHC = Oxygen-Free High-Conductivity

*Capacitance between conductors.

†1000 ft. put-ups not available in Blue or Green.

Color Code Chart

Cond.	Color
1	Black
2	Red
3	White
4	Green

Special Application Audio, Communication and Instrumentation Cable

Audio Connecting Cables and Dual Channel Audio Cables



Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Cond.	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance	
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	pF/Ft.*	pF/m*

25 AWG Stranded (7x33) Conductor • (3) TC, (4) TCCS • Double Beldfoil® Shield (100% Coverage) • 26 AWG Stranded TC Drain Wire

FPE Insulation • Chrome PVC Jacket

Miniature 80°C	8417	—	1	—	250	76.2	3.3	1.5	.020	.51	.026	.66	.140	3.56	29	95
-------------------	------	---	---	---	-----	------	-----	-----	------	-----	------	-----	------	------	----	----



25 AWG Stranded (7x33) Conductor • (3) TC, (4) TCCS • Tinned Copper Spiral Wrapped Shield (86% Coverage)

FPE Insulation • Chrome PVC Jacket


Low-Capacitance 80°C	8421	—	1	—	250	76.2	4.5	2.0	.051	1.30	.023	.58	.180	4.57	16	53
-------------------------	------	---	---	---	-----	------	-----	-----	------	------	------	-----	------	------	----	----



24 AWG Uni-strand (7x32) Tinned Copper Conductor • Beldfoil Shield (100% Coverage)

Flame-retardant Polypropylene Insulation • Black PVC Jacket

UL AWM Style 1770 (300V 80°C) VW-1	9264	—	1	—	1000	304.8	14.0	6.4	.027	.69	.020	.51	.122 x .146	3.10 x 3.71	30	99
--	------	---	---	---	------	-------	------	-----	------	-----	------	-----	-------------------	-------------------	----	----



Nominal impedance: 50 ohms.
Tear-drop, machine strippable coaxial cable.

Dual Channel • 30 AWG Stranded (7x38) TCCS Conductors • Individual Tinned Copper Spiral Wrapped Shield (85% Coverage)

FPE Insulation • Black PVC Jacket • Polarity Ribbed

Low-Capacitance 70°C	9454	—	2	—	100	30.5	3.5	1.6	.049	1.24	.020	.51	.160 x .320	4.06 x 8.13	12 each channel	39
-------------------------	------	---	---	---	-----	------	-----	-----	------	------	------	-----	-------------------	-------------------	-----------------------	----




Stereo connecting cable

Dual Channel • 25 AWG Stranded (7x38) Conductors • (3) TC, (4) TCCS • Individual TC Spiral Wrapped Shield (90% Coverage)

Polyethylene Insulation • Gray PVC Jacket • Polarity Rib on Red Conductor

80°C	8416	—	2	—	250	76.2	4.8	2.2	.018	.46	.020	.51	.106 x .213	2.69 x 5.41	36 each channel	118
------	------	---	---	---	-----	------	-----	-----	------	-----	------	-----	-------------------	-------------------	-----------------------	-----



For use with head sets, stereo and language labs.

FPE = Foam Polyethylene • TC = Tinned Copper • TCCS = Tinned Copper-covered Steel

*Capacitance between conductors.