

Overall Beldfoil® Shield

Audio, Control and Instrumentation Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Insulation Thickness		Jacket Thickness		Nominal OD		Nominal Capacitance			
					Ft.	m	Lbs.	kg	Inch	mm	Inch	mm	Inch	mm	* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m

22 AWG Stranded (7x30) TC Conductors • Twisted Pair • Overall Beldfoil Shield (100% Coverage) • 22 AWG Stranded TC Drain Wire (continued)

Polypropylene Insulation • Paper Wrap • Gray or Black PVC Jacket																		
300V RMS 75°C 	8451	NEC:	1	Black, Red	100*	30.5	2.3	1.1	.008	.20	.020	.51	.138	3.51	34	112	67	220
		CMR			U-500	U-152.4	8.5	3.8										
		CEC:			500	152.4	8.0	3.6										
		CMG			U-1000	U-304.8	16.0	7.3										
					1000	304.8	16.0	7.3										

*100 ft. put-up available in Black only.
Unique paper separator facilitates jacket stripping.

Polypropylene Insulation • PVC Jacket (Available in Black, Gray, Brown, Red, Orange, Yellow, Green, Blue, Purple or White)																		
300V RMS 75°C 	9451	NEC:	1	Black, Red	U-500*	U-152.4	8.5	3.9	.008	.20	.020	.51	.135	3.43	35	115	67	220
		CMR			500*	152.4	8.0	3.6										
		CEC:			T-1000*	T-304.8	18.0	8.2										
		CMG FT4			U-1000	U-304.8	15.0	6.8										
					5000	1524.0	75.0	34.0										


*U-500 ft., 500 ft. and T-1000 ft. put-ups available in Gray only.
The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield.

Polypropylene Insulation • Black Low-Smoke, Zero-Halogen Jacket																		
300V RMS 105°C 	9451SB new	NEC:	1	Black, Red	1000	304.8	20.0	9.1	.008	.20	.032	.81	.160	4.06	35	115	67	220
		CMG-LS																
		CEC:																
		CMG-LS FT4																
		Limited Smoke																

The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield.

Polyolefin Insulation • PVC Jacket in Zip-Cord Construction (Red & Green, Red & Black, Red & Purple or Red & Gray)																		
300V 105°C 	9451D	NEC:	2	Black, Red	U-1000	U-304.8	29.0	13.2	.008	.20	.020	.51	.135	3.43	34	112	67	220
		CMR			2000*	620.8	62.0	28.1					x	x				
		CEC:																
		CMR FT4																

*2000 ft. put-up available in Red & Green only.
The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield.

Plenum • FEP Insulation • White Flamarrest® Jacket in Zip-Cord Construction																		
300V RMS 60°C 	9451DP new	NEC:	2	Black & Red, Black & White	1000	304.8	24.0	10.9	.007	.18	.017	.43	.127	3.23	35	115	67	220
		CMP											x	x				
		CEC:																
		CMP FT6																

The jacket and shield are bonded so both can be removed on automatic stripping equipment. Drain wire is inside foil shield.

22 AWG Stranded (7x30) TC Conductors • Twisted Pairs • Overall Beldfoil Shield (100% Coverage) • 24 AWG Stranded TC Drain Wire

Polypropylene Insulation • PVC Jacket (Available in Brown, Red, Orange, Yellow, Green, Blue, Purple, Gray, White or Black)																		
300V RMS 	1266A	NEC:	1	Black, Red	U-1000	U-304.8	15.0	6.8	.010	.25	.020	.51	.143	3.63	30	99	54	177
		CM			1000†	304.8	15.0	6.8										
		CEC:																
		CM																

†1000 ft. put-up available in Black only.
Unique design features lower capacitance and greater flexibility than standard audio pair constructions.

PVC Insulation • PVC Jacket (Available in Brown, Red, Orange, Yellow, Green, Blue, Purple, Gray, White or Black)																		
300V 90°C 	1503A	NEC:	1	Black, Red	U-1000	U-304.8	16.0	7.3	.010	.25	.020	.51	.142	3.61	53	174	97	318
		CM																
		CEC:																
		CM																

TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Individually Shielded


Audio, Control and Instrumentation Cables
Plenum-Rated and Non-Plenum

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ ft.	* pF/ m	** pF/ ft.	** pF/ m

22 AWG Stranded (7x30) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil® (100% Coverage) • 22 AWG Stranded TC Drain Wire

Semi-rigid PVC Insulation • Pale Fawn Beige PVC Jacket (Shielded Pairs Parallel under Jacket)

UL AWM Style 2464 (300V 80°C)	9406	NEC:	2	Black & White,	100	30.5	3.8	1.7	15.0Ω/M'	13.0Ω/M'	.173	4.39	50	60%	50	164	95	312
		CMG			U-500	U-152.4	16.5	7.5	49.2Ω/km	42.7Ω/km	x	x						
		CEC:			500	152.4	17.0	7.7			.280	7.11						
		CMG FT4			U-1000	U-304.8	32.0	14.5										
					1000	304.8	33.0	15.0										




Z-Fold®

22 AWG Stranded (7x30) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil (100% Coverage) • 24 AWG Stranded TC Drain Wire

Polypropylene Insulation • Chrome PVC Jacket (Pairs Cabled on Common Axis to Reduce Diameter)

300V RMS 60°C	8723	NEC:	2	Red & Black,	100	30.5	2.3	1.0	15.0Ω/M'	16.6Ω/M'	.160	4.06	45	66%	35	115	62	203
		CM			U-500	U-152.4	10.5	4.8	49.2Ω/km	54.5Ω/km								
		CEC:			500	152.4	10.0	4.5										
		CM			U-1000	U-304.8	20.0	9.1										
					1000	304.8	20.0	9.1										
					1640	499.9	32.8	14.9										
					U-2000	U-609.6	38.0	17.2										
					2000	609.6	40.0	18.2										
					3280	999.7	65.6	29.8										
					5000	1524.0	95.0	43.2										
					10000	3048.0	200.0	90.9										




Z-Fold®

For Plenum versions of 8723,
see 88723, 87723 or 82723.

Polypropylene Insulation • Black Low-Smoke, Zero-Halogen Jacket (Pairs Cabled on Common Axis to Reduce Diameter)


300V RMS 60°C	8723SB	NEC:	2	Red & Black,	1000	304.8	26.0	11.8	14.7Ω/M'	15.0Ω/M'	.196	4.98	45	66%	35	115	62	203
		CMG-LS							48.2Ω/km	49.2Ω/km								
		CEC:																
		CMG-LS FT4 Limited Smoke																



Z-Fold®

Plenum • FEP Insulation • Natural Flamarrest® Jacket (Pairs Cabled on Common Axis to Reduce Diameter)


300V RMS, Non-conduit	82723	NEC:	2	Red & Black,	U-500†	U-152.4	10.5	4.8	14.7Ω/M'	16.6Ω/M'	.153	3.89	36	62%	43	141	75	246
		CMP			U-1000	U-304.8	20.0	9.1	48.2Ω/km	54.5Ω/km								
		CEC:			1000†	304.8	19.0	8.6										
		CMP FT6			U-2000†	U-609.6	40.0	18.1										



Z-Fold®

Plenum • FEP Insulation • Red FEP Jacket (Pairs Cabled on Common Axis to Reduce Diameter)


300V RMS, Non-conduit	88723	NEC:	2	Red & Black,	100†	30.5	3.4	1.5	16.0Ω/M'	14.7Ω/M'	.148	3.76	40	69%	35	115	67	220
		CMP			500†	152.4	11.0	5.0	52.5Ω/km	48.2Ω/km								
		CEC:			1000†	304.8	19.0	8.6										
		CMP FT6																



Z-Fold®

Plenum • FEP Insulation • Red Fluorocopolymer Jacket (Pairs Cabled on Common Axis to Reduce Diameter)

300V RMS, Non-conduit	87723	NEC:	2	Red & Black,	500†	152.4	11.0	5.0	14.7Ω/M'	15.0Ω/M'	.148	3.76	40	69%	35	115	67	220
		CMP			1000†	304.8	20.0	9.1	48.2Ω/km	49.2Ω/km								
		CEC:																
		CMP FT6																



Z-Fold®

DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper


*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.


† Spools and/or UnReel® cartons are one piece, but length may vary ±10% for spools and ±5% for UnReel from length show.

Individually Shielded

Audio, Control and Instrumentation Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
22 AWG Stranded (7x30) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil® (100% Coverage) • 22 AWG Stranded TC Drain Wire																		
Polypropylene Insulation • Chrome PVC Jacket																		
 Z-Fold®	8777	NEC:	3	See	100	30.5	4.7	2.1	15.0Ω/M'	10.6Ω/M'	.273	6.93	50	66%	30	98	55	180
		CM		Chart 3	250	76.2	10.0	4.5	49.2Ω/km	34.8Ω/km								
		CEC:		(Tech Info	U-500	U-152.4	21.0	9.5										
		CM		Section)	500	152.4	20.0	9.1										
					U-1000	U-304.8	41.0	18.6										
					1000	304.8	44.0	20.0										
					1640	499.9	70.5	32.0										
					3280	999.7	141.0	64.0										
					5000	1524.0	215.0	97.6										
					10000 ††	3048.0	460.0	208.8										
For Plenum versions of 8777, see 88777, 87777 or 82777.																		
	8778	NEC:	6	See	100	30.5	8.4	3.8	15.0Ω/M'	10.6Ω/M'	.362	9.19	50	66%	30	98	55	180
		CM		Chart 3	250	76.2	19.0	8.6	49.2Ω/km	34.8Ω/km								
		CEC:		(Tech Info	500	152.4	43.0	19.5										
		CM		Section)	1000	304.8	83.0	37.7										
	8774	NEC:	9	See	100	30.5	11.5	5.2	15.0Ω/M'	10.6Ω/M'	.417	10.59	50	66%	30	98	55	180
		CM		Chart 3	250	76.2	29.5	13.4	49.2Ω/km	34.8Ω/km								
		CEC:		(Tech Info	500	152.4	57.5	26.1										
		CM		Section)	1000	304.8	113.0	51.3										
	8775	NEC:	11	See	100	30.5	12.1	5.5	15.0Ω/M'	10.6Ω/M'	.464	11.79	50	66%	30	98	55	180
		CM		Chart 3	500	152.4	65.5	29.7	49.2Ω/km	34.8Ω/km								
		CEC:		(Tech Info	1000	304.8	130.0	59.0										
		CM		Section)														
	9768	NEC:	12	See	100	30.5	13.2	6.0	15.0Ω/M'	10.6Ω/M'	.464	11.79	50	66%	30	98	55	180
		CM		Chart 3	250	76.2	36.5	16.5	49.2Ω/km	34.8Ω/km								
		CEC:		(Tech Info	500	152.4	73.5	33.4										
		CM		Section)	1000	304.8	143.0	65.0										
	8776	NEC:	15	See	100	30.5	17.8	8.1	15.0Ω/M'	10.6Ω/M'	.548	13.92	50	66%	30	98	55	180
		CM		Chart 3	250	76.2	49.5	22.5	49.2Ω/km	34.8Ω/km								
		CEC:		(Tech Info	500	152.4	98.0	44.5										
		CM		Section)	1000	304.8	197.0	89.5										
	9769	NEC:	17	See	100	30.5	20.0	9.1	15.0Ω/M'	10.6Ω/M'	.577	14.66	50	66%	30	98	55	180
		CM		Chart 3	500	152.4	109.0	49.5	49.2Ω/km	34.8Ω/km								
		CEC:		(Tech Info	1000	304.8	215.0	97.7										
		CM		Section)														
	8769	NEC:	19	See	100	30.5	22.9	10.4	15.0Ω/M'	10.6Ω/M'	.603	15.32	50	66%	30	98	55	180
		CM		Chart 3	500	152.4	123.0	55.8	49.2Ω/km	34.8Ω/km								
		CEC:		(Tech Info	1000	304.8	244.0	110.8										
		CM		Section)														
	8773	NEC:	27	See	100	30.5	33.9	15.4	15.0Ω/M'	10.6Ω/M'	.709	18.00	50	66%	30	98	55	180
		CM		Chart 3	250 †	76.2	83.8	38.0	49.2Ω/km	34.8Ω/km								
		CEC:		(Tech Info	500	152.4	163.0	74.0										
		CM		Section)	1000	304.8	341.0	154.8										
	9767	NEC:	37	See	500 †	152.4	224.0	101.8	15.0Ω/M'	10.6Ω/M'	.800	20.32	50	66%	30	98	55	180
		CM		Chart 3	1000 †	304.8	481.0	218.6	49.2Ω/km	34.8Ω/km								
		CEC:		(Tech Info														
		CM		Section)														

Polypropylene Insulation • Black Low-Smoke, Zero-Halogen Jacket

U300V RMS, Non-conduit  Z-Fold®	8777SB new	NEC:	3	See	U-500†	U-152.4	19.5	8.9	15.0Ω/M'	10.6Ω/M'	.273	6.93	50	66%	30	98	55	180
		CMG-LS		Chart 3	U-1000	U-304.8	38.0	17.3	49.2Ω/km	34.8Ω/km								
		CEC:		(Tech Info	1000†	304.8	39.0	17.7										
		CMG-LS FT4		Section)														
		Limited Smoke																

DCR = DC Resistance • TC = Tinned Copper

See Attenuation, Rise Time and Bit Rate Data for this series on page 5.39.

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

† Spools are one piece, but length may vary -0 to +20% from length shown.

†† Final put-up length may vary -10% to +20% from length shown. May contain 2 pieces. Minimum length of any one piece is 1500 ft.

BELDEN

For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com

Belden114@CableCon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr