


Plenum-Rated

Overall Beldfoil® Shield

Low-Capacitance Computer Cables for EIA RS-232 and EIA RS-422 Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) Tinned Copper Conductors • Twisted Pairs • Overall Beldfoil Shield (100% Coverage) • 24 AWG Stranded TC Drain Wire																		
Plenum • Foam FEP Insulation • Gray Fluorocopolymer Jacket																		
	300V RMS	88102	NEC: CMP CEC: CMP FT6	2 (Tech Info Section)	See Chart 5	500 1000	152.4 304.8	10.0 20.0	4.5 9.1	24.0Ω/M' 78.7Ω/km	15.5Ω/M' 50.9Ω/km	.203 5.16	100	78%	12.95	42.5	23.3	76.4
		88103	NEC: CMP CEC: CMP FT6	3 (Tech Info Section)	See Chart 5	500 1000	152.4 304.8	13.5 31.0	6.1 14.1	24.0Ω/M' 78.7Ω/km	15.5Ω/M' 50.9Ω/km	.239 6.07	100	78%	12.95	42.5	23.3	76.4
		88104	NEC: CMP CEC: CMP FT6	4 (Tech Info Section)	See Chart 5	500 1000	152.4 304.8	17.0 38.0	7.7 17.3	24.0Ω/M' 78.7Ω/km	14.0Ω/M' 45.9Ω/km	.259 6.58	100	78%	12.95	42.5	23.3	76.4
		88105	NEC: CMP CEC: CMP FT6	5 (Tech Info Section)	See Chart 5	500 1000	152.4 304.8	23.5 44.0	10.7 20.0	24.0Ω/M' 78.7Ω/km	14.0Ω/M' 45.9Ω/km	.267 6.78	100	78%	12.95	42.5	23.3	76.4
		88106	NEC: CMP CEC: CMP FT6	6 (Tech Info Section)	See Chart 5	500 1000	152.4 304.8	26.5 50.0	12.0 22.7	24.0Ω/M' 78.7Ω/km	14.0Ω/M' 45.9Ω/km	.293 7.44	100	78%	12.95	42.5	23.3	76.4
		88107	NEC: CMP CEC: CMP FT6	7.5 (7 pairs + 1 single) (Tech Info Section)	See Chart 5	500 1000	152.4 304.8	31.0 59.0	14.1 26.8	24.0Ω/M' 78.7Ω/km	14.0Ω/M' 45.9Ω/km	.293 7.44	100	78%	12.95	42.5	23.3	76.4
		88109	NEC: CMP CEC: CMP FT6	9 (Tech Info Section)	See Chart 5	500 1000	152.4 304.8	36.5 74.0	16.6 33.6	24.0Ω/M' 78.7Ω/km	13.0Ω/M' 42.7Ω/km	.352 8.94	100	78%	12.95	42.5	23.3	76.4
		88112	NEC: CMP CEC: CMP FT6	12.5 (12 pairs + 1 single) (Tech Info Section)	See Chart 5	500 1000	152.4 304.8	48.0 97.0	21.8 44.1	24.0Ω/M' 78.7Ω/km	11.8Ω/M' 38.7Ω/km	.397 10.08	100	78%	12.95	42.5	23.3	76.4
		88118	NEC: CMP CEC: CMP FT6	18.5 (18 pairs + 1 single) (Tech Info Section)	See Chart 5	500 1000	152.4 304.8	71.0 148.0	32.2 67.3	24.0Ω/M' 78.7Ω/km	11.0Ω/M' 36.1Ω/km	.482 12.24	100	78%	12.95	42.5	23.3	76.4
		88125	NEC: CMP CEC: CMP FT6	25 (Tech Info Section)	See Chart 5	500 [†] 1000 [†]	152.4 304.8	98.0 195.0	44.5 88.6	24.0Ω/M' 78.7Ω/km	9.6Ω/M' 31.5Ω/km	.581 14.76	100	78%	12.95	42.5	23.3	76.4

DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

† Spools are one piece, but length may vary ±10% from length shown.

Plenum-Rated

Overall Foil/Braid Shield

Low-Capacitance Computer and Computer P.O.S. Cables

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ ft.	* pF/ m	** pF/ ft.	** pF/ m

Low Cap 24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Overall Beldfoil® (100% Coverage) + TC Braid Shield (90% Cov.) • Drain Wire

Plenum • Foam FEP Insulation • Natural Flamarrest® Jacket

	300V RMS	82841	NEC: CMP CEC: CMP FT6	1	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	13.0 26.0	6.0 11.8	24.0Ω/M' 78.7Ω/km	3.1Ω/M' 10.2Ω/km	.204 5.18	120	76%	12	39.4	22	72.2
--	----------	--------------	--------------------------------	---	--	-------------	----------------	--------------	-------------	----------------------	---------------------	--------------	-----	-----	----	------	----	------

	300V RMS	82842	NEC: CMP CEC: CMP FT6	2	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	19.0 42.0	8.6 19.1	24.0Ω/M' 78.7Ω/km	2.4Ω/M' 7.9Ω/km	.273 6.93	120	76%	12	39.4	22	72.2
--	----------	--------------	--------------------------------	---	--	-------------	----------------	--------------	-------------	----------------------	--------------------	--------------	-----	-----	----	------	----	------

Plenum • Foam FEP Insulation • Red FEP Jacket

	300V RMS	89841	NEC: CMP CEC: CMP FT6	1	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	13.5 27.0	6.1 12.3	24.0Ω/M' 78.7Ω/km	3.1Ω/M' 10.2Ω/km	.202 5.13	120	76%	12	39.4	22	72.2
--	----------	--------------	--------------------------------	---	--	-------------	----------------	--------------	-------------	----------------------	---------------------	--------------	-----	-----	----	------	----	------

	300V RMS	89842 new	NEC: CMP CEC: CMP FT6	2	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	25.5 49.0	11.6 22.2	24.0Ω/M' 78.7Ω/km	3.1Ω/M' 10.2Ω/km	.305 7.75	120	76%	12	39.4	22	72.2
--	----------	------------------------------------	--------------------------------	---	--	-------------	----------------	--------------	--------------	----------------------	---------------------	--------------	-----	-----	----	------	----	------

22 AWG Solid TC Conductors • Twisted Pairs • Overall Beldfoil (100% Coverage) + TC Braid Shield (90% Coverage) • 22 AWG TC Drain Wire

Plenum • Solid FEP Insulation • Black FEP Jacket

	300V RMS	1269A	NEC: MPP, CMP CEC: MPP, CMP FT6	2	Red & Blue, Black & Yellow	1000	304.8	48.0	21.8	16.5Ω/M' 54.1Ω/km	2.1Ω/M' 6.9Ω/km	.240 6.10	100	69.5%	15.5	50.9	27	88.6
--	----------	--------------	---	---	---	------	-------	------	------	----------------------	--------------------	--------------	-----	-------	------	------	----	------

22 AWG Solid TC Conductors • Twisted Pairs • Overall Beldfoil (100% Coverage) + TC Braid Shield (55% Cov.) + Polyester Tape • 22 AWG Drain Wire

Plenum • Solid FEP Insulation • Black FEP Jacket

	300V RMS	89855	NEC: MPP, CMP CEC: MPP, CMP FT6	2	1 Pair: Red & Blue 1 Pair: Black & Yellow	500 1000	152.4 304.8	22.5 42.0	10.2 19.1	16.5Ω/M' 54.1Ω/km	4.9Ω/M' 16.1Ω/km	.272 6.91	100	69.5%	15.5	50.9	27	88.6
--	----------	--------------	---	---	---	-------------	----------------	--------------	--------------	----------------------	---------------------	--------------	-----	-------	------	------	----	------

22 AWG Solid BC Conductors • Twisted Pairs • Overall Beldfoil (100% Coverage) + TC Braid Shield (55% Coverage) • 22 AWG Solid TC Drain Wire

Plenum • Solid FEP Insulation • Black FEP Jacket

	300V RMS	89696	NEC: MPP, CMP CEC: MPP, CMP FT6	2	1 Pair: Blue & White with Blue Stripes 1 Pair: Orange & White with Orange Stripes	500 1000	152.4 304.8	25.0 46.0	11.4 20.9	16.5Ω/M' 54.1Ω/km	4.2Ω/M' 13.8Ω/km	.262 6.65	100	69.5%	15.5	50.9	27	88.6
--	----------	--------------	---	---	--	-------------	----------------	--------------	--------------	----------------------	---------------------	--------------	-----	-------	------	------	----	------

BC = Bare Copper • DCR = DC Resistance • TC = Tinned Copper


*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.

Plenum-Rated

Individually Shielded Pairs

Low-Capacitance Computer Cables for EIA RS-232, EIA RS-422, and Digital Audio Applications

Description	Part No.	UL NEC/ C(UL) CEC Type	No. of Pairs	Color Code	Standard Lengths		Standard Unit Weight		Nom. DCR		Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nom. Capacitance			
					Ft.	m	Lbs.	kg	Cond.	Shield	Inch	mm			* pF/ Ft.	* pF/ m	** pF/ Ft.	** pF/ m
24 AWG Stranded (7x32) TC Conductors • Twisted Pairs • Individually Shielded w/Beldfoil® (100% Coverage) • 24 AWG Stranded TC Drain Wire																		
Plenum • Foam FEP Insulation • Gray Fluorocopolymer Jacket																		
	89729	NEC: CMP CEC: CMP FT6	2	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	17.0 31.0	7.7 14.1	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.261 6.63	100	76%	13.5	44	22.5	73.8	
	89730	NEC: CMP CEC: CMP FT6	3	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	21.5 40.0	9.8 18.2	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.278 7.06	100	76%	13.5	44	22.5	73.8	
	89728	NEC: CMP CEC: CMP FT6	4	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	26.5 50.0	12.0 22.7	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.307 7.80	100	76%	13.5	44	22.5	73.8	
	89705	NEC: CMP CEC: CMP FT6	5	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	30.5 62.0	13.9 28.2	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.333 8.50	100	76%	13.5	44	22.5	73.8	
	89731	NEC: CMP CEC: CMP FT6	6	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	35.0 71.0	15.9 32.3	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.361 9.17	100	76%	13.5	44	22.5	73.8	
	89757	NEC: CMP CEC: CMP FT6	7	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	39.5 80.0	18.0 36.4	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.361 9.17	100	76%	13.5	44	22.5	73.8	
	89732	NEC: CMP CEC: CMP FT6	9	See Chart 5 (Tech Info Section)	1000	304.8	108.0	49.2	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.433 10.90	100	76%	13.5	44	22.5	73.8	
	89734	NEC: CMP CEC: CMP FT6	12	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	71.0 140.0	32.3 63.6	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.498 12.65	100	76%	13.5	44	22.5	73.8	
	89758	NEC: CMP CEC: CMP FT6	18	See Chart 5 (Tech Info Section)	500 1000	152.4 304.8	100.5 204.0	45.7 92.7	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.616 15.65	100	76%	13.5	44	22.5	73.8	
Plenum • Foam FEP Insulation • Natural Flamarrest® Jacket																		
	82729	NEC: CMP CEC: CMP FT6	2	See Chart 5 (Tech Info Section)	U-1000 1000	U-304.8 304.8	26.0 28.0	11.8 12.7	23.3Ω/M' 76.4Ω/km	14.4Ω/M' 47.2Ω/km	.255 6.48	100	76%	13.5	44	22.5	73.8	

DCR = DC Resistance • TC = Tinned Copper

*Capacitance between conductors.

**Capacitance between one conductor and other conductors connected to shield.