

Broadband Coax

CATV Cables

Series 6

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

Series 6 • 18 AWG Solid .040" Bare Copper-covered Steel Conductor • Duobond® IV Quad Shield (60% and 40% Coverage)

Gas-injected Foam Polyethylene Insulation • Polyethylene Jacket with CoreGuard® (Black or Orange)

Burial 80°C	1190A	—	1000	304.8	31.0	14.1	18 AWG (solid) .040"	.180	4.57	Duobond IV* 60% + 40% Aluminum Braids	.298	7.57	75	83%	16.2	53.1	See Chart on page 6.92		
							28.0Ω/M' 91.9Ω/km			4.8Ω/M' 15.7Ω/km									



CoreGuard®

Series 6 • 18 AWG Solid .040" Bare Copper-covered Steel Conductor • Duofoil® (100% Coverage) + TC Braid Shield (95% Coverage)

Plenum • Foam FEP Insulation • Black FEP Jacket

200°C	89120	NEC:	500	152.4	21.5	9.8	18 AWG (solid) .040"	.170	4.32	Duofoil 95% TC	.234	5.94	75	82%	16.5	54.1	1	.3	1.0
		CATVP	1000	304.8	46.0	20.9											10	.7	2.2
		CMP															50	1.6	5.3
		CEC:															100	2.2	7.2
		CMP FT6															200	3.0	9.8
																	400	4.6	15.1
																	700	6.6	21.7
																	900	7.7	25.3
																	1000	8.2	26.9



Plenum • Foam FEP Insulation • Black Fluorocopolymer Jacket

150°C	87120	NEC:	500	152.4	20.5	9.3	18 AWG (solid) .040"	.170	4.32	Duofoil 95% TC	.234	5.94	75	82%	16.5	54.1	1	.3	1.0
		CATVP	1000	304.8	45.0	20.4											10	.7	2.2
		CMP															50	1.6	5.3
		CEC:															100	2.2	7.2
		CMP FT6, CXC FT4															200	3.0	9.8
																	400	4.6	15.1
																	700	6.6	21.7
																	900	7.7	25.3
																	1000	8.2	26.9



Plenum • Foam FEP Insulation • Natural Flamarrest® Jacket

75°C	82120	NEC:	1000	304.8	44.0	20.0	18 AWG (solid) .040"	.170	4.32	Duofoil 95% TC	.234	5.94	75	82%	16.5	54.1	1	.3	1.0
		CATVP															10	.7	2.2
		CMP															50	1.6	5.3
		CEC:															100	2.2	7.2
		CMP FT6															200	3.0	9.8
																	400	4.6	15.1
																	700	6.6	21.7
																	900	7.7	25.3
																	1000	8.2	26.9



Series 6 • 18 AWG Solid .040" BCCS Conductor • Duofoil (100% Coverage) + TC Braid Shield (60% and 40% Coverage)

Plenum • Foam FEP Insulation • Snow Beige FEP Jacket

200°C	1152A	NEC:	500	152.4	27.5	12.5	18 AWG (solid) .040"	.170	4.32	(2) Duofoil Shields + (2) TC Braids	.273	6.93	75	82%	16.5	54.1	1	.3	1.0
		CATVP	1000	304.8	53.0	24.1											10	.7	2.2
		CMP															50	1.6	5.3
		CEC:															100	2.2	7.2
		CMP FT6															200	3.0	9.8
																	400	4.6	15.1
																	700	6.6	21.7
																	900	7.7	25.3
																	1000	8.2	26.9

BCCS = Bare Copper-covered Steel • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**.

*Duobond IV = Bonded Duofoil (100% coverage) + aluminum braid (67% coverage) + Duofoil (100% coverage) + aluminum braid (46% coverage).

Broadband Coax

CATV Cables


Series 11

Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

Series 11 • 14 AWG Solid .064" Bare Copper-covered Steel Conductor • Duobond Plus® + Aluminum Braid Shield (77% Coverage)**Gas-injected Foam Polyethylene Insulation • Black PVC Jacket**

80°C	9064	NEC: CATV CM CEC: CM	1000	304.8	68.0	30.9	14 AWG (solid) .064" BCCS 11.0Ω/M' 36.1Ω/km	.280	7.11	Duobond Plus* + 77% Aluminum Braid 3.8Ω/M' 12.5Ω/km	.400	10.16	75	83%	16.2	53.1	See Chart on page 6.92		
																			
Shorting Fold																			
Sweep tested 5 MHz to 1 GHz.																			


Aerial 80°C	9065M	—	1000	304.8	86.0	39.0	14 AWG (solid) .064" BCCS 11.0Ω/M' 36.1Ω/km	.280	7.11	Duobond Plus* + 77% Aluminum Braid 3.8Ω/M' 12.5Ω/km	.400 x .580	10.16 x 14.73	75	83%	16.2	53.1	See Chart on page 6.92		
----------------	--------------	---	------	-------	------	------	--	------	------	--	-------------------	---------------------	----	-----	------	------	---------------------------	--	--




Shorting Fold

.072" (1.8mm) galvanized steel messenger.


Gas-injected Foam Polyethylene Insulation • Polyethylene Jacket (Black or Orange)

Burial 80°C	9764	—	1000	304.8	60.0	27.2	14 AWG (solid) .064" BCCS 11.0Ω/M' 36.1Ω/km	.280	7.11	Duobond Plus* + 77% Aluminum Braid 3.8Ω/M' 12.5Ω/km	.400	10.16	75	83%	16.2	53.1	See Chart on page 6.92		
																			
Shorting Fold																			
Sweep tested 5 MHz to 1 GHz.																			

Series 11 • 14 AWG Solid .064" Bare Copper-covered Steel Conductor • Duobond® III + Aluminum Braid Shield (77% Coverage)**Gas-injected Foam Polyethylene Insulation • Black PVC Jacket**

Aerial 80°C	7983A <small>new</small>	—	1000	304.8	89.0	40.4	14 AWG (solid) .064" BCCS 11.0Ω/M' 36.1Ω/km	.280	7.11	Duobond III* + 77% Aluminum Braid 4.0Ω/M' 13.1Ω/km	.400 x .580	10.16 x 14.73	75	83%	16.2	53.1	See Chart on page 6.92		
																			
CoreGuard®																			
.072" (1.8mm) galvanized steel messenger.																			

Gas-injected Foam Polyethylene Insulation • Polyethylene Jacket (Black or Orange)

Burial 80°C	7984A <small>new</small>	—	1000	304.8	57.0	25.9	14 AWG (solid) .064" BCCS 11.0Ω/M' 36.1Ω/km	.280	7.11	Duobond III* + 77% Aluminum Braid 4.0Ω/M' 13.1Ω/km	.400	10.16	75	83%	16.2	53.1	See Chart on page 6.92		
																			
CoreGuard																			
Sweep tested 5 MHz to 1 GHz.																			

BCCS = Bare Copper-covered Steel • DCR = DC Resistance

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**.

*Duobond Plus = Bonded Duofoil® (100% coverage) + aluminum braid (67% coverage) + shorting fold.

Duobond III = Bonded Duofoil (100% coverage) + aluminum braid (67% coverage) + Duofoil (100% coverage).

Broadband Coax

CATV Cables

Series 11


Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

Series 11 • 14 AWG Solid .064" Bare Copper-covered Steel Conductor • Duobond® IV Quad Shield (60% and 40% Coverage)**Gas-injected Foam Polyethylene Insulation • Black PVC Jacket**

80°C	1617A	NEC: CATV CM CEC: CM	1000	304.8	67.0	30.5	14 AWG (solid) .064" BCCS 11.0Ω/M' 36.1Ω/km	.280	7.11	Duobond IV* 60% & 40% Aluminum Braids 3.0Ω/M' 9.8Ω/km	.407	10.34	75	83%	16.2	53.1	See Chart on page 6.92		
Sweep tested 5 MHz to 1 GHz.																			




80°C	1619AM	—	1000	304.8	84.0	38.2	14 AWG (solid) .064" BCCS 11.0Ω/M' 36.1Ω/km	.280	7.11	Duobond IV* 60% & 40% Aluminum Braids 3.0Ω/M' 9.8Ω/km	.407 x .560	10.34 x 14.22	75	83%	16.2	53.1	See Chart on page 6.92		
Sweep tested 5 MHz to 1 GHz.																			



.072" (1.8mm) galvanized steel messenger.

80°C	1620AM	—	1000	304.8	87.0	39.5	14 AWG (solid) .064" BCCS 11.0Ω/M' 36.1Ω/km	.280	7.11	Duobond IV* 60% & 40% Aluminum Braids 3.0Ω/M' 9.8Ω/km	.407 x .560	10.34 x 14.22	75	83%	16.2	53.1	See Chart on page 6.92		
Sweep tested 5 MHz to 1 GHz.																			




CoreGuard®

.072" (1.8mm) galvanized steel messenger.

Gas-injected Foam Polyethylene Insulation • Polyethylene Jacket (Black or Orange)

Burial 80°C	1618A	—	1000	304.8	61.0	27.7	14 AWG (solid) .064" BCCS 11.0Ω/M' 36.1Ω/km	.280	7.11	Duobond IV* 60% & 40% Aluminum Braids 3.0Ω/M' 9.8Ω/km	.407	10.34	75	83%	16.2	53.1	See Chart on page 6.92		
Sweep tested 5 MHz to 1 GHz.																			



CoreGuard®

Series 11 • 14 AWG Solid .064" BCCS Conductors • Duofoil® (100% Coverage) + TC Braid Shields (60% and 40% Coverage)**Plenum • Foam FEP Teflon Insulation • Snow Beige FEP Jacket**

200°C	1153A	NEC: CMP CL2P CEC: CMP FT6	500	152.4	52.5	23.9	14 AWG (solid) .064" BCCS 11.0Ω/M' 36.1Ω/km	.280	7.11	(2) Duofoil Shields + (2) TC BCCS 1.8Ω/M' 5.9Ω/km	.387	9.83	75	82%	16.2	53.1	1	.2	.7
Sweep tested 5 MHz to 400 MHz.																			
10 4 1.3																			
50 1.2 3.9																			
100 1.7 5.6																			
200 2.5 8.2																			
400 3.5 11.5																			
700 4.6 15.1																			
900 5.3 17.4																			
1000 5.6 18.4																			



BCCS = Bare Copper-covered Steel • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • TC = Tinned Copper

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**.

* Duobond IV = Bonded Duofoil (100% coverage) + aluminum braid (67% coverage) + Duofoil (100% coverage) + aluminum braid (46% coverage).

Teflon is a DuPont trademark.

BELDENFor more information, contact **Belden Technical Support: 1-800-BELDEN-1 • www.belden.com****Belden114@CableCon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr**


DBS Cable

Series 6


Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

Series 6 • 18 AWG Solid .040" Bare Copper or Bare Copper-covered Steel Conductor (see below) • Duobond® II + Aluminum Braid Shield (60% Coverage)


Gas-injected Foam Polyethylene Insulation • PVC Jacket (Black, Gray, White or Neutral)

80°C 	1829A	NEC: CATV CM CEC: CM	U-1000†	U-304.8	29.0	13.2	18 AWG (solid) .040" BCCS 28.0Ω/M' 91.9Ω/km	.180	4.57	Duobond II* + 60% Aluminum Braid 9.0Ω/M' 29.5Ω/km	.270	6.86	75	83%	16.2	53.1	5	.5	1.6
			1000†	304.8	29.0	13.2											55	1.4	4.6
																	211	2.6	8.5
																	500	4.1	13.5
																	750	5.1	16.7
																	862	5.5	18.0
																	1000	6.0	19.7
																	1450	7.8	25.6
																	1800	8.6	28.2
																	2250	9.8	32.2

†Final put-up length may vary ±10% for spools, ±5% for unreel cartons.


80°C 	1829AC	NEC: CATV CM CEC: CM	U-1000 [▲]	U-304.8	27.0	12.3	18 AWG (solid) .040" BCAC 6.4Ω/M' 21.0Ω/km	.180	4.57	Duobond II* + 60% Aluminum Braid 9.0Ω/M' 29.5Ω/km	.270	6.86	75	83%	16.2	53.1	5	.5	1.6
			1000 [▲]	304.8	27.0	12.3											55	1.4	4.6
																	211	2.6	8.5
																	500	4.1	13.5
																	750	5.1	16.7
																	862	5.5	18.0
																	1000	6.0	19.7
																	1450	7.8	25.6
																	1800	8.6	28.2
																	2250	9.8	32.2


[▲]U-1000 ft. put-up available in Black, White or Gray only. 1000 ft. available in White or Black only.

80°C 	1829R <small>new</small>	NEC: CATVR, CMR CEC: CMG FT4	U-1000*	U-304.8	29.0	13.2	18 AWG (solid) .040" BCCS 28.0Ω/M' 21.0Ω/km	.180	4.57	Duobond II* + 60% Aluminum Braid 9.0Ω/M' 29.5Ω/km	.270	6.86	75	83%	16.2	53.1	5	.5	1.6
																	55	1.4	4.6
																	211	2.6	8.5
																	500	4.1	13.5
																	750	5.1	16.7
																	862	5.5	18.0
																	1000	6.0	19.7
																	1450	7.8	25.6
																	1800	8.6	28.2
																	2250	9.8	32.2


*U-1000 ft. put-up not available in Neutral.

Gas-injected Foam Polyethylene Insulation • Black Polyethylene Jacket

Burial 80°C 	1829B	—	1000	304.8	26.0	11.8	18 AWG (solid) .040" BCCS 28.0Ω/M' 91.9Ω/km	.180	4.57	Duobond II* + 60% Aluminum Braid 9.0Ω/M' 29.5Ω/km	.270	6.86	75	83%	16.2	53.1	5	.5	1.6
																	55	1.4	4.6
																	211	2.6	8.5
																	500	4.1	13.5
																	750	5.1	16.7
																	862	5.5	18.0
																	1000	6.0	19.7
																	1450	7.8	25.6
																	1800	8.6	28.2
																	2250	9.8	32.2

Burial 80°C 	1829BC	—	1000	304.8	27.0	12.3	18 AWG (solid) .040" BCAC 6.4Ω/M' 21.0Ω/km	.180	4.57	Duobond II* + 60% Aluminum Braid 9.0Ω/M' 29.5Ω/km	.270	6.86	75	83%	16.2	53.1	5	.5	1.6
																	55	1.4	4.6
																	211	2.6	8.5
																	500	4.1	13.5
																	750	5.1	16.7
																	862	5.5	18.0
																	1000	6.0	19.7
																	1450	7.8	25.6
																	1800	8.6	28.2
																	2250	9.8	32.2

Plenum • Foam FEP Insulation • Natural Flamarrest® Jacket

75°C 	1829P <small>new</small>	NEC: CATVP, CMP CEC: CMP FT6	U-1000	U-304.8	27.0	12.3	18 AWG (solid) .040" BCCS 28.0Ω/M' 91.9Ω/km	.170	4.32	Duobond II* + 60% Aluminum Braid 9.0Ω/M' 29.5Ω/km	.235	5.97	75	83%	16.3	53.4	1	.3	1.0
			1000	304.8	27.0	12.3											10	.7	2.2
																	50	1.5	4.9
																	100	2.1	6.9
																	200	3.0	9.8
																	400	4.4	14.4
																	700	6.1	20.0
																	900	7.2	23.6
																	1000	7.6	24.9
																	1450	9.6	31.5

BC = Bare Copper • BCAC = Bare Copper Anti-corrosion • BCCS = Bare Copper-covered Steel • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene


*Duobond II = Bonded Duofoil® (100% coverage) + aluminum braid (67% coverage).

DBS Cable

Series 6


Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

Series 6 • 18 AWG Solid .040" Bare Copper-covered Steel Conductor • Duobond® II + Aluminum Braid Shield (60% Coverage)**Gas-injected Foam Polyethylene Insulation • Black Polyethylene Jacket**

 CoreGuard®	Burial 80°C	1843A	—	1000	304.8	64.0	29.1	18 AWG (solid)	.180	4.57	Duobond II*	.273	6.93	75	83%	16.2	53.1	5	.5	1.6			
				28.0Ω/M'	91.9Ω/km	+ 60%	X	X	Aluminum	.750	19.05	BCCS								55	1.4	4.6	
																					211	2.6	8.5
																					500	4.1	13.5
																					750	5.1	16.7
																					862	5.5	18.0
																					1000	6.0	19.7
																					1450	7.8	25.6
																					1800	8.6	28.2
																					2250	9.8	32.2


.045" (1.14mm) copper-covered steel static ground.
Suitable for Outdoor and Direct Burial applications.

HDTV Series 6 • 18 AWG Solid .040" Bare Copper Conductor • Duobond + Aluminum Braid Shields (77% and 80% Coverage)**Gas-injected Foam Polyethylene Insulation • PVC Jacket (Black or White)**

 Shorting Fold	80°C	7915A	NEC:	U-500	U-152.4	16.5	7.5	18 AWG (solid)	.180	4.57	Duobond Plus**	.275	6.99	75	83%	16.2	53.1	5	.5	1.6			
			CATV CM	500	152.4	18.0	8.2	.040"												55	1.4	4.6	
			CEC:	U-1000	U-304.8	32.0	14.5														211	2.6	8.5
			CM	1000	304.8	32.0	14.5														500	4.1	13.5
																					750	5.1	16.7
																					862	5.5	18.0
																					1000	6.0	19.7
																					1450	7.8	25.6
																					1800	8.6	28.2
																					2250	9.8	32.2

Sweep tested 950 MHz to 2.25 GHz.

Series 6 • 18 AWG Solid .040" Bare Copper Conductor • Duobond + Aluminum Braid Shields (60% and 40% Coverage)**Gas-injected Foam Polyethylene Insulation • PVC Jacket (Black or White)**

	80°C	7916A	NEC:	U-500	U-152.4	18.5	8.4	18 AWG (solid)	.180	4.57	Duobond IV*	.298	7.57	75	83%	16.2	53.1	5	.5	1.6			
			CATV CM	500	152.4	19.5	8.9	.040"												55	1.4	4.6	
			CEC:	U-1000	U-304.8	36.0	16.3														211	2.6	8.5
			CM	1000	304.8	35.0	15.9														500	4.1	13.5
																					750	5.1	16.7
																					862	5.5	18.0
																					1000	6.0	19.7
																					1450	7.8	25.6
																					1800	8.6	28.2
																					2250	9.8	32.2

BC = Bare Copper • BCCS = Bare Copper-covered Steel • DCR = DC Resistance

*Duobond II = Bonded Duofoil® (100% coverage) + aluminum braid (67% coverage).

Duobond Plus = Bonded Duofoil (100% coverage) + aluminum braid (67% coverage) + shorting fold.

Duobond IV = Bonded Duofoil (100% coverage) + aluminum braid (67% coverage) + Duofoil (100% coverage) + aluminum braid (46% coverage).