

Precision Video Cable for Analog and Digital

Sub-Miniature RG-59/U Type



Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

25 AWG Stranded (19x37) .021" Bare Copper Conductor • Duofoil® (100% Coverage) + Tinned Copper Braid Shield (95% Coverage)

Gas-injected Foam HDPE Insulation • PVC Jacket (Available in 10 colors)*

75°C	1865A	NEC: CMR CEC: CMG FT4	1000	304.8	14.0	6.4	25 AWG (19x37) .021" BC 27.4Ω/M' 89.9Ω/km	.094	2.39	Duofoil + 95% TC Braid 5.4Ω/M' 17.7Ω/km	.150	3.81	75	82%	16.5	54.1	1	.5	1.5
																	3.6	1.0	3.1
																	10	1.6	5.2
																	71.5	3.7	12.1
																	135	5.0	16.4
																	270	7.1	23.3
																	360	8.2	26.9
																	540	10.1	33.1
																	720	11.8	38.7
																	750	12.0	39.4
																	1000	13.9	45.6
																	1500	17.0	55.8
																	2250	20.8	68.2
																	3000	24.0	78.7

100% Sweep tested. 5 MHz to 3 GHz.

23 AWG Solid .023" Bare Copper Conductor • Duofoil (100% Coverage) + Tinned Copper Braid Shield (95% Coverage)

Gas-injected Foam HDPE Insulation • PVC Jacket (Available in 10 colors)*

SDI/HDTV Digital Video 75°C	1855A	NEC: CMR CEC: CMG FT4	500 [▲]	152.4	9.0	4.1	23 AWG (solid) .023" BC 20.1Ω/M' 65.9Ω/km	.102	2.59	Duofoil + 95% TC Braid 7.6Ω/M' 24.9Ω/km	.159	4.03	75	82%	16.3	53.5	1	.4	1.3
																	3.6	.8	2.6
																	10	1.2	3.9
																	71.5	3.1	10.0
																	135	3.8	12.5
																	270	5.4	17.7
																	360	6.2	20.3
																	540	7.7	25.3
																	720	9.5	31.1
																	750	9.6	31.5
																	1000	10.5	34.4
																	1500	13.0	42.6
																	2250	16.0	52.5
																	3000	18.5	60.7

Also available in multiples, bundled.

See 7787A through 7792A.

100% Sweep tested. 5 MHz to 3 GHz.

*500 ft. put-up available in Black only.

BC = Bare Copper • DCR = DC Resistance • HDPE = Foam High-density Polyethylene • TC = Tinned Copper

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**. Request quotations of RG/U cables not listed.

*Available in Brown, Red, Orange, Yellow, Green, Blue, Purple, Gray, White or Black.

Precision Video Cable for Analog and Digital

RG-59/U Type



Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

23 AWG Stranded (7x32) .023" Bare Compacted Copper* • Tinned Copper Braid Shield (95% Coverage)

Polyethylene Insulation • Black Polyethylene Jacket

80°C	8279	—	500	152.4	13.0	5.9	23 AWG (7x32)	.146	3.71	TC + 95% Shield	.220	5.59	75	66%	21.0	68.9	1	.4	1.1
			1000	304.8	29.0	13.2	.023" BCC			19.1Ω/M'							3.6	.6	2.0
							62.6Ω/km			4.5Ω/M'							10.0	1.2	3.9
										14.8Ω/km							71.5	3.3	10.8
																	135	4.7	15.4
																	270	6.8	22.3
																	360	8.0	26.2
																	540	9.9	32.5
																	720	11.6	38.0
																	750	11.9	39.0
																	1000	13.8	45.3



23 AWG Solid .022" Bare Copper Conductor • Duofoil® (100% Coverage) + Tinned Copper Braid Shield (95% Coverage)

Polyethylene Insulation • Black Polyethylene Jacket

80°C	9209	—	U-500	U-152.4	15.0	6.8	23 AWG (solid)	.146	3.71	Duofoil + 95% TC Braid	.220	5.59	75	66%	21.0	68.9	1	.4	1.2
			U-1000	U-304.8	29.0	13.2	.022" BC			20.4Ω/M'							3.6	.5	1.8
							66.9Ω/km			4.5Ω/M'							10.0	1.2	3.8
										14.8Ω/km							71.5	2.9	9.5
																	135	4.0	13.0
																	270	5.6	18.4
																	360	6.6	21.5
																	540	8.3	27.2
																	720	9.7	31.7
																	750	9.9	32.5
																	1000	11.6	38.0



Flame-retardant Semi-foam Polyethylene Insulation • Black PVC Jacket

UL AWM Style 1354 (30V 75°C)	9209A	NEC: CMR CEC: CMG FT4	U-1000	U-304.8	35.0	15.9	23 AWG (solid)	.146	3.71	Duofoil + 95% TC Braid	.220	5.59	75	66%	20.5	67.2	1	.4	1.2
							.022" BC			20.4Ω/M'							3.6	.5	1.8
							66.9Ω/km			4.5Ω/M'							10.0	1.2	3.8
										14.8Ω/km							71.5	2.9	9.5
																	135	4.0	13.0
																	270	5.6	18.4
																	360	6.6	21.5
																	540	8.6	28.3
																	720	10.1	33.2
																	750	10.4	34.1
																	1000	12.8	41.9



BC = Bare Copper • BCC = Bare Compacted Copper • DCR = DC Resistance • HDPE = High-density Polyethylene • TC = Tinned Copper

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. **1-800-BELDEN-1**. Request quotations of RG/U cables not listed.

*Compacted conductor combines impedance uniformity of solid conductors and "nick-resistance" of stranded conductor.

Precision Video Cable for Analog and Digital

RG-59/U Type



Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

20 AWG Solid .032" Bare Copper Conductor • Duofoil® (100% Coverage) + Tinned Copper Braid Shield (95% Coverage)

Gas-injected Foam HDPE Insulation • PVC Jacket (Available in 10 colors)*

SDI/HDTV	1505A	NEC:	500 [▲]	152.4	17.0	8.0	20 AWG	.145	3.68	Duofoil	.233	5.92	75	83%	16.3	53.5	1	.3	1.0	
Digital Video		CMR:	1000	304.8	35.0	16.4	(solid)			+ 95%										
75°C		CEC:	5000 [▼]	1524.0	165.0	74.8	.032"			TC Braid								3.6	.6	1.8
		CMG FT4					10.0Ω/M'			3.8Ω/M'								10	.9	2.9
							32.8Ω/km			12.5Ω/km								71.5	2.1	6.9

For Plenum version of 1505A, see 1506A.
Also available in bundled versions. See 7794A through 7798A.
100% Sweep tested. 5 MHz to 3 GHz.

▲500 ft. put-up available in Black, Red or Blue only.
▼5000 ft. put-up may vary in length by -0 to +10%.
•1000 ft. and 5000 ft. put-ups available in all ten colors: Black, Brown, Red, Orange, Yellow, Green, Blue, Purple, Gray or White.

22 AWG Stranded (7x29) .031" Bare Compacted Copper Conductor* • Tinned Copper/Bare Copper Double Braid Shield (95% Coverage)

Gas-injected Foam HDPE Insulation • PVC Jacket (Matte Black, Red, Green, Blue, Yellow, Orange, White or Purple)

High-Flex	1505F	NEC:	1000	304.8	45.0	20.4	22 AWG	.145	3.68	TC Double	.242	6.15	75	80%	17.0	55.7	1	.2	.7
SDI/HDTV		CM					(7x29)			Braid							3.6	.5	1.6
Video Patch		CEC:					.031"			95% Shield							10	.9	2.9
75°C		CM					12.2Ω/M'			BCC							71.5	2.5	8.2
							40.0Ω/km			Coverage							135	3.5	11.5

100% Sweep tested. 5 MHz to 3 GHz.

*Compacted conductor combines impedance uniformity of solid conductors and "nick-resistance" of stranded conductor.

20 AWG Solid .032" Bare Copper Conductor • Duofoil (100% Coverage) + Tinned Copper Braid Shield (95% Coverage)

Plenum • Foam FEP Insulation • Flamarest® Jacket (Available in 10 colors)*

SDI/HDTV	1506A	NEC:	500 ^{†*}	152.4	14.5	6.6	20 AWG	.133	3.38	Duofoil	.196	4.93	75	84%	16.1	52.8	1	.3	1.0	
Digital Video		CMP:	1000 ^{†*}	304.8	29.0	13.2	(solid)			+ 95%										
75°C		CEC:					.032"			TC Braid								3.6	.6	2.0
		CMF FT6					10.0Ω/M'			3.8Ω/M'								10	1.1	3.4
							32.8Ω/km			10.5Ω/km								71.5	2.3	7.4

100% Sweep tested. 5 MHz to 3 GHz.

Suitable for Outdoor and Direct Burial applications.

†500 ft. put-up available in Black or Natural only.

*1000 ft. put-up available in all ten colors: Black, Brown, Red, Orange, Yellow, Green, Blue, Purple, Gray or Natural.

20 AWG Solid .031" Bare Copper Conductor • Tinned Copper/Bare Copper Double Braid Shield (98% Coverage)

Polyethylene Insulation • Gray PVC Jacket

60°C	9231	NEC:	500	152.4	39.0	17.7	20 AWG	.198	5.03	TC Double	.305	7.75	75	66%	21.0	68.9	1	.3	1.0	
VW-1		CMH:	1000	304.8	76.0	34.5	(solid)			Braid										
		CEC:					.031"			98% Shield								10.0	.8	2.6
		CMH FT1					9.9Ω/M'			Coverage								71.5	2.0	6.6
							32.5Ω/km			3.6Ω/km								135	3.5	11.5

100% Sweep tested. 5 MHz to 850 MHz.

BC = Bare Copper • BCC = Bare Compacted Copper • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • HDPE = High-density Polyethylene • TC = Tinned Copper

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. 1-800-BELDEN-1. Request quotations of RG/U cables not listed.

†Final put-up length may vary ±10% for spools or reels, ±5% for Unreel cartons from length shown.



Precision Video Cable for Analog and Digital

RG-59/U Type



Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/100 Ft.	dB/100m

20 AWG Solid .031" Bare Copper Conductor • Tinned Copper/Bare Copper Double Braid Shield (98% Coverage) (continued)

Polyethylene Insulation • Clear Polyethylene Jacket																			
Indoor Use 80°C	9141	—	1000	304.8	73.0	33.2	20 AWG (solid)	.200	5.06	TC Double Braid	.305	7.75	75	66%	20.0	65.6	1	.3	1.0
							.031"			98% Shield Coverage							3.6	.5	1.6
							BC										10.0	.8	2.6
							9.9Ω/M'										71.5	2.0	6.6
							32.5Ω/km										135	3.5	11.5
																	270	4.3	14.1
																	360	5.0	16.4
																	540	6.2	20.3
																	720	7.2	23.6
																	750	7.4	24.3
																	1000	9.1	29.8



20 AWG Solid .031" Bare Copper Conductor • Tinned Copper/Bare Copper Double Braid Shield (98% Coverage)

Polyethylene Insulation • Polyethylene Jacket (Available in Red, Yellow, Green, Blue, White, Orange or Black)																			
80°C	8281	—	500 [▲]	152.4	37.5	17.8	20 AWG (solid)	.198	5.03	TC Double Braid	.305	7.75	75	66%	21.0	68.9	1	.3	.8
			1000	304.8	74.0	33.6	.031"			98% Shield Coverage							3.6	.5	1.8
							BC										10.0	.8	2.6
							9.9Ω/M'										71.5	2.1	6.9
							32.5Ω/km										135	3.0	9.8
																	270	4.3	14.1
																	360	5.1	16.6
																	540	6.3	20.7
																	720	7.4	24.3
																	750	7.6	24.9
																	1000	9.2	30.2

*500 ft. put-up not available in White.



20 AWG Stranded (7x29) .031" Bare Compacted Copper Conductor* • Tinned Copper/Bare Copper Double Braid Shield (98% Coverage)

Flame-retardant Semi-foam Polyethylene Insulation • PVC Jacket (Available in 9 colors)*																			
UL AWM Style 1354 (30V 80°C)	8281B	NEC: CMR CEC: CMG FT4	1000	304.8	84.0	38.1	20 AWG (solid)	.198	5.03	TC Double Braid	.305	7.75	75	66%	21.0	68.9	1	.3	.8
							.031"			98% Shield Coverage							3.6	.5	1.8
							BC										10.0	.8	2.6
							9.9Ω/M'										71.5	2.1	6.9
							32.5Ω/km										135	3.0	9.8
																	270	4.4	14.4
																	360	5.1	16.6
																	540	6.6	21.5
																	720	7.8	25.4
																	750	8.0	26.2
																	1000	10.2	33.5

*8281B available in Red, Orange, Yellow, Green, Blue, Purple, Gray, White or Black.



22 AWG Stranded (7x29) .031" Bare Compacted Copper Conductor* • Tinned Copper/Bare Copper Double Braid Shield (98% Coverage)

Polyethylene Insulation • PVC Jacket (Matte Red, Blue, Green, Gray or Black)																			
High-Flex 60°C	8281F	—	500 [*]	152.4	34.5	15.7	22 AWG (7x29)	.193	4.90	TC Double Braid	.305	7.75	75	66%	21.0	68.9	1	.3	.9
			1000	304.8	67.0	30.4	.031"			98% Shield Coverage							3.6	.5	1.7
							BCC										10.0	.9	2.9
							12.2Ω/M'										71.5	2.5	8.0
							40.0Ω/km										135	3.6	11.6
																	270	5.1	16.7
																	360	6.0	19.7
																	540	7.4	24.3
																	720	8.7	28.5
																	750	8.9	29.2
																	1000	10.5	34.4

*500 ft. put-up available in Black only.



20 AWG Solid .032" Bare Copper Conductor • Tinned Copper/Bare Copper Double Braid Shield (98% Coverage)

Plenum • FEP Insulation • Black Fluorocopolymer Jacket																			
150°C	88281	NEC: CMP CEC: CMP FT6	500	152.4	44.5	20.2	20 AWG (solid)	.185	4.70	TC Double Braid	.271	6.88	75	71%	19.0	62.4	1	.2	.7
			1000	304.8	86.0	39.1	.032"			98% Shield Coverage							3.6	.5	1.6
							BC										10.0	.8	2.6
							9.9Ω/M'										71.5	2.3	7.5
							32.5Ω/km										135	3.3	10.8
																	270	5.1	16.7
																	360	6.1	20.0
																	540	8.0	26.2
																	720	9.7	31.8
																	750	10.0	32.8
																	1000	12.3	40.3

Suitable for Outdoor and Direct Burial applications.

BC = Bare Copper • BCC = Bare Compacted Copper • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • HDPE = High-density Polyethylene • TC = Tinned Copper

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. 1-800-BELDEN-1. Request quotations of RG/U cables not listed.

*Compacted conductor combines impedance uniformity of solid conductors and "nick-resistance" of stranded conductor.



For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com

Belden114@CableCon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr

Precision Video Cable for Analog and Digital

RG-6/U and RG-11/U Type



Description	Part No.	UL NEC/ C(UL) CEC Type	Standard Lengths		Standard Unit Weight		Conductor (stranding) Diameter Nom. DCR	Nominal Core OD		Shielding Materials Nom. DCR	Nominal OD		Nom. Imp. (Ω)	Nom. Vel. of Prop.	Nominal Capacitance		Nominal Attenuation		
			Ft.	m	Lbs.	kg		Inch	mm		Inch	mm			pF/Ft.	pF/m	MHz	dB/ 100 Ft.	dB/ 100m

RG-6/U Type • 18 AWG Solid .040" Bare Copper Conductor • Duofoil® (100% Coverage) + Tinned Copper Braid Shield (95% Coverage)

Gas-injected Foam HDPE Insulation • PVC Jacket (Available in 10 colors)*

SDI/HDTV	1694A	NEC:	500 [▲]	152.4	20.5	9.3	18 AWG	.180	4.57	Duofoil	.275	6.99	75	82%	16.2	53.1	1	.2	.8
Digital Video		CMR	1000	304.8	45.0	20.5	(solid)			+ 95%							3.6	.5	1.5
75°C		CEC:	4500	1371.6	202.5	91.9	.040"			TC Braid							10	.7	2.4
		CMG FT4								2.8Ω/M'	For Plenum version of 1694A, see 1695A.						71.5	1.6	5.2
							BC			9.2Ω/km							135	2.1	6.9
							6.4Ω/M'										270	3.0	9.7
							21.0Ω/km										360	3.4	11.3
																	540	4.3	13.9
																	720	4.9	16.1
																	750	5.0	16.4
																	1000	5.9	19.3
																	1500	7.3	24.0
																	2250	9.1	30.0
																	3000	10.7	35.0

*500 ft. put-up available in Black only.

Gas-injected Foam HDPE Insulation • Black Low-Smoke, Zero-Halogen Jacket

SDI/HDTV	1694SB	NEC:	1000	304.8	46.0	20.9	18 AWG	.180	4.57	Duofoil	.274	6.96	75	82%	16.2	53.1	1	.2	.8
Digital Video		CMG-LS					(solid)			+ 95%							3.6	.5	1.5
75°C		CEC:					.040"			TC Braid							10	.7	2.4
		CMG-LS FT4								2.8Ω/M'							71.5	1.6	5.2
		Limited Smoke					BC			9.2Ω/km							135	2.1	6.9
							6.4Ω/M'										270	3.0	9.7
							21.0Ω/km										360	3.4	11.3
																	540	4.3	13.9
																	720	4.9	16.1
																	750	5.0	16.4
																	1000	5.9	19.3
																	1500	7.3	24.0
																	2250	9.1	30.0
																	3000	10.7	35.0

Plenum • Foam FEP Insulation • Flammarrest® Jacket (Available in 10 colors)**

SDI/HDTV	1695A	NEC:	500 [†] *	152.4	20.5	9.3	18 AWG	.170	4.32	Duofoil	.234	5.94	75	82%	16.2	53.1	1	.2	.8
Digital Video		CMP	1000	304.8	45.0	20.5	(solid)			+ 95%							3.6	.5	1.5
75°C		CEC:					.040"			TC Braid							10	.8	2.5
		CMP FT6								2.8Ω/M'							71.5	1.8	5.8
							BC			9.2Ω/km							135	2.4	7.9
							6.4Ω/M'										270	3.4	11.2
							21.0Ω/km										360	4.0	13.1
																	540	5.2	17.1
																	720	6.1	20.0
																	750	6.2	20.3
																	1000	7.3	24.0
																	1500	9.2	30.2
																	2250	11.6	38.0
																	3000	13.7	44.9

*500 ft. put-up available in Black or Natural only. Black jacket suitable for Indoor, Outdoor and Aerial applications.

RG-11/U Type • 14 AWG Solid .064" Bare Copper Conductor • Duofoil (100% Coverage) + Tinned Copper Braid Shield (95% Coverage)

Gas-injected Foam HDPE Insulation • PVC Jacket (Available in 10 colors)*

SDI/HDTV	7731A	NEC:	500 [▼]	152.4	46.5	21.1	14 AWG	.280	7.11	Duofoil	.405	10.3	75	85%	16.0	52.4	1	.2	.5
Digital Video		CMR	1000	304.8	95.0	43.1	(solid)			+ 95%							10	.5	1.5
75°C		CEC:	4000	1219.2	388.0	176.2	.064"			TC Braid							71.5	1.1	3.6
		CMG FT4								1.5Ω/M'							135	1.5	4.8
							BC			4.9Ω/km							270	2.1	6.9
							2.5Ω/M'										360	2.5	8.0
							8.2Ω/km										540	3.1	10.0
																	720	3.6	11.7
																	750	3.7	12.0
																	1000	4.3	14.1
																	1500	5.5	18.0
																	2250	6.9	22.6
																	3000	8.2	26.9

*500 ft. put-up available in Red or Black only.

Plenum • Foam FEP Insulation • Fluorocopolymer Jacket (Available in 10 colors)**

SDI/HDTV	7732A	NEC:	500 [•]	152.4	45.0	20.5	14 AWG	.274	6.96	Duofoil	.348	8.84	75	83%	16.3	53.5	1	.2	.5
Digital Video		CMP	1000	304.8	90.0	40.9	(solid)			+ 95%							10	.4	1.3
150°C		CEC:	2000 ⁺	609.6	176.0	80.0	.064"			TC Braid							71.5	1.2	4.1
		CMP FT6								1.6Ω/M'							135	1.8	5.8
							BC			5.3Ω/km							270	2.6	8.5
							2.5Ω/M'										360	3.1	10.2
							8.2Ω/km										540	3.9	12.8
																	720	4.6	15.0
																	750	4.7	15.4
																	1000	5.5	18.0
																	1500	6.9	22.7
																	2250	9.2	30.2
																	3000	10.2	33.5

*500 ft. put-up available in Black or Natural only.

**2000 ft. put-up available in Natural only.

Suitable for Outdoor and Direct Burial applications.

BC = Bare Copper • DCR = DC Resistance • FEP = Fluorinated Ethylene Propylene • HDPE = High-density Polyethylene • TC = Tinned Copper

Contact the Belden Customer Service Department for a Comprehensive Connector Cross Reference. 1-800-BELDEN-1. Request quotations of RG-U cables not listed.

* Non-Plenum Available in Black, Brown, Red, Orange, Yellow, Green, Blue, Purple, Gray or White.

** Plenum Available in Black, Brown, Red, Orange, Yellow, Green, Blue, Purple, Gray or Natural.

† Final put-up length may vary ±10% for spools or reels and ±5% for Unreel cartons from length shown.

BELDEN

For more information, contact Belden Technical Support: 1-800-BELDEN-1 • www.belden.com

Belden114@CableCon.kr / 0707-434-7704 / Fax. 02-744-0909 / www.CableCon.co.kr