


**2-Conductor**


UL/CSA Types: SJ, SJO, SJTOW, SO

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm


**SJ Rubber Jacket** • Smooth Jacket • UL/CSA Listed**300V, 60°C** • Paper Tape Separator • Color Code: Black, White

	<b>8478</b>	250	76.2	10.8	4.9	Black	18 (42x34) BC	.032	.81	.035	.89	.290	7.37
		1000	304.8	48.0	21.8								
	<b>8472</b>	250	76.2	12.8	5.8	Black	16 (65x34) BC	.033	.84	.035	.89	.315	8.00


**SJO Oil-Resistant Rubber Jacket** • Smooth Jacket • UL/CSA Listed**300V, 90°C** • Paper Tape Separator • Color Code: Black, White

	<b>19227</b>	250 <sup>†</sup>	76.2	11.0	5.0	Black	18 (16x30) BC	.031	.79	.035	.89	.290	7.37
	<b>19228</b>	250 <sup>†</sup>	76.2	13.5	6.1	Black	16 (26x30) BC	.031	.79	.035	.89	.315	8.00


**SJTOW Belflex® Matte Black Premium PVC** • Smooth Jacket • UL/CSA Listed**300V, 105°C** • Paper Tape Separator • International Color Code: Light Blue, Brown

	<b>19506*</b>	250	76.2	11.0	5.0	Matte Black	18 (42x34) BC	.032	.81	.035	.89	.290	7.34													
														<b>19507*</b>	250	76.2	13.5	6.1	Matte Black	16 (65x34) BC	.033	.84	.037	.94	.319	8.10
														<b>19508*</b>	250	76.2	17.0	7.7	Matte Black	14 (41x30) BC	.033	.84	.032	.81	.348	8.84

**SO Oil-Resistant Rubber Jacket** • Smooth Jacket • UL/CSA Listed**600V, 90°C** • Cotton Serve Separator • Color Code: Black, White

	<b>19204</b>	250 <sup>†</sup>	76.2	18.5	8.4	Black	18 (42x34) BC	.032	.81	.065	1.65	.360	9.14													
														<b>19203</b>	250 <sup>†</sup>	76.2	19.0	8.6	Black	16 (65x34) BC	.033	.84	.065	1.65	.385	9.78

**600V, 90°C** • Paper Tape Separator • Color Code: Black, White

	<b>19201</b>	250 <sup>†</sup>	76.2	52.8	24.0	Black	12 (65x30) BC	.051	1.30	.100	2.54	.610	15.49
--	--------------	------------------	------	------	------	-------	---------------------	------	------	------	------	------	-------

BC = Bare Copper

\*These constructions are approved as water-resistant, oil-resistant and for outdoor use.

<sup>†</sup>Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.