


**2-Conductor**


UL/CSA Types: SJ, SJO, SJTOW, SO

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm


**SJ Rubber Jacket** • Smooth Jacket • UL/CSA Listed**300V, 60°C** • Paper Tape Separator • Color Code: Black, White

	<b>8478</b>	250	76.2	10.8	4.9	Black	18 (42x34) BC	.032	.81	.035	.89	.290	7.37
		1000	304.8	48.0	21.8								
	<b>8472</b>	250	76.2	12.8	5.8	Black	16 (65x34) BC	.033	.84	.035	.89	.315	8.00


**SJO Oil-Resistant Rubber Jacket** • Smooth Jacket • UL/CSA Listed**300V, 90°C** • Paper Tape Separator • Color Code: Black, White

	<b>19227</b>	250 <sup>†</sup>	76.2	11.0	5.0	Black	18 (16x30) BC	.031	.79	.035	.89	.290	7.37
	<b>19228</b>	250 <sup>†</sup>	76.2	13.5	6.1	Black	16 (26x30) BC	.031	.79	.035	.89	.315	8.00


**SJTOW Belflex® Matte Black Premium PVC** • Smooth Jacket • UL/CSA Listed**300V, 105°C** • Paper Tape Separator • International Color Code: Light Blue, Brown

	<b>VW-1</b>	<b>19506*</b>	250	76.2	11.0	5.0	Matte Black	18 (42x34) BC	.032	.81	.035	.89	.290	7.34
		<b>19507*</b>	250	76.2	13.5	6.1	Matte Black	16 (65x34) BC	.033	.84	.037	.94	.319	8.10
		<b>19508*</b>	250	76.2	17.0	7.7	Matte Black	14 (41x30) BC	.033	.84	.032	.81	.348	8.84

**SO Oil-Resistant Rubber Jacket** • Smooth Jacket • UL/CSA Listed**600V, 90°C** • Cotton Serve Separator • Color Code: Black, White

		<b>19204</b>	250 <sup>†</sup>	76.2	18.5	8.4	Black	18 (42x34) BC	.032	.81	.065	1.65	.360	9.14
		<b>19203</b>	250 <sup>†</sup>	76.2	19.0	8.6	Black	16 (65x34) BC	.033	.84	.065	1.65	.385	9.78
		<b>19202</b>	250 <sup>†</sup>	76.2	37.3	16.9	Black	14 (41x30) BC	.048	1.22	.085	2.16	.523	13.28

**600V, 90°C** • Paper Tape Separator • Color Code: Black, White

		<b>19201</b>	250 <sup>†</sup>	76.2	52.8	24.0	Black	12 (65x30) BC	.051	1.30	.100	2.54	.610	15.49

BC = Bare Copper

\*These constructions are approved as water-resistant, oil-resistant and for outdoor use.


<sup>†</sup>Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.

**2-Conductor**


UL/CSA Types: STOW, SV, SVT

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm


**STOW Belflex® Matte Black Premium PVC • Smooth Jacket • UL/CSA Listed****600V, 105°C • Paper Tape Separator • International Color Code: Light Blue, Brown**

	<b>19500*</b>	250	76.2	16.0	7.3	Matte Black	18 (42x34) BC	.032	.81	.070	1.78	.360	9.14
	<b>19501*</b>	250	76.2	18.8	8.5	Matte Black	16 (65x34) BC	.033	.84	.070	1.78	.386	9.80
	<b>19502*</b>	250	76.2	34.0	15.5	Matte Black	14 (41x30) BC	.049	1.24	.089	2.26	.524	13.31


**SV Rubber Jacket • Serrated Jacket • UL/CSA Listed****300V, 60°C • Cotton Serve Separator • Color Code: Black, White**

	<b>8452</b>	250	76.2	9.5	4.3	Black	18 (42x34) BC	.017	.43	.037	.94	.245	6.22
		U-500	U-152.4	18.5	8.4								
		500	152.4	17.0	7.7								
		U-1000	U-304.8	36.0	16.3								
		1000	304.8	38.0	17.3								

**SV Rubber Jacket • Smooth Jacket • UL/CSA Listed****300V, 60°C • Cotton Serve Separator • Color Code: Black, White**

	<b>19120</b>	250 <sup>†</sup>	76.2	8.8	4.0	Black	18 (42x34) BC	.017	.43	.037	.94	.245	6.22

**SVT PVC Jacket • Serrated Jacket • UL/CSA Listed****300V, 60°C • Paper Tape Separator • Color Code: Black, White**

	<b>19140</b>	250 <sup>†</sup>	76.2	8.8	4.0	Black, Gray	18 (42x34) BC	.018	.46	.036	.91	.243	6.17

BC = Bare Copper

\*These constructions are approved as water-resistant, oil-resistant and for outdoor use.


†Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.

**3-Conductor**


UL/CSA Types: SJTOW, STOW, SV, SVT

Description	Part No.	Standard Lengths		Standard Unit Weight		Jacket Color	Conductor AWG (stranding)	Nom. Insulation Thickness		Nom. Jacket Thickness		Nominal OD	
		Ft.	m	Lbs.	kg			Inch	mm	Inch	mm	Inch	mm


**SJTOW Belflex® Premium PVC** • Smooth Jacket • UL/CSA Listed**300V, 105°C** • Paper Tape Separator • International Color Code: Light Blue, Brown, Green/Yellow

	VW-1	<b>19509*</b>	250	76.2	14.0	6.4	Matte Black	18 (42x34) BC	.032	.81	.038	.97	.315	8.00
		<b>19510*</b>	250	76.2	17.5	7.9	Matte Black	16 (65x34) BC	.033	.84	.038	.97	.340	8.64
		<b>19511*</b>	250	76.2	23.8	10.8	Matte Black	14 (41x30) BC	.032	.81	.040	1.02	.380	9.65


**STOW Belflex Premium PVC** • Smooth Jacket • UL/CSA Listed**600V, 105°C** • Paper Tape Separator • International Color Code: Light Blue, Brown, Green/Yellow

	VW-1	<b>19503*</b>	250	76.2	19.0	8.6	Matte Black	18 (42x34) BC	.032	.81	.070	1.78	.380	9.65
		<b>19504*</b>	250	76.2	23.0	10.5	Matte Black	16 (65x34) BC	.033	.84	.070	1.78	.405	10.29
		<b>19505*</b>	250	76.2	42.5	19.3	Matte Black	14 (41x30) BC	.049	1.24	.089	2.26	.558	14.17


**SV Rubber Jacket** • Smooth Jacket • UL/CSA Listed**300V, 60°C** • Cotton Serve Separator • Color Code: Black, White, Green

		<b>8453</b>	100	30.5	4.9	2.2	Black	18 (41x34) TC	.018	.46	.036	.91	.256	6.50
			500	152.4	21.0	9.5								

**SVT PVC Jacket** • Serrated Jacket • UL/CSA Listed**300V, 60°C** • Paper Tape Separator • Color Code: Black, White, Green

		<b>19350</b>	250 <sup>†</sup>	76.2	10.8	4.9	Gray	18 (42x34) BC	.018	.46	.038	.97	.253	6.43

**SVT PVC Jacket** • Smooth Jacket • UL/CSA Listed**300V, 60°C** • Paper Tape Separator • International Color Code: Light Blue, Brown, Green/Yellow

		<b>19402</b>	250 <sup>†</sup>	76.2	12.3	5.6	Black	18 (42x34) BC	.018	.46	.034	.86	.253	6.43

BC = Bare Copper

\*These constructions are approved as water-resistant, oil-resistant and for outdoor use.

<sup>†</sup>Put-ups may contain more than one piece. Minimum length of any one piece is 50 ft.